



US005504467A

United States Patent [19]

[11] **Patent Number:** **5,504,467**

McColloch et al.

[45] **Date of Patent:** **Apr. 2, 1996**

[54] **CIRCUIT BREAKER WITH IMPROVED CONTACT ARM FOLLOWER SPRING ARRANGEMENT**

4,350,965	9/1982	Norden	335/189
4,382,240	5/1983	Kondo et al.	335/8
4,488,133	12/1984	McClellan et al. .	

[75] Inventors: **Rex J. McColloch**, Snellville; **Stephen D. Cella**, Stone Mountain; **Bernard DiMarco**, Lilburn, all of Ga.

Primary Examiner—Lincoln Donovan

[73] Assignee: **Siemens Energy & Automation, Inc.**, Alpharetta, Ga.

[57] **ABSTRACT**

A current limiting circuit breaker including a novel spring arrangement between the contact arms of the circuit breaker and the crossbar. The spring arrangement includes a single spring which holds the cam follower attached to each associated contact arm in contact with cam surfaces of the crossbar. The longitudinal axis of the spring is located within a plane passing through the longitudinal axis of the contact arm, wherein the plane is also perpendicular to the rotational axis of the contact arm. The cam surfaces and spring are configured to permit the contact arm to blow open under unacceptable fault conditions even though the crossbar remains stationary.

[21] Appl. No.: **413,745**

[22] Filed: **Mar. 30, 1995**

[51] **Int. Cl.⁶** **H01H 9/00**

[52] **U.S. Cl.** **335/172; 335/10; 335/190**

[58] **Field of Search** **335/8-10, 23-25, 335/167-176, 185-192**

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,342,974 8/1992 Nakano et al. 335/22

23 Claims, 3 Drawing Sheets




FIG. 1






FIG. 2





CIRCUIT BREAKER WITH IMPROVED CONTACT ARM FOLLOWER SPRING ARRANGEMENT

FIELD OF THE INVENTION

The present invention relates to the contact operating mechanism of a circuit breaker. In particular, the present invention relates to a new, improved and novel crossbar spring arrangement for connecting the contact arm to the cross bar which improves blow-open performance of the circuit breaker during short circuit conditions.

BACKGROUND OF THE INVENTION

It is recognized in the prior art that contact operating mechanisms must quickly respond to severe fault conditions by permitting the contact arms and associated contacts to blow open quickly in response to unacceptable fault current conditions. Various mechanical arrangements have been provided to improve blow-open response speeds for the current carrying contacts. For example, circuit breaker designs have produced circuit breaker configurations which provide current paths which utilize the high currents during fault conditions to increase electromagnetic blow-apart forces between contact arms and associated current carrying members in the circuit breaker. Unacceptable fault currents within properly configured current paths produce electrodynamic forces which drive contact arms and associated contacts open quickly. One problem encountered as a result of high blow-apart forces is the potential that these forces cause the contact arm to rebound from its associated stop and bounce back past the over-center position, thereby causing the arm to reengage the circuit breaker contacts.

Another type of circuit breaker design practice used to improve the separation speed and performance of the circuit breaker contacts during unacceptable fault current conditions is the use of cam arrangements with the contact arm. These arrangements produce high contact forces to produce adequate contact engagement pressures during normal operation, and produce reduced or eliminated contact force after the contact arm is moved a relatively small distance during blow-apart under fault current conditions. For example, U.S. Pat. No. 4,488,133, issued to McClellan et al. on Dec. 11, 1984, discloses a current-limiting circuit breaker including a contact pressure spring configured to hold the contact arms and associated contacts in their open position after the contacts are blown open. In particular, a multi-section cam transmits contact opening and closing forces produced by a spring powered, over-center, toggle-type operating mechanism to the associated pivoting contact arms. A follower on the contact arm is biased into engagement with the cam by the contact pressure spring. The cam is configured so that the moveable contact arm requires relatively little motion to move the knee of the cam surface into the open direction during blow-off under fault conditions. The cam is further configured to control the speed of the contact arm to reduce the potential for contact arm rebound.

While various designs have been provided to increase blow-off speeds and performance of circuit breaker contact arms during unacceptable fault current conditions, the need to reduce circuit breaker size and cost for given voltage and current carrying ratings requires that blow-off speeds and performance increase even though there is substantial market pressure to maintain present circuit breaker selling prices. Accordingly, it would be desirable to provide a

design which is an improvement over the above-described designs and lower in cost.

SUMMARY OF THE INVENTION

The present invention relates to a circuit breaker of the type including a contact arm operated by a crossbar under normal conditions. The contact arm is pivotally attached to the circuit breaker base to pivot about a first axis between open and closed positions so that the longitudinal axis of the contact arm is generally perpendicular with the first axis. The contact arm includes first and second cam followers supported by the contact arm in a spaced relationship on a second axis parallel to the first axis. The crossbar includes first and second cam surfaces, and is pivotally attached to the base to pivot between open and closed positions about a third axis parallel to the first axis. A single spring including a longitudinal axis is attached to the contact arm and the crossbar such that the spring is located between the first and second cam followers. The spring forces the first cam follower against the first cam surface and the second cam follower against the second cam surface with substantially equal force so that the contact arm moves to its open position when the crossbar is moved to its open position while the contact arm is permitted to move to its open position while the crossbar is in its closed position.

The present invention also relates to a configuration of the circuit breaker wherein the contact arm includes a cam follower, and is pivotally attached to the base to pivot about a first axis between open and closed positions. The crossbar includes at least one cam surface and is pivotally attached to the base to pivot between open and closed positions about a second axis parallel to the first axis. The contact arm and crossbar are attached to each other by a spring having a longitudinal axis. The spring is attached between the contact arm and the crossbar such that the longitudinal axes of the spring and contact arm lay substantially within a plane perpendicular to the first axis. The spring forces the cam follower against the cam surface such that the contact arm moves to its open position when the crossbar is moved to its open position. The contact arm is permitted to independently move to its open positions while the crossbar is in its closed position.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a sectional view of a circuit breaker taken along line 2—2 of FIG. 2;

FIG. 2 is a top view of the circuit breaker with a portion of the cover removed to show the components of one phase of the circuit breaker; and

FIG. 3 is a perspective view of the crossbar of the circuit breaker.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIGS. 1 and 2, a circuit breaker 10 according to one aspect of the invention includes an insulating plastic support base 12 and cover 13. The main components of circuit breaker 10 are pivoting (movable) upper contact arms 14, pivoting (movable) lower contact arms 16, lower contact arm support spring 18, arc chambers 22, an upper pivoting contact arm operating mechanism 24 (partially shown in FIG. 2), an electronic or thermal magnetic trip unit 26, load terminals 28, and line terminals 30. Circuit breaker 10 is a multi-phase (e.g. three-phase) circuit breaker having one

arm 14, one arm 16, support spring 18, terminal 28, and terminal 30 for each of the three phases. Components 16, 18, 22, 24, 26, 28 and 30 are of conventional design, e.g. Siemens Breaker Type HQJ2H. One operating mechanism 24 and one trip unit 26 cooperate to move a single insulative crossbar 32, which moves arms 14 of each phase in unison during contact opening and closing under normal conditions. An operating handle 25 is mechanically coupled to operating mechanism 24 to rotate crossbar 32 between its open and closed positions thereby moving arms 14 between their open and closed positions. For purposes of clarity, the following description will only reference the components of one phase of circuit breaker 10, but it should be understood that it is applicable to each or all of the phases of the circuit breaker.

Contact arm 14 has a conventional electrical contact 34 brazed or otherwise fastened to a first end and a pivot hole 36 at its second end. Electrical contact 34 engages and disengages an electrical contact 38 at the end of contact arm 16. A pivot pin 40, mounted in pivot hole 36 of a pivot clip 37, pivotally attaches contact arm 14 to a terminal strap 42. Pin 40 may also pivotally attach crossbar 32 to base 12 via strap 42. Strap 42 is fastened to base 12 by any suitable means, such as a screw 44, and is coupled to load terminal 28 by trip unit 26. Trip unit 26 is fastened, and electrically connected, to mount 46 of load terminal 28 and mount 48 of strap 42.

Each contact arm 16 is pivotally mounted to base 12 by a pivot pin 17, which pivotally attaches respective arm 16 to a pivot mount 20 which is electrically connected to terminal 30. An arc insulating barrier 56 is attached to base 12 and configured as shown in FIG. 2 to rest between arms 14 and 16 and inhibit arcing therebetween. Insulator 56 is fastened above contact arm 16 with screws 58. More specifically, screws 58 engage threaded holes within base 12. Each contact arm supporting spring 18 is compressed between the respective arm 16 and base 12 to force arm 16 against the bottom surface of insulator 56 as illustrated in FIG. 1.

Load terminals 28 provide locations for electrically coupling a three-phase apparatus or distribution system to circuit breaker 10. Line terminals 30 provide corresponding locations for electrically coupling a three-phase power source to circuit breaker 10. Accordingly, when contacts 34 and 38 for each phase are engaged, power is transmitted from the three-phase power source to the three-phase device or power distribution system. Load and line terminals 28 and 30 may include any suitable attachment means for allowing wires or other conductors to be secured thereto, such as a pair of threaded holes 84 which receive screws for fastening one terminal block (not shown) to each of terminals 28, 30. Of course, depending upon the application, the terminal block may be replaced with other appropriate arrangements for coupling conductors to terminals 28, 30.

In general, operating mechanism 24 moves crossbar 32 between closed and open positions. As discussed in detail below, the configuration of crossbar 32 allows crossbar 32 to interact with arms 14 to move arms 14 between their open and closed positions during ON/OFF switching and under overload conditions. Electrical contacts 34 and 38 are engaged when arms 14 are in their closed positions, and disengaged when arms 14 are in their open positions. When trip unit 26 detects an unacceptable current level (i.e., overload current) in one of the phases, it actuates operating mechanism 24 in a conventional manner so that mechanism 24 rotates crossbar 32 and contact arms 14 counterclockwise about pin 40 to separate contacts 34 and 38. Occurrence of a fault current in one of the phases will cause the associated contact arm 14 to blow open and pivot counter-clockwise (as

viewed in FIG. 1) about pin 40 to separate contacts 34 and 38. At the same time, contact arm 16 rotates clockwise about pin 17 to increase the speed of separation between contacts 34 and 38. However, under these conditions contact arm 14 and 16 will pivot to the open position independent of crossbar 32 while crossbar 32 remains stationary.

Referring to FIG. 3, crossbar 32 is configured as shown and preferably molded from an appropriate thermoset or thermoplastic material (i.e., plastic) having characteristics which do not require the use of reinforcing materials within molded crossbar 32. By way of specific example, the preferred embodiment of crossbar 32 is molded from glass polyester plastic. However, depending upon the application, it may be useful to use strengthening materials such as steel or glass fibers at areas of the crossbar which require additional rigidity and strength, or when an adequate plastic to mold crossbar 32 from is unavailable. The crossbar shown in FIG. 3 is configured for a three-phase circuit breaker and includes three formations 60 each including a saddle 62 within which respective contact arms 14 are located. In general, formations 60 and the associated cam follower (discussed below) connect and disconnect a driving part of circuit breaker 10 (i.e. crossbar 32) with a driven part of circuit breaker 10 (i.e. contact arms 14). In other words, under certain conditions, formation 60 permits arms 14 to move in unison with crossbar 32 or move independently thereof. Thus, formation 60 and the cam follower generally operate as a clutch. Formations 60 of crossbar 32 include pivot holes 64 through which shaft 40 extends. Accordingly, when crossbar 32 is mounted upon pivot shaft 40, crossbar 32 rotates along the axis of shaft 40 which is the same axis of rotation as that of cross arms 14. In addition to formations 60, crossbar 32 also includes an operating arm 66 which is linked to operating mechanism 24. Thus, operating mechanism 24 can rotate crossbar 32 between its open and closed positions.

Each formation 60 includes first and second parallel insulating barriers 68 and 70. Barriers 68 and 70 are joined by a member 72 to form saddles 62 and a member 74 to cooperate with member 72 to provide rigid parallel support between insulating barriers 68 and 70. Adjacent clutches 60 are joined by torque carrying members 76 and 78, which are configured as shown to rigidly attach formations 60 together. As shown in FIG. 3, operating arm 60 is integrally molded with torque member 78.

Each insulating barrier 68 is formed to include a cam surface 80 including two surfaces 82 and 84. Additionally, each insulating barrier 68 and 70 is formed to include a spring pin support slot 86.

Referring again to FIGS. 1 and 2, for each phase of circuit breaker 10 there is included a cam follower 88 having a pair of rollers 90 and a roller shaft or pin 92. Each roller shaft 92 is supported by a respective contact arm 14 by a pair of links 94 attached to respective arm 14. In particular, links 94 are attached to arm 14 by an appropriate rivet, bolt or shaft pin 96. Roller shaft 92 and pin 96 have parallel axes, and pass through appropriately configured openings in links 94. Furthermore, links 94 are fastened to respective arms 14 so that the longitudinal axes of shaft 92 and pin 96 remain generally parallel, and the longitudinal axis of shaft 92 may rotate about the longitudinal axis of pin 96 when cam follower 88 travels along cam surfaces 80.

As discussed above, crossbar 32 is preferably fabricated as a one-piece unit molded from plastic. Accordingly, cam surfaces 80 are also fabricated from plastic. To prevent unacceptable wear which may undesirably restrict the move-

ment of cam follower **88** along cam surface **80**, rollers **90** are rotatably mounted on roller shaft **92** to contact surface **80** and roll along surface **80**. Use of rollers **90** eliminates the need to slide shaft **92** along surface **80**, thus reducing undesirable wearing of plastic surface **80** and increasing the endurance limits.

As discussed above, links **94** of cam follower **88** permit shaft **92** to move along an arc defined by links **94** and pin **96**. Accordingly, one end of a spring **98** is attached to shaft **92** and the other end of spring **98** is attached to a spring support pin **100**. This arrangement advantageously utilizes a single spring **98** to provide the force to hold rollers **90** of cam follower **88** in contact with cam surface **80**. By locating spring **98** between and at substantially equal distances from cam follower rollers **90**, rollers **90** are forced against their respective cam surfaces at with substantially equal forces. Additionally, when a respective contact arm **14** is blown open (as discussed in further detail below) and rollers **90** move from surface **84** to surface **82** during unacceptable fault current conditions, spring **98** pulls follower **88** along surface **82** to increase the rotational speed of contact arm **14** in the counter-clockwise direction and thus increase the speed at which contacts **34** and **38** separate. However, under normal operating conditions, spring **98** operates to hold rollers **90** in contact with surface **84** to prevent undesirable counter-clockwise rotation of contact arm **14**. Furthermore, spring **98** is mounted in tension to ensure that pin **100** remains in spring pin slots **86**, regardless of the position of contact arm **14** relative to crossbar **32**.

Turning now to the operation of circuit breaker **10**, arm **14** is shown in its closed position, and arm **16** is in its operating position with contacts **34** and **38** being electrically engaged. In its operating position, arm **16** is urged upwardly by an upward force applied by biasing spring **18**. When contacts **34** and **38** are engaged, the current path through arms **14** and **16** substantially follows the path shown by the arrow **150**. The main component of current in circuit breaker **10** is substantially parallel to the central axis of arm **16** until the current passes from arm **16** to arm **14** via contacts **34** and **38**, where the main component of current in arm **14** is substantially parallel to its central axis.

Currents which have current flow components which are parallel and in opposite directions repel each other. This phenomenon is a result of the magnetic fields produced by the currents and the interaction of these magnetic fields with the currents. The magnitude of the repulsion or attraction is affected by the distance between the respective parallel components of the currents, and magnetic shielding which may be provided between the currents. Accordingly, when there is current flow from contact arm **16** to contact arm **14**, contact arms **14** and **16** will repel each other due to the repulsive forces ("blow-off forces") produced by the parallel components of current in arms **14** and **16**.

When the current flow in arms **14** and **16** is sufficiently high, and hence the blow-off forces are sufficiently high, arms **14** and **16** will be forced to rotate counter-clockwise and clockwise, respectively. During the period in which arms **14** and **16** move in these directions, an arc occurring between contacts **34** and **38** is stretched, extinguished and moved toward arc chamber **22**. To move to its blown-open position, arm **14** must be repelled from arm **16** with sufficient force to overcome an opening force required to move cam follower **88** along cam surface **80** from surface **82** to surface **84**. The opening force is of opposite magnitude to (i.e., higher than) the moving force produced when follower **88** is pulled along, and to the end of, surface **84**. Accordingly, upon moving from surface **82** to **84** the speed of

rotation of arm **14** substantially increases to aid in extinguishing the arc. Furthermore, the use of rollers **90** decreases the friction forces developed between follower **88** and surface **84**, which further increases the rotational speed of arm **14** during blow apart.

In summary, the present crossbar **32** and follower **88** arrangements make it possible to achieve much higher interrupting ratings and lower let-thru energy in a cost effective manner. Of course, surface **80** could be modified to provide more than the two cam surface configurations **82** and **84**.

Subsequent to blow apart, circuit breaker **10** must be reset by rotating the crossbar counter-clockwise to its open (OFF) position. To reset circuit breaker **10**, operating mechanism **24** is manually operated in a conventional manner. During reset, a cam follower stop (not shown) engages follower **88** so that follower **88** moves from surface **84** to surface **82** while crossbar **32** is rotated counter-clockwise.

The preferred embodiment of the present invention has been disclosed by way of example and it will be understood that other modifications may occur to those skilled in the art without departing from the scope and spirit of the appended claims. For example, in the present embodiment, rollers **90**, shaft **92**, links **84** and other similar non-current conducting components of circuit breaker **10** are fabricated from metals. However, improvements in plastic properties may permit replacing these components with similar components fabricated from plastic.

What is claimed is:

1. A circuit breaker comprising:

a base;

a contact arm pivotally attached to the base to pivot about a first axis between open and closed positions, the contact arm having a first longitudinal axis generally perpendicular with the first axis, and including first and second cam followers supported by the contact arm in a spaced relationship on a second axis parallel to the first axis;

a crossbar including first and second cam surfaces, the crossbar being pivotally attached to the base to pivot between open and closed positions about a third axis parallel to the first axis; and

a spring including a second longitudinal axis and attached to the contact arm and the crossbar such that the spring is located between the first and second cam followers, wherein the spring forces the first cam follower against the first cam surface and the second cam follower against the second cam surface with substantially equal force such that the contact arm moves to its open position when the crossbar is moved to its open position, and the contact arm is permitted to move to its open position while the crossbar is in its closed position.

2. The circuit breaker of claim 1, wherein the cam surfaces are formed from plastic.

3. The circuit breaker of claim 1, wherein the crossbar is formed from plastic, and the cam surfaces are formed integrally therewith.

4. The circuit breaker of claim 1, further comprising a spring shaft for supporting the cam followers and a linkage for pivotally attaching the spring shaft on the contact arm, the spring being attached to the contact arm by the spring shaft and linkage.

5. The circuit breaker of claim 1, wherein the first and third axes are coincident.

6. The circuit breaker of claim 1, wherein each cam follower includes a roller which contacts the respective cam

surface and rolls along the respective surface when the contact arm moves to its open position while the crossbar is in its closed position.

7. The circuit breaker of claim 6, wherein the crossbar is a one-piece, plastic, molded component.

8. The circuit breaker of claim 6, wherein each cam surface includes at least a first surface portion which contacts the respective roller to require a first force to move the roller relative thereto and a second surface portion which contacts the respective roller to require a second force to move the roller relative thereto, the second force being greater than the first force.

9. The circuit breaker of claim 8, wherein the rollers of the cam follower are in contact with the respective second surfaces when the contact arm and the crossbar are in their respective closed positions.

10. The circuit breaker of claim 9, wherein the crossbar further comprises first and second insulating barriers located on respective sides of the contact arm, and the first cam surface is molded integrally with the first insulating barrier and the second cam surface is molded integrally with the second insulating barrier.

11. The circuit breaker of claim 10, further comprising an operating mechanism mechanically coupled to the crossbar to move the crossbar between its open and closed positions.

12. The circuit breaker of claim 11, wherein the crossbar includes an arm molded integrally with the crossbar and extending from the crossbar generally perpendicular with the second axis, the arm coupling the crossbar to the operating mechanism.

13. A circuit breaker of the type including a base, the circuit breaker comprising:

a contact arm including a cam follower, and pivotally attached to the base to pivot about a first axis between open and closed positions, the first contact arm including a first longitudinal axis perpendicular to the first axis;

a crossbar including a cam surface, the crossbar being pivotally attached to the base to pivot between open and closed positions about a second axis parallel to the first axis; and

a spring having a second longitudinal axis, the spring being attached between the contact arm and the crossbar such that the second longitudinal axis lays substantially within a plane perpendicular to the first axis and

passing through the second axis, wherein the spring forces the cam follower against the cam surface such that the contact arm moves to its open position when the crossbar is moved to its open position, and the contact arm is permitted to independently move to its open positions while the crossbar is in its closed position.

14. The circuit breaker of claim 13, further comprising a spring shaft for supporting the cam follower and a linkage for pivotally attaching the spring shaft to the contact arm, the spring being attached to the contact arm by the spring shaft and linkage.

15. The circuit breaker of claim 13, wherein the first and second axes are coincident.

16. The circuit breaker of claim 13, wherein the cam surface is formed from plastic.

17. The circuit breaker of claim 13, wherein the crossbar is formed from plastic, and the cam surfaces are formed integrally therewith.

18. The circuit breaker of claim 16, wherein the cam follower includes a roller which contacts the cam surface and rolls along the surfaces when the contact arm moves to its open position while the crossbar is in its closed position.

19. The circuit breaker of claim 18, wherein the cam surface includes at least a first surface portion which contacts the roller to require a first force to move the roller relative thereto and a second surface portion which contacts the roller to require a second force to move the roller relative thereto, the second force being greater than the first force.

20. The circuit breaker of claim 19, wherein the roller is in contact with the second surfaces when the contact arm and the crossbar are in their respective closed positions.

21. The circuit breaker of claim 20, wherein the crossbar further comprises pairs of insulating barriers located on the sides of the contact arm, and the cam surfaces are molded integrally with an insulating barrier.

22. The circuit breaker of claim 21, further comprising an operating mechanism mechanically coupled to the crossbar to move the crossbar between its open and closed positions.

23. The circuit breaker of claim 22, wherein the crossbar includes an arm molded integrally with the crossbar and extending from the crossbar generally perpendicular with the second axis, the arm coupling the crossbar to the operating mechanism.

* * * * *