

US009116543B2

(12) **United States Patent**
Wells

(10) **Patent No.:** **US 9,116,543 B2**
(45) **Date of Patent:** ***Aug. 25, 2015**

(54) **VIRTUAL INPUT SYSTEM**

(71) Applicant: **III Holdings 1, LLC**, Wilmington, DE (US)

(72) Inventor: **William R. Wells**, Reno, NV (US)

(73) Assignee: **III Holdings 1, LLC**, Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/158,013**

(22) Filed: **Jan. 17, 2014**

(65) **Prior Publication Data**

US 2014/0132509 A1 May 15, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/618,910, filed on Sep. 14, 2012, now Pat. No. 8,668,584, which is a continuation of application No. 13/077,606, filed on Mar. 31, 2011, now Pat. No. 8,398,488, which is a continuation of application No. 10/921,518, filed on Aug. 19, 2004, now Pat. No. 7,942,744.

(51) **Int. Cl.**

A63F 13/06 (2006.01)
G06F 3/01 (2006.01)
G01S 13/56 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC . **G06F 3/01** (2013.01); **G01S 13/56** (2013.01);
G01S 13/862 (2013.01); **G01S 15/025**
(2013.01); **G01S 15/87** (2013.01); **G01S 15/88**
(2013.01); **G01S 17/89** (2013.01); **G06F**
3/0346 (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G06F 3/016; G06F 3/011; A63F 13/06;
A63F 2300/1062; A63F 13/10

USPC 345/156, 158; 463/36, 37, 25, 42
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,662,105 A 5/1972 Parks et al.
3,697,698 A 10/1972 Oswald et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU 704691 B2 4/1997
AU 2005265179 1/2011

(Continued)

OTHER PUBLICATIONS

U.S. Office Action from U.S. Appl. No. 11/825,481, dated Nov. 24, 2010.

(Continued)


Primary Examiner — Pierre E Elisca

(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson Kindness PLLC

(57) **ABSTRACT**

For a user having a user input actuator, a virtual interface device, such as for a gaming machine, for determining actuation of a virtual input by the input actuator is disclosed. The device comprises a position sensing device for determining a location of the user input actuator and a controller coupled to the position sensing device, the controller determining whether a portion of the user input actuator is within a virtual input location in space defining the virtual input.

20 Claims, 7 Drawing Sheets



(51)	Int. Cl.		5,811,772 A	9/1998	Lucero et al.
	<i>G01S 15/02</i>	(2006.01)	5,816,918 A	10/1998	Kelly et al.
	<i>G01S 15/87</i>	(2006.01)	5,818,954 A	10/1998	Tomono et al.
	<i>G01S 15/88</i>	(2006.01)	5,833,536 A	11/1998	Davids et al.
	<i>G01S 17/89</i>	(2006.01)	5,833,540 A	11/1998	Miodunski et al.
	<i>G06F 3/0346</i>	(2013.01)	5,844,824 A	12/1998	Newman et al.
	<i>G06F 3/042</i>	(2006.01)	5,851,148 A	12/1998	Brune et al.
	<i>G07F 17/32</i>	(2006.01)	5,855,515 A	1/1999	Pease et al.
	<i>G01S 13/86</i>	(2006.01)	5,871,398 A	2/1999	Schneier et al.
	<i>G01S 13/34</i>	(2006.01)	5,885,158 A	3/1999	Torango et al.
(52)	U.S. Cl.		5,892,566 A	4/1999	Bullwinkel
	CPC	<i>G06F 3/0421</i> (2013.01); <i>G07F 17/3211</i>	5,910,048 A	6/1999	Feinberg
		(2013.01); <i>G01S 13/34</i> (2013.01)	5,913,727 A	6/1999	Ahdoot
			5,919,091 A	7/1999	Bell et al.
			5,951,397 A	9/1999	Dickinson
			5,954,583 A	9/1999	Green et al.
			5,957,776 A	9/1999	Hoehne et al.
(56)	References Cited		5,967,896 A	10/1999	Jorasch et al.
	U.S. PATENT DOCUMENTS		5,971,271 A	10/1999	Wynn et al.
			5,982,326 A	11/1999	Chow et al.
			5,984,779 A	11/1999	Bridgeman et al.
			5,999,808 A	12/1999	Laude et al.
	3,724,932 A	4/1973 Cornsweet et al.	6,001,016 A	12/1999	Walker et al.
	3,986,030 A	10/1976 Teltscher	6,003,013 A	12/1999	Boushy et al.
	4,071,689 A	1/1978 Talmage	6,003,651 A	12/1999	Waller et al.
	4,072,930 A	2/1978 Lucero et al.	6,008,800 A	12/1999	Pryor
	4,109,145 A	8/1978 Graf	6,010,404 A	1/2000	Walker et al.
	4,283,709 A	8/1981 Lucero et al.	6,012,832 A	1/2000	Saunders et al.
	4,339,798 A	7/1982 Hedges et al.	6,012,983 A	1/2000	Walker et al.
	4,348,696 A	9/1982 Beier	6,038,666 A	3/2000	Hsu et al.
	4,553,222 A	11/1985 Kurland et al.	6,048,269 A	4/2000	Burns et al.
	4,595,990 A	6/1986 Garwin	6,050,895 A	4/2000	Luciano et al.
	4,836,670 A	6/1989 Hutchinson	6,062,981 A	5/2000	Luciano
	4,837,728 A	6/1989 Barrie et al.	6,068,552 A	5/2000	Walker et al.
	4,856,787 A	8/1989 Itkis et al.	6,077,163 A	6/2000	Walker et al.
	4,950,069 A	8/1990 Hutchinson	6,089,975 A	7/2000	Dunn
	4,973,149 A	11/1990 Hutchinson	6,099,408 A	8/2000	Schneier et al.
	5,033,744 A	7/1991 Bridgeman et al.	6,104,815 A	8/2000	Alcorn et al.
	5,038,022 A	8/1991 Lucero et al.	6,106,396 A	8/2000	Alcorn et al.
	5,042,809 A	8/1991 Richardson et al.	6,110,041 A	8/2000	Walker et al.
	5,048,831 A	9/1991 Sides	6,110,043 A	8/2000	Olsen
	5,059,959 A	10/1991 Barry	6,113,492 A	9/2000	Walker et al.
	5,116,055 A	5/1992 Tracy et al.	6,113,493 A	9/2000	Walker et al.
	5,179,517 A	1/1993 Sarbin et al.	6,113,495 A	9/2000	Walker et al.
	5,280,809 A	1/1994 Tive et al.	6,135,884 A	10/2000	Hedrick et al.
	5,288,078 A	2/1994 Capper et al.	6,135,887 A	10/2000	Pease et al.
	5,367,315 A	11/1994 Pan	6,139,431 A	10/2000	Walker et al.
	5,371,345 A	12/1994 LeStrange et al.	6,142,876 A	11/2000	Cumbers et al.
	5,429,361 A	7/1995 Raven et al.	6,146,273 A	11/2000	Olsen et al.
	5,442,168 A	8/1995 Gurner et al.	6,149,522 A	11/2000	Alcorn et al.
	5,470,079 A	11/1995 LeStrange et al.	6,161,059 A	12/2000	Tedesco et al.
	5,474,082 A	12/1995 Junker	6,162,121 A	12/2000	Morro et al.
	5,517,021 A	5/1996 Kaufman et al.	6,162,122 A	12/2000	Acres et al.
	5,536,016 A	7/1996 Thompson	6,168,522 B1	1/2001	Walker et al.
	5,577,731 A	11/1996 Jones et al.	6,174,234 B1	1/2001	Seibert, Jr. et al.
	5,605,334 A	2/1997 McCrea et al.	6,182,221 B1	1/2001	Hsu et al.
	5,616,078 A	4/1997 Oh	6,183,362 B1	2/2001	Boushy
	5,618,045 A	4/1997 Kagan	6,190,256 B1	2/2001	Walker et al.
	5,638,826 A	6/1997 Wolpaw et al.	6,191,773 B1	2/2001	Maruno et al.
	5,643,086 A	7/1997 Alcorn et al.	6,210,279 B1	4/2001	Dickinson
	5,655,961 A	8/1997 Acres et al.	6,227,972 B1	5/2001	Walker et al.
	5,655,966 A	8/1997 Werdin, Jr. et al.	6,227,974 B1	5/2001	Eilat et al.
	5,702,304 A	12/1997 Acres et al.	6,234,900 B1	5/2001	Cumbers
	5,704,836 A	1/1998 Norton et al.	6,244,958 B1	6/2001	Acres
	5,716,273 A	2/1998 Yuen	6,247,643 B1	6/2001	Lucero
	5,718,632 A	2/1998 Hayashi	6,253,119 B1	6/2001	Dabrowski
	5,741,183 A	4/1998 Acres et al.	6,264,560 B1	7/2001	Goldberg et al.
	5,759,102 A	6/1998 Pease et al.	6,264,561 B1	7/2001	Saffari et al.
	5,761,647 A	6/1998 Boushy	6,267,671 B1	7/2001	Hogan
	5,766,076 A	6/1998 Pease et al.	6,270,410 B1	8/2001	DeMar et al.
	5,768,382 A	6/1998 Schneier et al.	6,280,328 B1	8/2001	Holch et al.
	5,769,716 A	6/1998 Saffari et al.	6,285,868 B1	9/2001	LaDue
	5,770,533 A	6/1998 Franchi et al.	6,293,866 B1	9/2001	Walker et al.
	5,779,545 A	7/1998 Berg et al.	6,302,790 B1	10/2001	Brossard
	5,788,573 A	8/1998 Baerlocher et al.	6,307,956 B1	10/2001	Black
	5,795,228 A	8/1998 Trumbull et al.	6,313,871 B1	11/2001	Schubert
	5,796,389 A	8/1998 Bertram et al.	6,319,125 B1	11/2001	Acres
	5,797,085 A	8/1998 Beuk et al.	6,341,353 B1	1/2002	Herman et al.
	5,803,809 A	9/1998 Yoseloff	6,346,044 B1	2/2002	McCrea, Jr.
	5,809,482 A	9/1998 Strisower			

(56)

References Cited

U.S. PATENT DOCUMENTS

6,368,216 B1	4/2002	Hedrick et al.	7,815,507 B2	10/2010	Parrott et al.
6,371,852 B1	4/2002	Acres	7,942,744 B2	5/2011	Wells
6,375,572 B1	4/2002	Masuyama et al.	2001/0000118 A1	4/2001	Sines et al.
6,379,246 B1	4/2002	Dabrowski	2001/0028147 A1	10/2001	Ornstein et al.
6,383,076 B1	5/2002	Tiedeken	2001/0031663 A1	10/2001	Johnson
6,409,595 B1	6/2002	Uihlein et al.	2001/0039204 A1	11/2001	Tanskanen
6,409,602 B1	6/2002	Wiltshire et al.	2001/0040572 A1	11/2001	Bradski et al.
6,439,993 B1	8/2002	O'Halloran	2002/0002072 A1	1/2002	Sines et al.
6,443,843 B1	9/2002	Walker et al.	2002/0022518 A1	2/2002	Okuda et al.
6,450,885 B2	9/2002	Schneier et al.	2002/0036617 A1	3/2002	Pryor
6,471,591 B1	10/2002	Crumby	2002/0042297 A1	4/2002	Torango
6,488,585 B1	12/2002	Wells et al.	2002/0046100 A1	4/2002	Kinjo
6,508,710 B1	1/2003	Paravia et al.	2002/0055383 A1	5/2002	Onda
6,511,376 B2	1/2003	Walker et al.	2002/0075240 A1*	6/2002	Lieberman et al. 345/170
6,511,377 B1	1/2003	Weiss	2002/0098888 A1	7/2002	Rowe et al.
6,519,607 B1	2/2003	Mahoney et al.	2002/0103024 A1	8/2002	Jeffway, Jr. et al.
6,530,835 B1	3/2003	Walker et al.	2002/0103027 A1	8/2002	Rowe et al.
6,554,705 B1	4/2003	Cumbers	2002/0107066 A1	8/2002	Seelig et al.
6,561,903 B2	5/2003	Walker et al.	2002/0133418 A1	9/2002	Hammond et al.
6,582,310 B1	6/2003	Walker et al.	2002/0142824 A1	10/2002	Kazaoka et al.
6,585,592 B1	7/2003	Crumby	2002/0142825 A1	10/2002	Lark et al.
6,599,193 B2	7/2003	Baerlocher et al.	2002/0142844 A1	10/2002	Kerr
6,607,443 B1	8/2003	Miyamoto et al.	2002/0142846 A1	10/2002	Paulsen
6,611,253 B1	8/2003	Cohen	2002/0147047 A1	10/2002	Letovsky et al.
6,620,047 B1	9/2003	Alcorn et al.	2002/0198052 A1	12/2002	Soltys et al.
6,624,561 B2	9/2003	Nakamura et al.	2003/0003988 A1	1/2003	Walker et al.
6,628,939 B2	9/2003	Paulsen	2003/0017872 A1	1/2003	Oishi et al.
6,629,890 B2	10/2003	Johnson	2003/0027632 A1	2/2003	Sines et al.
6,637,883 B1	10/2003	Tengshe et al.	2003/0032485 A1	2/2003	Cockerille et al.
6,645,077 B2	11/2003	Rowe	2003/0045354 A1	3/2003	Giobbi
6,645,078 B1	11/2003	Mattice	2003/0050806 A1	3/2003	Friesen et al.
6,650,318 B1	11/2003	Arnon	2003/0054881 A1	3/2003	Hedrick et al.
6,651,985 B2	11/2003	Sines et al.	2003/0060280 A1	3/2003	Oles et al.
6,652,378 B2	11/2003	Cannon et al.	2003/0069071 A1	4/2003	Britt et al.
6,676,522 B2	1/2004	Rowe et al.	2003/0078101 A1	4/2003	Schneider et al.
6,682,421 B1	1/2004	Rowe et al.	2003/0078103 A1	4/2003	LeMay et al.
6,685,480 B2	2/2004	Nishimoto et al.	2003/0083132 A1	5/2003	Berg et al.
6,685,567 B2	2/2004	Cockerille et al.	2003/0083943 A1	5/2003	Adams et al.
6,712,698 B2	3/2004	Paulsen et al.	2003/0100361 A1	5/2003	Sharpless et al.
6,720,949 B1	4/2004	Pryor et al.	2003/0109308 A1	6/2003	Rowe
6,722,985 B2	4/2004	Criss-Puszkiewicz et al.	2003/0148808 A1	8/2003	Price
6,739,975 B2	5/2004	Nguyen et al.	2003/0148812 A1	8/2003	Paulsen et al.
6,743,097 B2	6/2004	Walker et al.	2003/0162593 A1	8/2003	Griswold
6,776,715 B2	8/2004	Price	2003/0179229 A1	9/2003	Van Erlach et al.
6,783,459 B2	8/2004	Cumbers	2003/0190944 A1	10/2003	Manfredi et al.
6,800,029 B2	10/2004	Rowe et al.	2003/0203756 A1	10/2003	Jackson
6,801,188 B2	10/2004	Longobardi	2003/0228898 A1	12/2003	Rowe
6,804,763 B1	10/2004	Stockdale et al.	2004/0001182 A1	1/2004	Dyner
6,830,515 B2	12/2004	Rowe	2004/0002386 A1	1/2004	Wolfe et al.
6,846,238 B2	1/2005	Wells	2004/0027450 A1	2/2004	Yoshino
6,852,031 B1	2/2005	Rowe	2004/0029635 A1	2/2004	Giobbi
6,863,608 B1	3/2005	LeMay	2004/0043814 A1	3/2004	Angell et al.
6,863,609 B2	3/2005	Okuda et al.	2004/0046736 A1	3/2004	Pryor et al.
6,866,586 B2	3/2005	Oberberger	2004/0053675 A1	3/2004	Nguyen et al.
6,884,170 B2	4/2005	Rowe	2004/0063480 A1	4/2004	Wang
6,908,387 B2	6/2005	Hedrick et al.	2004/0063481 A1	4/2004	Wang
6,921,332 B2	7/2005	Fukunaga et al.	2004/0082385 A1	4/2004	Silva et al.
6,922,276 B2	7/2005	Zhang et al.	2004/0085293 A1	5/2004	Soper
6,939,231 B2	9/2005	Mäntyjärvi et al.	2004/0087370 A1	5/2004	Tarantino
6,965,868 B1	11/2005	Bednarek	2004/0092310 A1	5/2004	Brosnan et al.
6,997,807 B2	2/2006	Weiss	2004/0116174 A1	6/2004	Baerlocher et al.
7,001,277 B2	2/2006	Walker et al.	2004/0127277 A1	7/2004	Walker et al.
7,022,017 B1	4/2006	Halbritter et al.	2004/0137987 A1	7/2004	Nguyen et al.
7,035,626 B1	4/2006	Luciano, Jr.	2004/0147314 A1	7/2004	LeMay et al.
7,083,518 B2	8/2006	Rowe	2004/0162139 A1	8/2004	Blanco
7,111,141 B2	9/2006	Nelson	2004/0166937 A1	8/2004	Rothschild et al.
7,112,138 B2	9/2006	Hedrick et al.	2004/0189720 A1	9/2004	Wilson et al.
7,128,651 B2	10/2006	Miyamoto et al.	2004/0193413 A1	9/2004	Wilson et al.
7,168,089 B2	1/2007	Nguyen et al.	2004/0199284 A1	10/2004	Hara
7,217,190 B2	5/2007	Weiss	2004/0203895 A1	10/2004	Balasuriya
7,255,642 B2	8/2007	Sines et al.	2004/0251630 A1	12/2004	Sines et al.
7,275,991 B2	10/2007	Burns et al.	2004/0254006 A1	12/2004	Lam et al.
7,384,339 B2	6/2008	LeMay et al.	2005/0037844 A1	2/2005	Shum et al.
7,515,718 B2	4/2009	Nguyen et al.	2005/0059488 A1	3/2005	Larsen et al.
7,611,407 B1	11/2009	Itkis et al.	2005/0076242 A1	4/2005	Breuer
			2005/0143169 A1	6/2005	Nguyen et al.
			2005/0212753 A1	9/2005	Marvit et al.
			2005/0255911 A1	11/2005	Nguyen et al.
			2005/0255922 A1	11/2005	Nguyen et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0261059 A1 11/2005 Nguyen et al.
 2005/0261060 A1 11/2005 Nguyen et al.
 2005/0261061 A1 11/2005 Nguyen et al.
 2005/0261816 A1 11/2005 DiCroce et al.
 2005/0273815 A1 12/2005 Orr et al.
 2005/0282603 A1 12/2005 Parrott et al.
 2006/0036874 A1 2/2006 Cockerille et al.
 2006/0040730 A1 2/2006 Walker et al.
 2006/0040739 A1 2/2006 Wells
 2006/0052109 A1 3/2006 Ashman et al.
 2006/0058091 A1 3/2006 Crawford et al.
 2006/0073888 A1 4/2006 Nguyen et al.
 2006/0079333 A1 4/2006 Morrow et al.
 2006/0189365 A1 8/2006 Crawford et al.
 2006/0189367 A1 8/2006 Nguyen et al.
 2006/0189382 A1 8/2006 Muir et al.
 2006/0189384 A1 8/2006 Crawford et al.
 2006/0252530 A1 11/2006 Oberberger et al.
 2007/0004510 A1 1/2007 Underdahl et al.
 2007/0021198 A1 1/2007 Muir et al.
 2007/0052636 A1 3/2007 Kalt et al.
 2007/0202952 A1 8/2007 Francis et al.
 2007/0259716 A1 11/2007 Mattice et al.
 2007/0259717 A1 11/2007 Mattice et al.
 2007/0298873 A1 12/2007 Nguyen et al.
 2008/0076505 A1 3/2008 Nguyen et al.
 2008/0076506 A1 3/2008 Nguyen et al.
 2008/0146344 A1 6/2008 Rowe et al.
 2009/0069090 A1 3/2009 Moser et al.
 2009/0098925 A1 4/2009 Gagner et al.
 2009/0280910 A1 11/2009 Gagner et al.
 2009/0325686 A1 12/2009 Davis et al.
 2010/0087241 A1 4/2010 Nguyen et al.
 2010/0255902 A1 10/2010 Goldstein et al.
 2011/0065490 A1 3/2011 Lutnick
 2011/0212778 A1 9/2011 Wells
 2011/0275432 A1 11/2011 Lutnick et al.

FOREIGN PATENT DOCUMENTS

CN 1969301 5/2007
 DE 10034275 A1 1/2002
 EP 0698858 A1 2/1996
 EP 0744786 A1 11/1996
 EP 0769769 A1 4/1997
 EP 0924657 A1 6/1999
 EP 0942285 9/1999
 EP 1120757 8/2001
 EP 1231577 A2 8/2002
 EP 1482459 A2 12/2004
 EP 1494182 A2 1/2005
 GB 2284913 A 6/1995
 GB 2429564 2/2007
 JP 2001/218982 A 8/2001
 JP 2003-181137 A 7/2003
 JP 2004-113755 4/2004
 JP 07299248 A 11/2007
 WO WO 95/24689 A1 9/1995
 WO WO 96/00950 A1 1/1996
 WO WO 98/50876 A1 11/1998
 WO WO 98/58509 A1 12/1998
 WO 99/07153 2/1999
 WO WO 99/10061 A1 3/1999
 WO WO 01/00291 A1 1/2001
 WO WO 01/01379 A1 1/2001
 WO WO 01/03786 A1 1/2001
 WO WO 01/27759 A2 4/2001
 WO WO 01/48712 A1 7/2001
 WO WO 01/76710 A2 10/2001
 WO WO 02/24288 A2 3/2002
 WO 02/050652 6/2002
 WO WO 02/055163 A2 7/2002
 WO WO 02/058020 A2 7/2002
 WO WO 03/019486 A2 3/2003

WO WO 03/084623 A1 10/2003
 WO 2004/025595 3/2004
 WO 2004/034905 4/2004
 WO WO 2004/027584 A2 4/2004
 WO WO 2004/056432 A2 7/2004
 WO WO 2004/070591 A1 8/2004
 WO 2005/023389 3/2005
 WO 2006/010011 1/2006
 WO WO 2006/009917 A1 1/2006
 WO 2006/023285 3/2006
 WO 2006/090197 8/2006
 WO 2008/028148 3/2008
 WO 2008/030777 3/2008
 WO 2009/009225 1/2009
 WO WO 2009/009224 A1 1/2009

OTHER PUBLICATIONS

U.S. Office Action from U.S. Appl. No. 11/825,477, dated Nov. 15, 2010.
 U.S. Restriction Requirement from U.S. Appl. No. 10/921,518, dated Nov. 15, 2007.
 U.S. Office Action from U.S. Appl. No. 10/921,518, dated Mar. 17, 2008.
 U.S. Restriction Requirement from U.S. Appl. No. 10/921,518, dated Nov. 21, 2008.
 U.S. Final Office Action from U.S. Appl. No. 10/921,518, dated Apr. 20, 2010.
 U.S. Notice of Allowance from U.S. Appl. No. 10/921,518, dated Oct. 21, 2010.
 U.S. Notice of Allowance from U.S. Appl. No. 10/921,518, dated Feb. 2, 2011.
 Australian Office Action from Application Serial No. 2005265179, dated Jan. 28, 2010.
 Chinese Office Action from Application No. 200580020194.0, dated Apr. 3, 2009.
 Chinese Office Action from Application No. 200580020194.0, dated Aug. 5, 2010.
 British Examination Report from Application No. 0625344.7, dated Oct. 5, 2007.
 British Examination Report from Application 0625344.7, dated Sep. 12, 2008.
 International Preliminary Report on Patentability from Application No. PCT/US2005/021605, dated Dec. 20, 2006.
 International Search Report from Application No. PCT/US2005/021605, dated Sep. 29, 2005.
 Written Opinion from Application No. PCT/US2005/021605, dated Sep. 29, 2005.
 International Preliminary Report on Patentability from Application No. PCT/US2008/064779, dated Jan. 12, 2010.
 International Search Report from Application No. PCT/US2008/064779 dated Sep. 30, 2008.
 Written Opinion from Application Serial No. PCT/US2008/064779 dated Sep. 30, 2008.
 International Preliminary Report on Patentability from Application Serial No. PCT/US2008/064776, dated Jan. 12, 2010.
 International Search Report from Application Serial No. PCT/US2008/064776, dated Sep. 29, 2008.
 Written Opinion from Serial Application No. PCT/US2008/064776, dated Sep. 29, 2008.
 International Preliminary Report on Patentability dated Feb. 20, 2007 from Application No. PCT/US2005/027731.
 International Search Report, dated Jan. 16, 2006, from corresponding International Application No. PCT/US2005/027731, 7 pp. including Notification of Transmittal.
 Written Opinion of the International Searching Authority, dated Jan. 16, 2006, from corresponding International Application No. PCT/US2005/027731, 10 pp.
 "CHI97: The Magic Carpet; Physical Sensing for Immersive Environments", website, <http://www.acm.org/sigchi/chi97/proceedings/short-demo/jp.htm>, 5 pages, Nov. 8, 2004.
 Paradiso, "Several Sensor Approaches that Retrofit Large Surfaces for Interactivity", ACM Ubicomp 2002 Workshop on Collaboration with Interactive Walls and Tables, Gothenburg, Sweden, Sep. 29, 2002, 8 pages.

(56)

References Cited

OTHER PUBLICATIONS

Canesta, Inc., "Getting Started With Canesta, Device Prototyping Program" Copyright 2002, Canesta, Inc., 1 page document. <http://www.canesta.com/devtools.htm>.

Dean, Katie, "Wired News: Gesture Your Mouse Goodbye" May 28, 2003 2 pages, <http://www.wired.com/new/gizmos/0,1452,58978,00.html>.

LC Technologies, Inc., 4 page document entitled "Eyeglaze Technology, Solutions and Applications" Copyright 2003, <http://www.eyegaze.com/Solutions.htm>.

LC Technologies, Inc., 9 page document entitled "The Eyegaze Analysis System, Research Tools" Copyright 2003, <http://www.eyegaze.com/2Products/Development/Developmentnain.htm>.

Townsend, J. Eric et al., 11 page document entitled "Mattel Power Glove FAQ version 0.1, May 7, 1993" <http://www.ccs.new.edu/home/ivan/pglove/faq-0.1.html>.

U.S. Final Office Action from U.S. Appl. No. 11/825,481, dated May 3, 2011.

U.S. Final Office Action from U.S. Appl. No. 11/825,477, dated Apr. 19, 2011.

Canadian Office Action from Application Serial No. 2,570,901, dated May 18, 2011.

Canadian Office Action from Application Serial No. 2,570,901, dated May 3, 2012.

Third Party Submission for U.S. Appl. No. 13/077,606, filed Oct. 31, 2011.

U.S. Notice of Allowance from U.S. Appl. No. 13/077,606, dated Apr. 4, 2012.

U.S. Notice of Allowance from U.S. Appl. No. 13/077,606, dated Jul. 11, 2012.

Notice of Allowance dated Oct. 1, 2012, in U.S. Appl. No. 11/825,477, filed Jul. 6, 2007, 25 pages.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6





FIG. 7



VIRTUAL INPUT SYSTEM

PRIORITY CLAIM

This application is a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 13/618,910, filed on Sep. 14, 2012, which is a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 13/077,606, filed on Mar. 31, 2011, which issued as U.S. Pat. No. 8,398,488 on Mar. 19, 2013, which is a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 10/921,518, filed on Aug. 19, 2004, which issued as U.S. Pat. No. 7,942,744 on May 17, 2011, the entire contents of each of which are incorporated herein by reference.

TECHNICAL HELD

The present invention relates to a system for providing a virtual input, such as for an electronic gaming machine.

BACKGROUND OF THE INVENTION

Player interaction with a gaming machine is typically limited to touching a touch screen sensor or depressing an electro-mechanical switch. A touch screen sensor usually fits the shape and size of an associated active display, such as an LCD or a CRT.

A typical gaming touch screen assembly consists of a touch screen sensor attached to the front surface of an active display device, such as a CRT or an LCD. The sensor is connected to a touch screen controller, which sends touch position data to the game controller. The basic sensor material is typically plastic or glass and requires a transparent conductive oxide (TCO) layer, such as Indium Tin Oxide (ITO), wires or acoustic components to work. The specifics depend on the type of touch screen technology (capacitive, resistive, acoustic and near-field).

The sensor surfaces are typically flat, but could be slightly curved, such as for example CRT's. All of these conventional sensor technologies have limitations when dealing with large surface sizes, non-planar or discontinuous surfaces, and no-contact requirements. This limits the areas where a touch screen can be used on a gaming machine, or other systems requiring such user input.

Additionally, electro-mechanical switches have limitations. Electro-mechanical switches have been used on gaming machines for decades. The number of switches is limited by the size of the mechanical panel. And when the game on the gaming machine is changed, the switches and/or labels must be replaced. Therefore, they are not programmable and must be located in a convenient location for the player to reach.

A primary objective of this invention is to provide another form of user input, such as for a gaming machine, other than using a conventional physical surface or mechanical device. The present system is able to sense a touch on a virtual surface. The virtual surface may be in the middle of the air. The virtual surface may be close to the actual surface, so close it seems that it was a physical touch.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a virtual input system according to the present invention;

FIG. 2 is a block diagram of a Doppler radar sensor module as utilized by the virtual input system of FIG. 1;

FIG. 3 is a block diagram of an ultrasonic sensor module as utilized by the virtual input system of FIG. 1;

FIGS. 4a and 4b are respective front and side views of a gaming machine top box which utilizes the virtual input system of FIG. 1;

FIG. 5 is a view of a hemispherical display of the top box of FIGS. 4a and 4b;

FIG. 6 is a block diagram of an IR camera sensor according to the present invention; and

FIG. 7 is a block diagram of an IR/laser scanning sensor, according to the invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

While this invention is susceptible of embodiments in many different forms, there is shown in the drawings and will herein be described in detail, preferred embodiments of the invention with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the broad aspect of the invention to the embodiments illustrated.

The present invention is described herein with respect to an interactive game surface device (IGSD) 10, a specific embodiment for use in conjunction with a gaming machine. It should be understood that the present invention is also applicable for use with other systems requiring similar user input.

The IGSD 10 allows any surface, non-conductive or otherwise, to be used for player input. It allows a player to touch an animated figure or a non-planar display in a top box of a gaming device, discussed below. The IGSD 10 also allows the player to use a hand or body movement as an interactive input.

In a first embodiment, the IGSD 10 includes a first sensor module, such as a lower power Doppler radar sensor module 12, and a second sensor module, such as an ultrasonic sensor module 14. Alternatively, and as discussed further below, the IGSD may include only single Doppler radar sensor module, multiple Doppler radar sensor modules, an IR camera, or an infrared/laser scan sensor.

According to Doppler radar theory, a constant frequency signal that is reflected off a moving surface, in this case the skin or clothing of the player, will result in a reflected signal at the same frequency, but with a time varying phase indicative of the relative motion.

In the first embodiment, the Doppler radar sensor module 12 senses movement of all or part of the body via skin or clothing reflections. The Doppler radar sensor module 12 could sense the light movement of the fingers, even the beating of a heart.

With software mapping, the Doppler radar sensor module 12 can sense net amount of motion, mean speed, and average direction for objects in its field of view. With frequency modulation, the Doppler radar sensor module 12 can sense range.

The Doppler radar sensor module 12 must be physically located such that it has a view of the player unobstructed by a surface which is opaque to radar, such as a conductive surface. The center of the field of sensing of the Doppler radar sensor module 12 is usually perpendicular to the orientation of its antenna. The Doppler radar sensor module 12 could be mounted at the side of the gaming machine and aimed so that its field of sensing goes across, or on top of, a surface, which could be metal. The field of sensing would be limited, but this might be desirable for a particular application.

The ultrasonic sensor module 14 utilizes sound energy, or sonar signals, at frequencies of 20 to 100 Kh range. Solid

objects reflect this sound energy, and the time difference between transmission and reception indicates range and direction.

Radar signals and sonar signals have different reflective and speed characteristics. Therefore, they are a good combination when dealing with distances between 2-3 cm to 5 meters.

The IGSD **10** also includes an IGSD controller **18**, such as a dedicated embedded controller or a standard microprocessor. The IGSD controller **18** provides control, power, interface, and data translation for the Doppler radar and ultrasonic sensor modules **12**, **14**. The IGSD controller **18** also includes a conventional USB communication channel **20** to a host **24**.

The Doppler radar sensor module **12** uses a low power (<10 mw) 2.45 Ghz microwave sensor. Referring to FIG. 2, the Doppler radar sensor module **12** includes a first micro-patch array **26** as a receiving antenna and a second micro-patch array **28** as a transmitting antenna.

The radar module **12** can be configured for continuous wave (CW) operation or for frequency modulated/continuous wave (FM-CW) operation. The CW configuration provides simple motion detection only. The FM-CW configuration adds range sensing.

The Doppler radar sensor module **12** is provided with a 15 to 20 degree beam-width with a range of 20 to 1 feet. Depending on the location of the antennas **26**, **28** of the Doppler radar sensor module **12** within the gaming machine, not only can the Doppler radar sensor module **12** detect objects at the front of the gaming machine, but also hands and fingers touching the surface of the gaming machine.

The Doppler radar sensor module **12** can provide motion and range detection. However when the Doppler radar sensor module **12** is used alone, there can be problems with reflections and noise from multiple sources, such as large groups of people or metal carts in the vicinity of the gaming machine. This potential problem can be minimized or prevented by using multiple radar modules **12**, discussed below. However, one can preferably also use ultrasonic sensors on the low side of the electromagnetic frequency spectrum, as also discussed below.

As illustrated in FIG. 3, the ultrasonic sensor module **14** drives several 38-80 kHz ultrasonic transceivers, or sensors, **30**. Each of the ultrasonic sensors **30** includes an ultrasonic transmitter **30a** and an ultrasonic receiver **30b**. The ultrasonic sensors **30** are small, cylindrical sensors which can be installed in various points on the gaming machine. The sensors **30** connect to the rest of the ultrasonic module **14** via cable. Using data processing, the IGSD controller **18** determines the best data image.

Although the IGSD controller **18** preferably includes dual ultrasonic sensors, one sensor can be used, or two of the same type of sensor. Other types of sensors could be used if the application requires such, such as an optical sensor.

Referring to FIG. 1, the IGSD controller **18** provides control and data translation. The USB communication interface **20** is provided between the IGSD controller **18** and the host system **24**. The host system **24** provides set-up information, which is used by the IGSD controller **18** and the sensor modules **12**, **14**.

The sensor modules **12**, **14** acquire data in the form of sensor images. After data processing, the modules **12**, **14** send data streams to the IGSD controller **18**. The IGSD controller **18** processes this data, looking for sequences and combinations that match parameters loaded in during a set-up routine. For example, the host system **24** wants the IGSD **10** to perform two functions: 1) provide a people sensor during an attract mode; and 2) provide touch data during bonus mode.

The host system **24** continuously provides mode status to the IGSD **10**, which in turn changes the parameters for determining what data, and when data, is sent to the host system **24**.

Each of the sensor modules **12**, **14**, includes a respective processor **12a**, **14a**. The present system was designed to maximize the workload of the processors **12a**, **14a**, on each respective sensor module **12**, **14**, allowing the IGSD controller **18** to handle the integration of both data images from the modules **12**, **14**. This could be a function of the host system **24** if the processor of the host system **24** could handle the extra workload and use USB communication. This would eliminate the IGSD controller **18**, or at least function of the IGSD controller **18**.

The Doppler radar sensor module **12** is illustrated in detail in FIG. 2. The Doppler radar sensor module **12** interfaces to the IGSD controller **18** via a conventional USB connection. The processor **12a** of the Doppler radar sensor module **12** is a digital signal processor (DSP), such as a Texas Instruments TMS320 series DSP. The radar sensor module **12** uses the radar sensor module processor **12a** for control, sampling, filtering and data processing.

The radar sensor module **12** includes an RF Oscillator **34** set for 2.45 Ghz. In the CW mode, this is the frequency of the transmitting signal. In the FM-CW mode, a voltage controlled oscillator (VCO) **36** provides a frequency control voltage to the RF Oscillator **34**. The output of the RF oscillator **34** drives the transmitting antenna **28** via a directional coupler **35**. The signal is coupled to the receiving input, which is mixed by a mixer **38** with the signal from the receiving antenna **26**. The output of the mixer **38** is an IF frequency signal, which is the difference of the transmitted and received signals.

In the CW mode, the IF frequency signal relates to the relative velocity of the object. In the FM-CW mode, the IF frequency signal relates to the distance due to function of time. The IF frequency signal is amplified by a programmable IF amplifier **39** and fed to a filter circuit **40**, which helps remove noise. The output of the filter circuit **40** is connected to an A/D input of the radar module processor **12a**. The radar module processor **12a** processes the signal, using peak detection, digital filtering, and measurements, providing a digital image. If the digital image meets certain parameters, depending on the set-up, the radar module processor **12a** could send a complete data stream or just a message.

It should be understood that other radar designs would work. A frequency of 2.45 Ghz is used here because it is in the ISM frequency band, an unlicensed range. However as a result, power output is limited (~20 dbm) due to FCC rules. There could be other frequencies that would operate with more accuracy.

A 4x4 array is used for the micro-strip patch array antennas **26**, **28** of the present embodiment. The 4x4 array is formed of 16 small squares connected together. PCB cladding material is used as part of the layout. The antenna array mandates the sensor be mounted behind a non-conductive surface. Depending on the frequency, the antenna array will change in type and size. Using an array of 4"x4", or smaller, one can place the array in a plastic structure or behind a glass panel. Commercially specialized antennas are available which are designed for specific beam patterns. Other optimal antenna configurations are possible, such as phased antennas, different sized arrays or a helical configuration for narrow beam width. With increased sensitivity and increased data processing, one could sense the vital signs of people standing in front of the machine.

Referring to FIG. 3, ultrasonic sensors operate in the basic mode of transmitting a burst of ultrasonic frequency, and then

5

waiting a certain period of time. Following this period of time, a reflected signal, or echo, of the pulse previously transmitted is received. As is well known, the time between transmission and reception is proportional to the object's distance. Depending on the sensor device, the beam width can be adapted to the application. Using multiple sensor devices and angulation processing improves resolution and accuracy.

The processor **14a** of the ultrasonic module **14** is a micro-processor controller (MPC) **14a**, such as a Philips Semiconductors P8051. The processor **14a** controls operation of the sensor devices and interfaces to the IGSD controller **18** via a conventional USB communications link.

The processor **14a** is connected to an ultrasonic sensor **30**. However, the processor **14a** could control multiple ultrasonic sensors **30**. The limitation is the number of I/O lines on the processor **14a**, and cost. An oscillator **42** oscillates at a frequency set for 38 kHz, matching the sensor specification. The oscillator **42** has two outputs; one is 38 kHz (digital) for the processor **14a**, and the other is a 38 kHz (sin wave) for the transmitters. A gated amplifier **44** controls the length of the burst, plus provide a high voltage output for the transmitter **30a**. The processor **14a** provides control. If multiple sensors **30** are utilized, it is important to gate each ultrasonic transmitter to turn on one at a time, especially if multiple receivers will detect the reflected signal.

Although the beam width for the transmitter is narrow, >10 degrees, and the range is short (5 ft to 2 in), the reflections can be multi-directional depending on the object. All 38 kHz signals are ignored beyond an established time limit. These signals could be reflecting off an object greater than 5 ft or caused by a nearby noise source. A combination filter/peak detector **46** eliminates unwanted frequencies and converts the AC signal into a digital signal for the ultrasonic module controller **14a**.

Data processing by the ultrasonic module controller **14a** provides data analysis, comparing the 38 kHz signal from the oscillator **42** to the received signal in order to determine range and direction. If there are multiple ultrasonic sensors **30**, the ultrasonic module controller **14a** performs various triangulation computations for increased accuracy. The ultrasonic sensor module controller **14a** then sends a data image to the IGSD controller **18**.

There are different circuits and types of ultrasonic sensors that could alternately be used. The 38 kHz sensor is used here because such sensors are very available. However, higher frequencies could be better for using the Doppler effect for detecting moving objects.

Both the Doppler radar sensor module **12** and the ultrasonic sensor module **14** are plagued by unwanted reflections. Accordingly, circuitry is provided to set the receive sensitivity of both the modules **12**, **14**.

The Doppler radar sensor module **12** works better by first adjusting to its environment, so the programmable IF amplifier **39** is utilized. The radar sensor processor **12a** is coupled to the programmable IF amplifier **39**. This provides a 4-level (2 bits binary) programmable control for the programmable IF amplifier **39**.

Referring again to FIG. 3, the programmable Ultrasonic receiver **30b** The ultrasonic sensor processor **14a** is coupled to a programmable amplifier **47** located between the filter/peak detector and the receiver **30b**. The programmable amplifier **47** is also coupled to the processor **14a**, and has eight (3 bits) levels of sensitivity. The programmable amplifies **47** adjusts the sensitivity of the filter/peak detector **46**. When the IGSD **10** is turned on, or goes through a reset, the IGSD controller **18** sends out a control signal to the programmable amplifies **47** to adjust the receiver **30 b** for optimal sensitivity.

6

Optimal sensitivity is achieved by adjusting the respective received signal, measuring any reflections, and then readjusting and repeating. This continues until optimized, under control of the IGSD controller **18**, because it's important to limit only unwanted reflections, not true ones.

After setting optimal operating parameters, if multiple ultrasonic sensors **30** are utilized, the sensors **30** cooperate, using their programmable capabilities. As the reflections move closer to the machine, the ultrasonic sensors **30** are given the command to reduce sensitivities, removing background reflections. There could be cases when one wants the sensors to adjust for maximum sensitivity.

According to a second embodiment, a second Doppler radar sensor modules **12** is utilized instead of the ultrasonic sensor module **14**. Using two Doppler radar sensor modules **12** provides greater flexibility in design. A Doppler radar sensor will not work behind conducting surfaces, such as steel, aluminum, and the like, and the location is important to sense direction of motion. But with two Doppler radar sensors, one can physically locate them in two different areas with overlapping fields of scan where one wants the player to touch. It allows the object to stay in view of both, or at least one, sensor at any time, resulting in no blind spots. Plus, it provides a three dimensional field of view in certain areas, providing a greater detection of other hand movements that could be used for other than playing the machine. For example, one could request a drink by making a particular hand gesture, and the machine will send a signal to the bar ordering the drink. Although this configuration improves accuracy, the cost is higher.

Configuration of the Doppler radar sensor module **12** and the ultrasonic sensor module **14** is as follows. Once set for optimal, both sensors **12**, **14** must report an object in the field of sensing to start the process. If one or both sensors **12**, **14** report an object getting closer, the ultrasonic sensor module **14** reduces its output to check. With more control over the ultrasonic sensor module **14**, one can reduce the number of reflections because the distance the signal can be received from the source has been limited per the square law rule. If a valid reflection is sensed, the Doppler and ultrasonic sensor modules **12**, **14** re-adjust and then re-verify. This repeats until the object is in front of the gaming machine by a player distance. To maximize people interaction with the machine, one could use different attract visuals and sound depending on the distance of the object sensed. Absent software analysis of the motion of the detected object, the IGSD **10** does not know whether it has detected a human, or whether it has detected some other object, such as a vacuum cleaner. With both sensor modules **12**, **14** verifying each other, accuracy is improved.

Once there's an action to begin play of the machine, such as by insertion of a coin, the IGSD **10** knows it has detected a human. The application sends commands to the Doppler radar sensor module **12** via the controller to change the transmitting and receiving parameters to focus on the area between the player and the touch area. If the touch area is very close to the sensor modules **12**, **14**, the ultrasonic sensor module **14** is used to sense the touch, but the Doppler radar sensor module has already notified the IGSD controller **18** that a hand or arm is approaching.

A top-box **50** is illustrated in FIGS. **4a** and **4b**. The top-box **50** is a mechanical structure located above a main cabinet or main game area of a gaming machine (not shown). Top-box designs are used for player attraction and bonus game play, as are well known. There are many types of images displayed on top-boxes, such as spinning wheels, rotating reels, mechanically animated devices or other displays. Some top-box dis-

plays have a non-planar shape, such as a hemispherically formed screen **52**. In one example, as illustrated in FIG. **5**, the image spins or rotates as part of a bonus game. The player can cause the image to stop by touching the image, or extending the player's arm toward the image, but not making actual contact with the actual image.

According to the present invention; the Doppler radar sensor module **12** is located above a video projection unit **54** inside the top-box **50**. Because the surface of the screen **52** is made of rear projection material, the screen **52** has a clear field of view towards the player. The ultrasonic sensors **30** are installed around the bottom of the display and provide additional coverage if the Doppler radar sensor module **12** has a so-called dead spot near the edges of the screen **52**.

Other top-box designs can be in the form of mechanical doors. The player points to one of the doors and/or touches the door; which opens to reveal the amount of the bonus. In this top-box design, the Doppler radar antennas are mounted above the top-box doors, and a respective one of the ultrasonic sensors **30** is located next to each door. The host system **24** notifies the IGSD controller **18** that the game is in a bonus mode. The IGSD controller **18** begins to monitor and translate the data streams from the sensor modules **12**, **14**. In this example, the doors are too far from the player, so the player is required to point to the door. Data from Doppler radar sensor module **12** shows motion and a set direction. The ultrasonic sensor module **14** shows position and a set direction. Triangulation confirms the angle and set direction. Motion stop and data is verified. The IGSD controller **18** sends the result to the host controller **24**.

Typically gaming machines have a silk-screened glass panel below the main play area called the belly glass. Some gaming machines have another one above the main play area called the top glass. Because these glass panels typically go through a silk-screen process, it would be very difficult to use it as a touch-sensor, especially if these touch-sensor/glass panels required a wired connection. This would result in the disconnecting and connecting of the glass panels every time the machine is accessed for troubleshooting or the glass panel is replaced. Using the IGSD **10** of the present invention, no direct connection to the glass panel is required. The Doppler radar sensor module **12** is placed behind the glass panel, and one is able to use the glass panel as a player input.

Another use of the IGSD **10** is for player attraction. Gaming machines use a combination of visuals and sounds to attract players to the machines. With the IGSD **10**, one can have a dynamic attraction. The IGSD **10** can sense people walking by the gaming machine, or stopping to look. This in turn can cause a change in the visuals and sounds, attracting a possible player. Sensing the position and direction, the gaming machine would again change the visuals and sounds as the person nears the machine. Gender can be determined, which enables a different set of visuals and sounds.

In a third embodiment, only a single Doppler radar sensor module **12** is utilized, no ultrasonic, or other sensor. The single Doppler radar sensor module **12** can detect any object in its field of sensing, moving or range and motion, depending on microwave type. The single Doppler radar sensor module **12** will sense motion, speed and direction as an object approaches the machine. It could be used as an object sensor, which would be used to change attract modes. It is unable to distinguish a human from an inanimate object, unless the sensor has the sensitivity, and the IGSD controller **18** has the computing power, to be able to detect heartbeat by sensing the blood flow in the arm or hand, but, such would be a relatively complex configuration.

For example a top box display could respond to the approaching object, with a welcome screen or a preview of a bonus play. The only way to verify the object is a player is to use the attract mode changes, but wait until the host **24** detects the start of a game, such as upon insertion of a coin, before using it as a touch sensor. The disadvantage of the simple configuration compared to configurations with multiple sensors is the possibility of blind area. These are areas within the field of sensing that motion detection can be easily blocked, so the location of the sensor is important. Also, the touch area cannot be too close to the sensor because the Doppler radar sensor module **12** typically cannot detect close objects, such as those within 1 ft. The main advantage of this simple configuration is the cost and the size of the sensor module.

An embodiment utilizing an IR camera sensor **59** is illustrated in FIG. **6**. The IR camera sensor **59** includes an IR camera sensor processor **59a** coupled via an LED driver **60** to an IR emitter array **62**. The IR camera sensor **59** further includes an IR camera **64**, also coupled to the IR camera sensor processor **59a**. The most common configuration of the LED emitter array **62** is a circle of LEDs around the lens of the IR camera **64**. The IR camera **64** has several manual or programmable features, such as focus, sensitivity, and the like. An application program in the IR camera sensor processor **59a** provides noise filtering, gray level conversion, and detection.

The IR emitter array **62** floods the area around the machine with infrared light. To a human, this light is invisible, but not to the IR camera **64**. The human eye acts like a mirror to the IR wavelength. When looking at the machine, the IR light reflects off the retina of the eye, and the lens of the eye focuses this reflected light towards the IR camera **64**. The IR camera **64**, being sensitive to IR light, will sense reflected light, and the IGSD controller **18** can determine, via software application, if the received IR light is actually an eye reflection.

The IR camera **64** can also be used to detect motion, using angular processing as reflections move. However, it cannot accurately determine distance. The IR camera sensor **59** would appear as another device connected to the IGSD controller **18**. The IR camera sensor **59** would be used in conjunction with any of the above described systems.

Alternatively, a standard camera, also designated **64**, can be utilized to detect human form. All of this is to determine if the object detected for motion is actually a human player, rather than some inanimate device.

A final embodiment utilizing an infrared laser scan sensor **70** is illustrated in FIG. **7**. The infrared laser scan sensor **70** is preferably utilized in conjunction with the ultrasonic sensor **30**, discussed above. The infrared laser scan sensor **70** is capable of being mounted in small areas. It can be mounted behind metallic surfaces, although it would require a small opening in the surface. The opening could be covered with plastic or glass, provided the covering is not opaque to the infra red light.

The infrared laser scan sensor comprises an infrared projector **72** and an infrared detector **74**. The infrared projector **72** comprises: (1) an IR or red laser **76**; (2) a reflector device **78**, such as a digital micro-mirror device (DMD), as provided by Texas Instruments, or a MEMS (Micro-Electrical mechanical system) scanner; and (3) a lens **80**. The projector **72** further includes a scanner interface **82** and a laser driver **84**. The scanner interface **82** can be digital drivers, or a DAC, depending on the type of reflector device **78**. The laser module **76** can be continuous, pulsed or modulated, all under control of the processor **70a**.

The reflective device **78** is extremely small, and requires a narrow beam. The lens **80** assures the light beam covers the entire surface to be scanned.

The infrared projector **72** beams light into a prismatic shaped pattern in front of the sensor opening. As is known in the art, the DMD and MEMS use mechanical action to sequentially reflect light from an X-Y array of reflectors under control of the processor **70a**. The reflector located in the upper left corner is first activated, sending the reflected beam out toward a first point in space. Then the next reflector is activated, sending the reflected beam toward a second, adjacent point in space. This continues until each reflector has been activated, at which time the process is repeated.

The high rate of switching between individual reflectors of the reflector device **78** causes a laser beam to be reflected in an X-Y pattern through the lens, forming a prismatic field of sensing. A physical object in this field is scanned by the laser. The infrared detector **74** is coupled to the processor **70a** by a programmable amplifier **86** and a filter/peak detector **88**. The detector **74** detects the reflection of the laser spot (beam) off of the object, generating an output trigger signal. This trigger signal with information identifying the particular reflector activated at that time indicates the location of the illuminated point of the object. The IR detector **78** has a wide field of sensing, and a programmable amplifier **86**, under control of the processor, adjusts the output of the detector **78**.

A hand in the field of scanning could generate hundreds of triggers and each trigger will appear at different X-Y locations. The IGSD **10**, or the host **24** would use angular processing providing motion detection and location, but referencing these as if they were on a single plane of the three dimensional space. Accordingly, the ultrasonic sensor **30** would work in conjunction with the infrared laser sensor **70**

Relative position is determined by using the X-Y coordinates as a reflected signal is detected. Motion can be determined by comparing the relative changes in the reflected signals or by using the Doppler effect. One feature of the laser scan sensor **70** is its ability to outline objects in the field of sensing, such as to distinguish a human outline from that of a cart. The laser scan sensor **70** can also determine the number of people standing in front of the machine. This feature can be used for very interesting attract modes.

Alternatively, an IR camera system could be used to detect the X-Y location of the reflected beam and then use the next set of scans to determine angular movement, although this would be more complex.

The beam scan gets larger further away from the source, like an inverted pyramid. When the ultrasonic sensor detects the object is in the virtual touch area, and the infrared laser scan sensor sends the correct X-Y coordinate, the system determines the touch is valid.

While the specific embodiment has been illustrated and described, numerous modifications come to mind without significantly departing from the spirit of the invention, and the scope of protection is only limited by the scope of the accompanying claims.

The invention is claimed as follows:

1. A device comprising:

an electromagnetic sensor module configured to determine a location of a user input at a virtual input location; a camera configured to detect motion at the virtual input location; and

a controller coupled to the electromagnetic sensor and the camera, wherein the controller is configured to determine whether a portion of the user input is within the virtual input location in a space that defines a virtual input.

2. The device of claim **1**, wherein the controller is configured to generate an output signal indicating an actuation of the virtual input in response to determining that the portion of the user input is within the virtual input location in the space that defines the virtual input.

3. The device of claim **1**, wherein the electromagnetic sensor module comprises a Doppler radar sensor.

4. The device of claim **3**, wherein the Doppler radar sensor comprises at least two micro-patch arrays.

5. The device of claim **4**, wherein a first micro-patch array is configured to operate as a transmitting antenna and a second micro-patch array is configured to operate as a receiving antenna.

6. The device of claim **3**, wherein the Doppler radar sensor is configured to operate using a frequency modulated/continuous wave operation.

7. The device of claim **3**, wherein the Doppler radar sensor has a beam width between about 15 degrees and about 20 degrees.

8. The device of claim **1**, wherein the camera comprises an infrared emitter and an infrared camera.

9. The device of claim **1**, wherein the camera comprises a visible light camera.

10. The device of claim **1**, further comprising: a surface, wherein the space that defines the virtual input is defined substantially on the surface.

11. The device of claim **10**, wherein the surface comprises an image indicating the space that defines the virtual input.

12. The device of claim **11**, further comprising: a projector configured to project the image on the surface.

13. The device of claim **12**, wherein the projector is configured to project the image as moving on the surface.

14. The device of claim **10**, wherein the surface is non-planar.

15. A method comprising: determining, by an electromagnetic sensor module, a location of a user input at a virtual input location; detecting, by a camera, motion at the virtual input location; and

determining, by a controller coupled to the electromagnetic sensor module and the camera, whether a portion of the user input is within the virtual input location in a space that defines a virtual input.

16. The method of claim **15**, further comprising: generating, by the controller, an output signal indicating an actuation of the virtual input in response to determining that the portion of the user input is within the virtual input location in the space that defines the virtual input.

17. The method of claim **15**, wherein the space that defines the virtual input is defined substantially on a surface, and wherein the surface is at least one of a planar surface or a non-planar surface.

18. A system comprising: means for sensing a location of a user input at a virtual input location; means for detecting motion at the virtual input location; and means for determining whether a portion of the user input is within the virtual input location in a space that defines a virtual input, wherein the means for determining is coupled to the means for sensing and the means for detecting.

19. The system of claim **18**, wherein the means for determining comprises: means for generating an output signal indicating an actuation of the virtual input in response to determining that

11

the portion of the user input is within the virtual input location in the space that defines the virtual input.

20. The system of claim **18**, wherein the space that defines the virtual input is defined substantially on a surface, and wherein the surface is at least one of a planar surface or a non-planar surface. 5

* * * * *

12