



US006511322B1

(12) **United States Patent**
Kometas

(10) **Patent No.:** **US 6,511,322 B1**
(45) **Date of Patent:** **Jan. 28, 2003**

(54) **SELF-LIMITING OCCLUSION REDUCTION BURR AND METHOD OF USE**

(76) Inventor: **Athas N. Kometas**, 3162 S. Atlantic Ave., Daytona Beach Shores, FL (US) 32118

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/893,951**

(22) Filed: **Jun. 29, 2001**

(51) **Int. Cl.**⁷ **A61C 3/06**

(52) **U.S. Cl.** **433/166**

(58) **Field of Search** 433/165, 166; 408/85, 86, 241 B; 407/54, 34

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,280,927 A	4/1942	Phillips	
2,453,696 A	11/1948	Brooks	
2,901,826 A	* 9/1959	Kline et al.	433/165
3,101,546 A	* 8/1963	Thomas	433/166
3,309,772 A	* 3/1967	Lieb et al.	433/166
3,576,076 A	4/1971	Weissman	
4,389,192 A	* 6/1983	Neuwirth	433/166
4,526,542 A	7/1985	Kochis	
4,609,352 A	* 9/1986	Riitano	433/165
4,834,655 A	* 5/1989	Kyotani	433/166
4,854,871 A	8/1989	Weissman	
5,100,322 A	3/1992	Weissman	

5,403,187 A	4/1995	Wauchope	
5,575,650 A	* 11/1996	Niznick et al.	433/165
5,839,897 A	11/1998	Bordes	
5,868,572 A	2/1999	Lazzara et al.	
5,890,897 A	4/1999	Kruger et al.	
5,971,758 A	10/1999	Hugo et al.	
6,235,035 B1	* 5/2001	Boukhris	433/165
6,319,005 B1	* 11/2001	Hollander et al.	433/165

* cited by examiner

Primary Examiner—Todd E. Manahan

(74) *Attorney, Agent, or Firm*—Paul S. Rooy

(57) **ABSTRACT**

A self-limiting occlusal reduction burr and method of use. The self-limiting occlusal reduction burr comprises a shank rigidly attached to one end of a conical shoulder, and a burr rigidly attached to an opposite end of the shoulder. The shank, shoulder, and burr are all axially symmetrical about an axis. A shoulder angle is defined by a shoulder outside surface and the axis, and in the preferred embodiment was 39°±20°. The self-limiting occlusal reduction burr may include indicia specifying a length of said burr and/or a diameter of said burr. The method of use includes the steps of determining an appropriate depth reduction required for a given tooth surface, selecting a self-limiting occlusal reduction burr having a burr length and/or burr diameter sized to yield the depth reduction determined, making a groove pattern using the self-limiting occlusal reduction burr selected, and using said self-limiting occlusal reduction burr to connect said grooves in order to yield a tooth reduction of said depth previously determined.

13 Claims, 4 Drawing Sheets




FIG 1




FIG 2




FIG 3




FIG 4




FIG 5 34




FIG 6





FIG 7



**SELF-LIMITING OCCLUSION REDUCTION
BURR AND METHOD OF USE**

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to dental burrs, and in particular to a self-limiting occlusal reduction burr and method of use.

2. Background of the Invention

One of the more common dental procedures currently performed is the installation of a crown on a tooth whose state of decay is such that a filling is not a viable option. The tooth must first be prepared by removal of sufficient tooth material so that a ceramist can create a crown whose appearance is realistic. At the same time, excessive tooth material should not be removed during this preparation step, in order that the maximum feasible amount of good tooth be left intact. The problem of removing the correct amount of tooth material becomes more difficult where occlusal grooves are present. In this case, the deepest part of the occlusal groove should be reached by the reduction tool used, so that enough material is removed.

Existing Designs

One approach suggested to permit tooth reductions of a pre-determined depth to be made is illustrated in U.S. Pat. Nos. 2,280,927, 5,403,187, 4,526,542, 3,576,076, 5,100,322, and 5,890,897, granted to Phillips, Wauchope, Kochis, Weissman, Weissman, and Kruger et al. respectively. The apparatuses of these patents all incorporate a disc-shaped drill stop attached to a drill. When the drill has progressed to a certain depth, the drill stop impinges on the tooth being reduced, and prevents further reduction depth from being achieved.

There are a number of problems associated with this approach. During the tooth preparation step, cooling air/water spray must be constantly played on the cutting surface, in order to prevent over-heating of the tooth being reduced. If insufficient cooling is achieved, the tooth could overheat and suffer nerve damage. Because these prior art disc-shaped stops are possessed of flat faces facing the tooth, it is difficult to get the cooling air/water spray into contact with the drill cutting edges.

Another problem is that the flat faces adjacent the tooth prevent the cutting edge from adequately penetrating the tooth in order to remove sufficient tooth material from the bottom of occlusal grooves. If insufficient material is removed from the tooth being prepared, then it is difficult for the ceramist to make the crown appear realistic.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a self-limiting occlusal reduction burr which can quickly and easily reduce a tooth surface to a pre-determined depth. Design features allowing this object to be accomplished include a burr having a pre-determined burr length, and a shoulder. Advantages associated with the accomplishment of this object include reduced time to make tooth surface reductions, along with the associated cost savings and reduction in patient discomfit time.

It is another object of the present invention to provide a self-limiting occlusal reduction burr whose geometry allows coolant spray to be sent directly to a tooth groove being cut. Design features allowing this object to be accomplished include a conical shoulder having a major diameter and a minor diameter, a shank attached to the shoulder at the shoulder major diameter, and a burr attached to the shoulder

at the shoulder minor diameter. Benefits associated with the accomplishment of this object include better tooth cooling during the reduction operation, consequently less chance of tooth nerve damage, and the associated reduction in patient discomfit.

It is still another object of this invention to provide a self-limiting occlusal reduction burr capable of removing sufficient material from fissures. Design features enabling the accomplishment of this object include a conical shoulder having a major diameter and a minor diameter, a shank attached to the shoulder at the shoulder major diameter, and a burr attached to the shoulder at the shoulder minor diameter. Advantages associated with the realization of this object include more accurate tooth material removal and crowns whose appearance is more realistic.

It is another object of the present invention to provide a method of use for a self-limiting occlusal reduction burr which provides for quick and accurate reduction of a tooth in preparation for attachment of a crown. Method steps allowing this object to be accomplished include determining an appropriate depth reduction required for a given tooth surface, selecting a self-limiting occlusal reduction burr having a burr length and/or burr diameter sized to yield the depth reduction previously determined, making a groove pattern using the self-limiting occlusal reduction burr selected, and using the self-limiting occlusal reduction burr to connect the grooves in order to yield a tooth reduction of the depth previously determined. Benefits associated with the accomplishment of this object include reduced time to make tooth surface reductions, along with the associated cost savings and reduction in patient discomfit time.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention, together with the other objects, features, aspects and advantages thereof will be more clearly understood from the following in conjunction with the accompanying drawings.

Four sheets of drawings are provided. Sheet one contains FIG. 1. Sheet two contains FIGS. 2 and 3. Sheet three contains FIGS. 4 and 5. Sheet four contains FIGS. 6 and 7.

FIG. 1 is a front isometric view of a self-limiting occlusal reduction burr.

FIG. 2 is a side view of a self-limiting occlusal reduction burr cutting a groove in a tooth.

FIG. 3 is a side view of a self-limiting occlusal reduction burr in position, ready to start making a groove into a tooth having a fissure.

FIG. 4 is a side view of tooth into which a groove pattern has been cut.

FIG. 5 is a side view of tooth into which a reduction has been made.

FIG. 6 is a side view of a self-limiting occlusal reduction burr in position, ready to start making a groove into a tooth having a fissure.

FIG. 7 is a side view of a self-limiting occlusal reduction burr making a groove into a tooth having a fissure.

**DETAILED DESCRIPTION OF THE
PREFERRED EMBODIMENT**

FIG. 1 is a front isometric view of self-limiting occlusal reduction burr 2. Self-limiting occlusal reduction burr 2 comprises shank 6 and burr 16 attached to opposite ends of shoulder 12. Shank 6 bears indicia 8 which identifies the size groove which may be cut into a tooth using self-limiting

occlusal reduction burr **2**. Shoulder **12** is conical in shape, and comprises shoulder major diameter **10** at one end, and shoulder minor diameter **14** at an opposite end. Shank **6** is rigidly attached to shoulder **12** at shoulder major diameter **10**, and burr **16** is rigidly attached to shoulder **12** at shoulder minor diameter **14**.

Burr **16** comprises burr abrasive surface **18**, which is used to cut grooves **28** and tooth reductions **34** into tooth **26**. In the preferred embodiment, burr abrasive surface **18** was diamond powder, carbide, tool steel, or other appropriate abrasive surface capable of abrading tooth material.

In use, self-limiting occlusal reduction burr **2** rotates at high speed about axis **4**. Thus, shank **6**, shoulder **12** and burr **16** are all axially symmetrical about axis **4**, that is to say, the cross-sectional shapes of shank **6**, shoulder **12** and burr **16** taken at a cut perpendicular to axis **4** would all be circular.

Defining dimensions of burr **16** include burr length **17** and burr diameter **24**. Referring now also to FIG. 2, defining dimensions of shoulder **12** include shoulder major diameter **10**, shoulder minor diameter **14**, and shoulder angle **20**, which is the side view angle between shoulder outer surface **19** and axis **4**. In the preferred embodiment, shoulder angle **20** was $39^{\circ} \pm 20^{\circ}$.

There are two main reasons for shoulder angle **20** being $39^{\circ} \pm 20^{\circ}$. First, shoulder angle **20** permits coolant spray **22** to be sprayed directly to where it is needed most: the interface between self-limiting occlusal reduction burr **2** and tooth **26** at groove **28**. Second, shoulder angle **20** allows self-limiting occlusal reduction burr **2** to be positioned properly over fissure **30** (as is illustrated in FIG. 3) in order to permit a groove **28** to be cut to the proper depth in and around fissure **30** as depicted in FIGS. 6 and 7. FIG. 6 is a side view of a self-limiting occlusal reduction burr **2** in position, ready to start making a groove **28** into a tooth **26** having a fissure **30**. FIG. 7 is a side view of a self-limiting occlusal reduction burr **2** making a groove **28** into a tooth **26** having a fissure **30**.

Note that in the case of making a reduction in tooth **26** having fissure **30**, the correct place to measure the depth of groove **28** is from fissure shoulder **32**. This is possible to do using the instant self-limiting occlusal reduction burr because of shoulder angle **20**.

The depth groove **28** which may be cut using self-limiting occlusal reduction burr **2** is determined by burr length **17** and burr diameter **24**. Either or both these dimensions are identified by means of indicia **8** inscribed on shank **6**. Indicia **8** may be any means of communicating this information, including but not limited to numbers, letters, color bands, etc.

FIG. 4 is a side view of tooth **26** into which a groove **28** pattern has been cut. FIG. 5 is a side view of tooth **26** into which tooth reduction **34** has been made. FIGS. 4 and 5 illustrate two of the instant method steps of tooth reduction in preparation for attaching a crown.

First, a self-limiting occlusal reduction burr **2** of correct burr **16** dimensions is selected. This step is important, because burr length **17** serves as a visual aid to make grooves **28** of the correct depth. For example, a porcelain to gold crown typically requires a tooth reduction of 2.5 mm, a porcelain crown requires 2.0 mm, and a pure gold crown 1.5 mm. The side of the tooth facing the outside of the mouth may require a 2.5 mm reduction, while the back side of the tooth may be reduced only 1.5 mm.

In use, self-limiting occlusal reduction burr **2** is used to make a groove of depth such that shoulder minor diameter **14** is flush with the surface of the tooth **26** being prepared.

As soon as self-limiting occlusal reduction burr **2** has penetrated the tooth until shoulder minor diameter **14** is flush with the tooth surface, self-limiting occlusal reduction burr **2** is moved sideways in order to produce a constant-depth groove.

A pattern of these constant-depth grooves **28** is cut into tooth **26** as may be observed in FIG. 4. Once the groove **28** pattern has been made, self-limiting occlusal reduction burr **2** is used to connect the grooves **28** into tooth reduction **34** as is shown in FIG. 5. Tooth reduction **34** is made of appropriate size and depth as required for the crown to be attached.

Thus, the instant method of use for a self-limiting occlusal reduction burr **2** comprises the following steps:

- A. Determining an appropriate depth reduction required for a given tooth surface;
- B. Selecting a self-limiting occlusal reduction burr having a burr length and/or burr diameter sized to yield the depth reduction determined in step A;
- C. Making a groove pattern using the self-limiting occlusal reduction burr selected in step B, making each groove only deep enough for a self-limiting occlusal reduction burr shoulder minor diameter to be flush with the tooth surface when the burr is touching the bottom of the groove; and
- D. Using the self-limiting occlusal reduction burr to connect the grooves in order to yield a tooth reduction of the depth determined in step A.

While a preferred embodiment of the invention has been illustrated herein, it is to be understood that changes and variations may be made by those skilled in the art without departing from the spirit of the appending claims.

DRAWING ITEM INDEX

- 2 self-limiting occlusal reduction burr
- 4 axis
- 6 shank
- 8 indicia
- 10 shoulder major diameter
- 12 shoulder
- 14 shoulder minor diameter
- 16 burr
- 17 burr length
- 18 burr abrasive surface
- 19 shoulder outside surface
- 20 shoulder angle
- 22 coolant spray
- 24 burr diameter
- 26 tooth
- 28 groove
- 30 fissure
- 32 fissure shoulder
- 34 tooth reduction

I claim:

1. A self-limiting occlusal reduction burr comprising a shank, a shoulder and an abrasive burr, said shoulder being non-abrasive and conical in shape and comprising a shoulder major diameter at one end and a shoulder minor diameter at an opposite end, said shank being rigidly attached to said shoulder at said shoulder major diameter, and said burr being attached to said shoulder at said shoulder minor diameter.

2. The self-limiting occlusal reduction burr of claim 1 wherein said shank, said shoulder, and said burr are all axially symmetrical about an axis.

3. The self-limiting occlusal reduction burr of claim 2 wherein said shoulder comprises a shoulder outer surface

5

and a shoulder angle, said shoulder angle being defined as an angle between said shoulder outer surface and said axis, said shoulder angle being $39^{\circ}\pm 20^{\circ}$.

4. The self-limiting occlusal reduction burr of claim 3 wherein said shank further comprises indicia, said indicia specifying a length of said burr and/or a diameter of said burr.

5. The self-limiting occlusal reduction burr of claim 4 wherein said burr is coated with abrasive.

6. The self-limiting occlusal reduction burr of claim 5 wherein said burr abrasive is diamond powder.

7. The self-limiting occlusal reduction burr of claim 6 wherein said burr is a cylinder whose axis corresponds to said self-limiting occlusal reduction burr axis.

8. A self-limiting occlusal reduction burr comprising a shank, a shoulder and an abrasive burr all axially symmetrical about an axis, said shoulder being non-abrasive and conical in shape and comprising a shoulder outside surface, a shoulder angle, a shoulder major diameter at one end and a shoulder minor diameter at an opposite end, said shank being rigidly attached to said shoulder at said shoulder major diameter, and said burr being attached to said shoulder at said shoulder minor diameter, said shoulder angle being defined as an angle between said shoulder outer surface and said axis, and said shoulder angle measures $39^{\circ}\pm 20^{\circ}$.

9. The self-limiting occlusal reduction burr of claim 8 wherein said burr is covered with abrasive.

10. The self-limiting occlusal reduction burr of claim 9 further comprising indicia specifying a length of said burr and/or a diameter of said burr.

11. A method of use of self-limiting occlusal reduction burr, said self-limiting occlusal reduction burr comprising a shank, a shoulder and an abrasive burr all axially symmetrical about an axis, said shoulder being non-abrasive and conical in shape and comprising a shoulder outside surface,

6

a shoulder angle, a shoulder major diameter at one end and a shoulder minor diameter at an opposite end, said shank being rigidly attached to said shoulder at said shoulder major diameter, and said burr being attached to said shoulder at said shoulder minor diameter, said method comprising the steps of:

A. Determining an appropriate depth reduction required for a given tooth surface;

B. Selecting a self-limiting occlusal reduction burr having a burr length and/or burr diameter sized to yield the depth reduction determined in step A;

C. Making a groove pattern using the self-limiting occlusal reduction burr selected in step B substantially perpendicular to said tooth surface, whereby the conical shoulder shape provides enhanced cooling and improved access to said tooth surface, making each groove only deep enough for said self-limiting occlusal reduction burr shoulder minor diameter to be flush with said tooth surface when the burr is touching a bottom of said grooves; and

D. Using said self-limiting occlusal reduction burr to connect said grooves in order to yield a tooth reduction of said depth determined in step A.

12. The method of use of a self-limiting occlusal reduction burr of claim 11 comprising the further step of spraying coolant spray onto said burr in order to prevent said tooth from over-heating.

13. The method of use of a self-limiting occlusal reduction burr of claim 11 comprising the further step of measuring a groove made with said self-limiting occlusal reduction burr into a tooth fissure such that a correct groove depth is achieved when said shoulder minor diameter is flush with a fissure shoulder.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,511,322 B1
DATED : January 28, 2003
INVENTOR(S) : Kometas, Athas N.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4,

Line 61, "buff..." should be -- burr... --

Column 5,


Line 31, "A method of use of self-limiting..." should be -- A method of use of a self-limiting... --

Column 6,

Line 13, "buff..." should be -- burr... --

Signed and Sealed this

Third Day of June, 2003

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

JAMES E. ROGAN
Director of the United States Patent and Trademark Office