

US009094525B2

(12) **United States Patent**
Dye et al.

(10) **Patent No.:** **US 9,094,525 B2**
(45) **Date of Patent:** ***Jul. 28, 2015**

(54) **AUDIO-VIDEO MULTI-PARTICIPANT CONFERENCE SYSTEMS USING PSTN AND INTERNET NETWORKS**

USPC 370/260–263, 265, 352–356
See application file for complete search history.

(71) Applicant: **VPN Multicast Technologies LLC**,
Plano, TX (US)
(72) Inventors: **Thomas Dye**, Austin, TX (US); **Thomas Dundon**, San Marcos, TX (US)
(73) Assignee: **VPN Multicast Technologies LLC**,
Plano, TX (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,805,805 A 9/1998 Civanlar et al.
6,041,166 A 3/2000 Hart et al.

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 01/91397 A2 11/2001
WO WO 02/098063 A1 12/2002
WO WO 03003665 A1 1/2003

OTHER PUBLICATIONS

Higgins, L. et al., “Tunneling Multicast Traffic Through Non-Multicast Aware Networks and Encryption Devices,” MILCOM 2001, Proceedings. Communications for Network-Centric Operations: Creating the Information Force, McLean, VA Oct. 28-30, 2001; IEEE Military Communications Conference, New York, NY: IEEE, US, vol. 1 of 2, Oct. 28, 2001, pp. 296-300.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 105 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/674,233**

(22) Filed: **Nov. 12, 2012**

(65) **Prior Publication Data**

US 2013/0162754 A1 Jun. 27, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/646,892, filed on Dec. 23, 2009, now Pat. No. 8,339,997, which is a continuation of application No. 10/796,560, filed on Mar. 9, 2004, now Pat. No. 7,664,056.

(60) Provisional application No. 60/453,307, filed on Mar. 10, 2003.

(51) **Int. Cl.**
H04L 12/66 (2006.01)
H04M 3/56 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04M 3/568** (2013.01); **H04L 12/1818** (2013.01); **H04L 12/4641** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04M 3/56; H04M 7/006; H04M 3/561; H04L 29/06027; H04L 29/06326; H04L 49/25; H04L 49/30; H04L 12/64; H04L 12/6418; H04Q 2213/13204


Primary Examiner — Suhan Ni

(74) *Attorney, Agent, or Firm* — Martin & Ferraro, LLP

(57) **ABSTRACT**

A multi-participant conference system and method is described. The multi-participant system includes a PSTN client, at least one remote client and a first participant client. The PSTN client communicates audio data and the remote clients communicate audio-video data. The first participant client includes a voice over IP (VoIP) encoder, a VoIP decoder, a first audio mixer, and a second audio mixer. The VoIP encoder compresses audio data transported to the PSTN client. The VoIP decoder then decodes audio data from the PSTN client. The first audio mixer mixes the decoded audio data from the PSTN client with the audio-video data from the first participant into a first mixed audio-video data stream transmitted to the remote client. The second audio mixer mixes the audio-video data stream from the first participant with the audio-video data stream from each remote client into a second mixed audio transmitted to the PSTN client.

20 Claims, 6 Drawing Sheets



- (51) **Int. Cl.**
H04N 7/15 (2006.01)
H04L 12/18 (2006.01)
H04L 12/46 (2006.01)
H04L 29/06 (2006.01)
H04M 7/12 (2006.01)
H04M 7/00 (2006.01)
- (52) **U.S. Cl.**
CPC **H04L29/06027** (2013.01); **H04L 65/1009**
(2013.01); **H04L 65/4038** (2013.01); **H04M**
3/567 (2013.01); **H04M 7/1225** (2013.01);
H04N 7/15 (2013.01); **H04M 7/009** (2013.01);
H04M 2207/35 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,047,325	A	4/2000	Jain et al.
6,298,062	B1	10/2001	Gardell
6,526,056	B1	2/2003	Rekhter et al.
6,640,251	B1	10/2003	Wiget et al.
6,728,358	B2	4/2004	Kwan
6,751,477	B1	6/2004	Alperovich et al.
6,778,531	B1	8/2004	Kodialam et al.
6,788,681	B1	9/2004	Hurren et al.
6,870,842	B1	3/2005	Caronni et al.
6,977,929	B1	12/2005	Caronni et al.
6,981,022	B2	12/2005	Boundy
7,203,957	B2	4/2007	Balissat et al.
7,281,058	B1	10/2007	Shepherd et al.
7,330,468	B1	2/2008	Tse-Au
7,339,929	B2	3/2008	Zelig
7,366,894	B1	4/2008	Kalimuthu et al.
7,444,425	B2	10/2008	Lehmann et al.
7,447,203	B2	11/2008	Chen et al.
7,447,901	B1	11/2008	Sullenberger et al.
7,461,157	B2	12/2008	Ahlard
7,562,386	B2	7/2009	Balissat et al.
7,570,648	B2	8/2009	Hu et al.
7,653,192	B1	1/2010	Sylvain
7,664,056	B2	2/2010	Dye
7,724,744	B2	5/2010	Shur et al.
7,830,787	B1	11/2010	Wijnands et al.
8,339,997	B2	12/2012	Dye
8,477,778	B2	7/2013	Lehman et al.
2002/0016926	A1	2/2002	Nguyen
2002/0029350	A1	3/2002	Cooper et al.
2003/0110288	A1	6/2003	Ramanujan et al.
2003/0137976	A1	7/2003	Zhu et al.
2003/0147392	A1	8/2003	Hayashi et al.
2003/0235338	A1	12/2003	Dye
2004/0022322	A1	2/2004	Dye
2006/0039388	A1	2/2006	Shur et al.
2010/0228879	A1	9/2010	Wiget et al.
2011/0043601	A1	2/2011	Dye
2013/0163480	A1	6/2013	Dye

OTHER PUBLICATIONS

International Search Report, International Application No. PCT/US2004/007341, mailed Sep. 7, 2004.
U.S. Appl. No. 14/590,791, filed Jan. 2015, Dye.
VPN Multicast Technologies LLCv. AT&T Inc. and AT&T Corporation; Complaint; Case No. 2:14-cv-1013; Oct. 31, 2014; 8 pages.
VPN Multicast Technologies LLCv. Dimension Data North America, Inc., Dimension Data Holdings PLC, and Dimension Data, LLC; Complaint; Case No. 2:14-cv-1014; Oct. 31, 2014; 8 pages.
VPN Multicast Technologies LLCv. AT&T Inc. and At&T Corporation; VPN Multicast Technologies LLCv. Dimension Data North America, Inc., Dimension Data Holdings PLC, and Dimension Data, LLC; Dimension Data North America, Inc.'s Answer and Affirmative Defenses to Plaintiffs First Amended Complaint; Case Nos. 2:14-cv-1013 and 2:14-cv-1014; Jan. 29, 2015; 15 pages.

International Telecommunications Union Recommendation H.323, Titled "Packet Based Multimedia Communication System," Nov. 2000, 258 pages.
International Telecommunications Union Recommendation H.261, Titled "Video Codec for Audio Visual Services at Px64 kbps," Mar. 1993, 29 pages.
International Telecommunications Union Recommendation H.263, Titled "Video Coding for Low Bit-Rate Communications," Feb. 1998, 167 pages.
VPN Multicast Technologies LLCv. AT&T Corp.; VPN Multicast Technologies LLCv. Dimension Data North America, Inc., et al., Plaintiffs Responses to Defendants' First Set of Common Interrogatories to VPN Multicast Technologies LLC, Case Nos. 2:14-cv-1013 and 2:14-cv-1014, Apr. 14, 2015, 28 pgs.
VPN Multicast Technologies LLCv. AT&T Corp.; VPN Multicast Technologies LLCv. Dimension Data North America, Inc., et al.; Defendants' Invalidity Contentions including Appendix A and Claim Charts; Case Nos. 2:14-cv-1013 and 2:14-cv-1014; Apr. 16, 2015; 2,274 pages.
VPN Multicast Technologies LLCv. AT&T Corp.; VPN Multicast Technologies LLCv. Dimension Data North America, Inc., et al.; AT&T's Objections and Responses to VPN's First Set of Common Interrogatories; Case Nos. 2:14-cv-1013 and 2:14-cv-1014; Apr. 23, 2015; 20 pages.
Alchaal et al., "Offering a Multicast Delivery Service in a Programmable Secure IP VPN Environment," Fourth International Workshop on Networked Group Communication (NGC '02), 2002, 6 pgs.
Bokun et al., "The Meccano Internet Multimedia Conferencing Architecture," Multimedia Education and Conferencing Collaboration over ATM Networks and Others (MECCANO), Ver. 3.1.2, Dec. 1999, 67 pgs.
Cisco Systems, Inc., "Multicast VPN Design Guide—Cisco Systems," Aug. 9, 2003, 25 pgs.
Cisco Systems, Inc., "Multicast VPN—IP Multicast Support for MPLS VPNs," 2002, 86 pgs.
Cisco Systems, Inc., "Networkers: Multicast Support for MPLS/BGP VPNs: RST-322," cisco.com, 2001, 89 pgs.
Comer, "Internetworking with TCP/IP vol. I: Principles, Protocols, and Architecture," Third Edition, Mar. 1995, 628 pgs.
Costa et al., "An Introduction to Virtual Private Networks: Towards D-VPNs," Network and Information Systems Journal, vol. 2, Jun. 2000, 20 pgs.
Eriksson, "MBONE: The Multicast Backbone," ACM Communications of the ACM 37, Aug. 8, 1994, pp. 54-60, 11 pgs.
Finlayson, "The UDP Multicast Tunneling Protocol," Network Working Group, Internet Draft, Nov. 19, 1997, 6 pgs.
Kent et al., "Security Architecture for the Internet Protocol," Network Working Group, Request for Comments: 2401, Obsoletes: 1825, Category: Standards Track, Nov. 1998, 61 pgs.
Kirstein et al., "The RadioActive Networking Architecture," IEEE, DARPA Active Networks Conference and Exposition, 2002. Proceedings, May 2002, 16 pgs.
Kumar, "MBone: Interactive Multimedia on the Internet," New Riders Publishing, 1996, 242 pgs.
Labonte et al., "Group Management Strategies for Secure Multicasting on Active Virtual Private Networks," IEEE, 25th annual IEEE Conference on Local Computer Networks, pp. 213-222, Nov. 2000, 10 pgs.
Lamaster et al., "Internet technologies and requirements for telemedicine," Minimally Invasive Therapy and Allied Technologies 1997, vol. 6, No. 5-6, pp. 436-443, 1997, 8 pgs.
Macedonia et al., "MBone Provides Audio and Video Across the Internet," U.S. Naval Post Graduate School Website, available at <http://www.nps.edu/library>, Apr. 1994, 8 pgs.
Rosen et al., "Multicast in MPLS/BGP VPNs," Network Working Group, Internet Draft, Nov. 2000, 17 pgs.
Savetz et al., "MBONE: Multicasting Tomorrow's Internet," IDG Books Worldwide, Inc., 1996, 259 pgs.
Waitzman et al., "Distance Vector Multicast Routing Protocol," Networks Working Group, Request For Comments: 1075, Nov. 1988, 24 pgs.
Wittmann et al., "Multicast Communication: Protocols and Applications," Morgan Kaufmann Publishers, 1999, 362 pgs.




FIG. 1
(Prior Art)




FIG. 2
(Prior Art)




FIG. 3




FIG. 4




FIG. 5




FIG. 6

**AUDIO-VIDEO MULTI-PARTICIPANT
CONFERENCE SYSTEMS USING PSTN AND
INTERNET NETWORKS**

PRIORITY CLAIM

This application is a continuation of U.S. patent application Ser. No. 12/646,892, filed Dec. 23, 2009, which is a continuation of U.S. patent application Ser. No. 10/796,560, now U.S. Pat. No. 7,664,056, filed Mar. 9, 2004, which claims priority of U.S. Provisional Application No. 60/453,307, filed Mar. 10, 2003; wherein all of the above referenced applications are incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to computer system architectures and more particularly to audio and video telecommunications for collaboration over hybrid networks.

2. Description of the Related Art

Since their introduction in the early 1980's, audio/video conferencing systems ("video conferencing systems") have enabled users to communicate between remote sites using telephone lines based on dedicated or switched networks. Recently, technology and products to achieve the same over Internet Protocol have been attempted. Many such systems have emerged on the marketplace. Such systems produce low-frame-rate and low quality communications due to the unpredictable nature of the Internet. Such connections have been known to produce long latencies with limited bandwidth, resulting in jerky video, dropped audio and loss of lip sync.

Therefore, most video conferencing solutions have relied on dedicated switched networks such as T1/T3, ISDN or ATM. These systems have the disadvantage of higher cost and complexity and a lack of flexibility due largely to interoperability issues and higher cost client equipment. High costs are typically related to expensive conferencing hardware and dedicated pay-per-minute communications usage. Most often these dedicated communications circuits are switched circuits which use a fixed bandwidth allocation.

In most prior art systems the public switched telephone network (PSTN) is used to transfer audio during conferencing and collaboration with remote parties. It is known that quality of audio reception is poor over typical prior art Internet protocol (IP) systems. Prior art audio/video conferencing systems which use IP networks for audio and video transport lack the ability to terminate audio to client end systems through both PSTN and IP networks. Thus, it is desirable to achieve a hybrid mix of audio and video data over PSTN and IP-based audio/video conferencing to achieve full duplex real-time operation for all conference participants.

Modem voice over IP telephony systems have used the H.323 standard from the international telecommunications union (ITU). The H.323 standard focuses on the transmission of audio and video information through the Internet or switched private networks. FIG. 1 illustrates a prior art H.323 system. The block diagram of FIG. 1 includes a number of major components, including the general Internet 435, Internet H.323 bridges or gateways 411, telecommunications PSTN 433 (Public Switched Telephone Network), wireless and land-line phone handsets 412/413, standard Internet router 453, an optional gatekeeper 205, a multipoint control unit 203, a standard local area network 457, a voice over IP server running the H.323 protocol 201, and multiple I/O and display terminals 455. FIG. 1 is an example of the prior art

conferencing system used between hybrid networks connecting the PSTN and Internet. Hybrid networks are used to communicate audio on internal LAN and WAN networks as well as transfer of audio to the existing telephone or PSTN network. While the H.323 recommendation allows for video conferencing, the prior art systems use private switched networks to establish transport that require expensive H.323 bridges between dedicated networks and the PSTN. Each of the components in FIG. 1 serves this purpose to achieve audio telecommunications between multiple parties.

Referring again to FIG. 1, the components of FIG. 1 are interconnected as follows. Prior art technology uses PC or client terminals 455 connected through a local area network 457 to either a data server or a specialized audio/video server 201. The network server 201 contains the application necessary to generate the H.323 network protocol. The data server 201 may be connected to a local gatekeeper 205 that is responsible for management control functions. As known the gatekeeper 205 is responsible for various duties such as admission control, status determination, and bandwidth management. Data server 201 functions are specified and handled through the ITU-H.225.0RAS recommendations. In addition, management control unit (MCU) 203 is connected to the data server 201. The multipoint control unit of a 203 is required by the eight-step ITU-5 H.323 recommendation for flexibility to negotiate end points and determine compatible setups for any conference media correspondents. The multipoint control unit 203 enables communication between three or more end points. Similar to a multipoint bridge, the gatekeeper 205 and the multipoint control unit 203 are optional components of the H.323 enabled network. Another useful job of the multipoint control unit 203 is to determine whether to unicast or multicast the audio or video streams. As known by one skilled in the art, these decisions are dependent on the capability of the underlying network and the topology of the multipoint conference. The multipoint control unit 203 determines the capabilities of each client terminal 455 and status each of media stream.

Again referring to FIG. 1, a standard network router 453 is connected between the local area network 457 and the Internet 435. At the outer edges of the Internet, "points of presence" are located at multiple end points or call termination sites. Gateways 411 are used to transcode the H.323 network information onto the PSTN 433. Standard telephone handsets 413 or wireless phones 412 are connected to the PSTN telephony system.

FIG. 2 illustrates the embodiment of the H.323 protocol stack 200, its components and their interfaces to the local area network computers at the network interface 300. The input and control devices 455 along with a local area network 457 of FIG. 1 are shown in FIG. 2, consisting of the audio input output block 452, the video input and output block 451, the system control unit and data collaboration unit 459. These input devices are largely responsible for the delivery of media data to the H.323 protocol stack 200 shown in FIG. 2.

Again referring to FIG. 2, the sub blocks of functionality that make up the H.323 protocol stack 200 is described. The H.323 protocol stack consists of an audio codec 214, and a video CoDec 213 connected to the audio/video input and output blocks 452 and 451, respectively. The audio and video CoDecs are responsible for compression and decompression of the audio and video sources. The real-time network protocol component 215 is connected to the audio video CoDecs and is also responsible for preparation of the media data for transport according to the RTP (real-time protocol) recommendations.

Again referring to the prior art system of FIG. 2, the H.323 protocol stack has a system control unit 459 which connects to multiple control blocks within the H.323 protocol stack 200. The system control unit connects to the RTC Protocol block 217 for real time transport of the control information used to set-up and tear down the conference. The system control unit 459 also connects to the call-signaling units 221 and 219 for call signaling protocols and media stream packetization application used for packet-based multimedia communications. The system control unit 459 also connects to the control signaling block 223 used for control of protocols for multimedia communications. Lastly, the H.323 recommendation defines a data collaboration capability as known and outlined in the T.120 data collaboration unit 225.

All of the defined blocks make up the H.323 protocol network interface to the Transport protocol and network interface unit 300 for transport of data through the modem or router 453 to the Internet 435.

SUMMARY OF THE INVENTION

A multi-participant conference system is described. The multi-participant system comprises a public switched telephone network (PSTN) client, at least one remote client, and a first participant client. The PSTN client is configured to communicate audio data. Each of the remote clients is connected to the Internet and is configured to receive audio-video data. The first participant client is configured to receive audio-video data. The first participant client includes a voice over IP (VoIP) encoder, a VoIP decoder, a first audio mixer, and a second audio mixer. The VoIP encoder compresses audio data transported to the PSTN client. The VoIP decoder then decodes audio data from the PSTN client. The first audio mixer mixes the decoded audio data from the PSTN client with the audio-video data from the first participant into a first mixed audio-video data stream. The first mixed audio-video data stream is then transmitted to the at least one remote client connected to the Internet. The second audio mixer mixes the audio-video data stream from the first participant with the audio-video data stream from each remote client into a second mixed audio. The second mixed audio is compressed by the VoIP encoder, which is then transmitted to the PSTN client.

A system for supporting a multi-participant conference call is also described. The system includes a first mixer, a first transport output, a second mixer, and a second transport output. The first mixer is configured to mix a Public Switched Telephone Network (PSTN) client audio data stream with a moderator audio-video data stream into a first mixed data stream. The first transport output configured to transmit the first mixed data stream to at least one remote client that receives the first mixed data stream. Each remote client is connected to the Internet and configured to generate a remote client audio-video data stream. The second mixer mixes the moderator audio-video data stream with the remote client audio-video data stream into a second mixed data stream. The second transport output configured to transmit a mixed audio data stream, corresponding to the second mixed data stream, to the PSTN client.

A method for supporting a multi-participant conference call is also described. The method includes receiving a PSTN audio data stream from a public switched telephone network (PSTN) client. Also, the method includes receiving a moderator audio-video data stream from a moderator. Additionally, the method includes receiving a remote client audio-video data stream from at least one remote client connected to the Internet. The method then mixes the PSTN audio data

stream with the moderator audio-video data stream into a first mixed data stream, and transmits the first mixed data stream to the remote client. The method also mixes the moderator audio-video data stream with the remote client audio-video data stream into a second mixed data stream. The method then proceeds to transmit a mixed audio data stream, corresponding to the second mixed data stream, to the PSTN client.

BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the present invention can be obtained when the following detailed description of the preferred embodiment is considered in conjunction with the following drawings, in which:

FIG. 1 illustrates a typical H.323 audio and video conferencing system implemented in accordance with prior art;

FIG. 2 illustrates an H.323 protocol stack and its components implemented in accordance with prior art;

FIG. 3 illustrates one embodiment of the present invention;

FIG. 4 illustrates an embodiment using multicast Protocol;

FIG. 5 illustrates the audio and video data flow over hybrid networks; and

FIG. 6 illustrates the local client data mixing used in the preferred embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Incorporation by Reference

The following applications and references are hereby incorporated by reference as though fully and completely set forth herein.

U.S. application Ser. No. 10/446,407 titled "Transmission Of Independently Compressed Video Objects Over Internet Protocol", Dye et al. filed May 28, 2003

U.S. application Ser. No. 10/620,684 titled "Assigning Prioritization During Encode Of Independently Compressed Objects, Dye, et al. filed on Jul. 16, 2003.

International Telecommunications Union Recommendation H.323, Titled "Packet Based Multimedia Communication System." November, 2000

International Telecommunications Union Recommendation H.261, Titled "Video Coding for Audio Visual Services at Px64 kbps."

International Telecommunications Union Recommendation H.263, Titled "Video Coding for Low Bit-Rate Communications" February, 1998

One embodiment of the present invention uses a decentralized model for multipoint conferencing. The multipoint control unit insures communication capability once the media stream is transcoded to the H.323 standard as known. However, this embodiment mixes media streams at each terminal prior to multicast.

FIG. 3 illustrates one embodiment of the invention. This embodiment allows audio video and data collaboration information to be securely transferred between a plurality of local and remote clients preferably within a virtual private network.

This embodiment provides the ability for a moderator (single member of the conference) to dial out from a desktop computer or terminal (using a novel hybrid network structure) connecting an external telephone user's audio into the audio/video conference. The embodiment integrates full duplex audio, video, and data connections between clients conferencing on the Internet and clients conferencing on standard telephone systems. The Internet/PSTN hybrid network is the

5

medium used for transport. FIG. 3 depicts the necessary equipment and protocols to complete the dial out to PSTN network method and process.

Now referring to FIG. 3, the voice over IP moderator **401** (call initiator or caller) typically has a number of peripherals used for real input output devices at the desktop. These include a client computing devices such as a PC or other computer **459**, a client terminal **455** including a keyboard and mouse for input output control, a standard desktop telephone **457**, a video input device or camera **451** and the audio input device, microphone **452**. In one embodiment each conference call connected to the Internet will have similar peripheral hardware devices. FIG. 3 illustrates a multi-party virtual conference connected over the Internet. Internet clients include audio video client **415**, audio video client **418**, and audio video client number and **417**. In addition, FIG. 3 shows two possible telephony clients using standard wired **413** or wireless telephone **412** systems. PSTN client #1 **412** is connected to a wireless cell phone that in turn is connected to the global dial network **450**, as specified by the PSTN **433**. Remote telephony user client #2 **413** is connected to a standard telephone handset **413** which is connected to the global dial network **450** based on the PSTN **433**.

Again referring to FIG. 3 the Internet-based clients **401**, **415**, **418**, and **417** are connected through routers or modems **453** preferably in a virtual private network configuration **461**. A virtual private network bridge **461** is used to connect local and remote clients together within a secure private network. A local connection from the VPN bridge **407** to the voice over IP server **409** is used to transfer conference audio from any participant on the IP network to any participant in the PSTN. Thus, the voice over IP server **409** is responsible for transcoding audio information from the virtual private network **461** to and from the PSTN gateway **411**, thus bridging the PSTN and VPN together.

FIG. 4 illustrates one embodiment of the present invention. The system of FIG. 4 performs audio transport between multiple client groups who all share the same multicast group address such that audio/video and data may be shared interactively without the need of central servers. Multicast protocol and encapsulated media packets are implemented so that media data may be routed through public or private IP networks without the need for special hardware and software during the majority of the network transport. FIG. 4 shows a system of virtual networks that interconnect as a virtual private network **423**. Each VPN tunnel can be connected in a series or star topology between one or more multicasting appliances **447-457**. One or more central servers or VPN bridge(s) **407** are at the center of the network topology. Multicasting enabled appliances **447**, **449**, **451**, **453**, **455**, and **457** are used at the origination or termination points for audio, video, or data (media data) to and from the backbone of the transport path. PSTN gateways are used to provide "points of presence" throughout and are responsible for origination or termination of audio data on and off of the PSTN from the IP network topology. Multicast enabled routing allows remote clients to be PC's or PSTN gateways which become "Listeners" of media data. Thus, media data is presented or broadcast onto a network with one or more group addresses. This method uses less bandwidth and reduces latency during transport.

Again referring to FIG. 4, PSTN group #1 **412** has three analog telephones which are switched into a PSTN gateway and VoIP server **471** which is networked over public or private network connection to a multicast enabled VPN appliance **447**. Appliance **447** is connected to a VPN bridge server **407** also by means of a virtual private network. The VPN Bridge

6

407 is used to authenticate clients, assign multicast IP group addresses to various PC clients and VoIP gateway servers. In addition the VPN Bridge Server **407** may have additional meeting room or conferencing features necessary to carry out a multi-party conference. Connected to the VPN Bridge **407** are various virtual private networks which form network tunnels to one or more other multicasting appliances **449**, **451**, **453**, **455**, **457** which connect to one or more PSTN gateways typically located in geographically dispersed areas.

For the purpose of the illustration of FIG. 4, PSTN group #1 **412** is audio conferencing with PSTN client #3 **414** and PSTN client #5 **416**, each of which are audio conferencing with Audio/Video client group #4 **415**. In the illustration of FIG. 4, each member of audio/video client group #4 share audio with all the clients and video with each other. One example may be illustrated again referring to FIG. 4. If telephone client #5 **416** is talking, the analog audio is converted from switched network (PSTN) to IP in the VoIP/PSTN gateway **475**. The digital IP is routed via Internet to an appliance **455** at the edge of the network typically co-located with the VoIP/PSTN gateway **475**. The appliance has been configured to have a virtual private network creating a tunnel through Internet to appliance **453** which also has Internet-based virtual private tunnels to appliance **457** and appliance **447**. Audio from PSTN client #5 **416** is broadcast from appliance **457** whereby all the audio/video client PC's of group #4 are "listeners" and receive the audio from PSTN client **416** at the same time. Additionally, PSTN client #5's **416** audio is routed over another virtual private network to one or more appliances in this case appliances **447** and **449**. PSTN Client group #1 **412** are also "listeners" of the multicast group as well as PSTN Client #3 **414**. Thus, audio is broadcast to multiple audio devices in both IP networks and the PSTN using a unique group address and a virtual private network structure. Interactivity is gained by using the same process no matter who in the group is the broadcaster of audio or video.

FIG. 5 shows a more detailed block diagram of the embodiment of the present invention. The moderator client #1 **401** initiates the call using the application code running on the voice over IP server **409**. Call initiation and call transfer may be accomplished through a VPN tunnel **421** connected to the moderator client **401**. Two connections to the Moderator client #1 **401** through the VPN tunnel **421** are established. The first connection connects the VoIP conference data for call initiation, set-up and control **405**. The second connection **403** through the VPN tunnel connects the conference audio and video **403** between the moderator client **401** and multiple remote clients **415**, **417**, **413** connected to the Internet. The VPN tunnel **421** is connected into the VPN bridge **407** which may be located within the Internet **435** at either local or remote sites. As indicated in FIG. 5, the VPN bridge **407** is responsible for connecting and establishing the virtual private network used for secure conferencing. In the embodiment of the present invention the VPN bridge **407** bridges all the tunnels for data transfer. Thus, VPN tunnel **421**, VPN tunnel **423** and VPN tunnel **425** are on the same virtual private network. Alternate embodiments may include a plethora of tunnels connected to through a single VPN bridge or multiple VPN bridges based on scalability of the system. An additional tunnel containing the conference voice over IP audio and call set-up data **405** is connected to a separate voice over IP server **409**. The server **409** is responsible for transcoding the voice over IP audio and call set-up control **405** in preparation for data transfer across the H.323 network **437**. The H.323 network **437** traverses across the Internet to one of many PSTN gateways **411**. PSTN gateways **411** form the bridge between the Internet and the public switched telephone network **433**.

These VoIP gateways are typically located at the local exchange carrier (LEC) in a plethora of individual points of presence throughout the world. Audio telephony calls are terminated at the voice over IP client **413**. These termination points may be located throughout the world. Thus, the embodiment shown in FIG. **5** allows for the dial-out to standard phones from a client terminal with audio and video capability over IP networks allowing conferencing between multiple remote sites including secure voice over IP audio components over the PSTN.

FIG. **6** of the preferred embodiment shows the multiple network domains, the software applications and operating system boundaries and the operations necessary for audio manipulation and transport. It is noted that video accompanies the audio to all conference participants with the exception of the PSTN client **412**. For simplicity of illustration, FIG. **6** does not show the video conferencing path. The embodiment of FIG. **6** includes a local moderator client **401** who is responsible for initiating a dial out for audio conferencing to the PSTN client **412**. The local moderator client **401** may also be the initiator of the meeting. In this exemplary embodiment, it may be assumed that the local moderator client **401** has set up the audio video conference with remote audio video clients **418** previous to the dial out for audio conferencing to the PSTN client **412**. The local moderator **401** and the remote audio video clients **418** may share audio and video data in a full duplex mode among to all participants with the exception of the PSTN client **412**. The PSTN client **412** may share audio from a standard telephone or wireless telephone with all participants in the conference including the local client **401** and remote audio video clients **418**. Likewise, the remote audio video clients **418** and the local moderator client **401** may share audio with the remote PSTN client **412**. Thus, as indicated in FIG. **6**, a voice over IP call placed the standard telephone system may bring a remote telephone user into an audio/video conference with multiple remote participants.

A detailed description of FIG. **6** follows. It may be assumed in this embodiment that the functions and features of FIG. **6** are running on general-purpose hardware using various software to accomplish the tasks at hand. In alternate embodiments various pieces of FIG. **6** may be encompassed in specialized hardware for improved speed performance. Again referring to FIG. **6** and starting with the local moderator client **401**, the process of call set-up is first performed. The local moderator client **401** uses a computer terminal connected to a local area network that in turn is connected to a wide area network and preferably then connected to a virtual private network **461**. The local moderator client **401** is equipped with proprietary software, as depicted in FIG. **6**, to operate as a dial-out to PSTN application. The application interface allows a point-and-click interface establishing the dial out phone numbers to various possible clients on the PSTN **433**. In alternate embodiments "Dial-In" may be used in addition using the same techniques outlined but in a reverse path scenario.

Once the local moderator client **401** has selected the remote PSTN client **412** phone number, a point and click on the name initiates the dial-out process where audio information is to be transport across hybrid networks. General tones, as known in the art according to the ITT standard, are sent from the local moderators computer or terminal to the voice over IP server **409** located somewhere within a global Internet system **435**. The voice over IP server **409** may be connected to a virtual private network **461**. The voice over IP server **409** may use standard H.323 or SIP network protocol to establish communications as known directly to the PSTN gateway **433**.

Once the call set-up is complete both the PSTN client **412** and the local moderator client **401** have established a connection. In one embodiment the connection is not established for all the audio participants within the conference at this time. In the embodiment of FIG. **6** it is assumed that all the remote audio video clients **418** had previously been in a conference with the local moderator client **401**. In alternate embodiments the order at which callers are established may be different. With the foregoing assumption of a conference being established prior to the call-out to PSTN, further definition of the VoIP audio path is specified. The following discloses and further defines the audio paths through three layers of application software **562**, **564**, **566**, including the audio paths through four hybrid network boundaries **510**, **520**, **435**, and **515**.

Starting with the remote client/moderator boundary **510** preceding to the local client voice over IP boundary **520**, the Internet interface boundaries **435** and the PSTN telephone network boundary **515**, each of these distinct boundaries makes up the method used to transport audio media in a hybrid mixed network system. Remote client/moderator boundary **510** may be established as a virtual private network for transport of audio and video data between the local moderator client **401** and remote audio/video clients **418**. In alternate embodiments the virtual private network may be replaced with either switched dedicated network or standard non-secure IP networks. The local clients VoIP boundary **520** may also be a virtual private network connecting audio from the local moderator client **401** to a local or remote voice over IP server **409**. In alternate embodiments the local client voice over IP boundary may be established through switched networks or the open Internet. For security purposes all connections that traverse across the open Internet **435** are preferably secured by the use of encryption running within a virtual private network. Alternate embodiments may exclude encryption and virtual private networks including public non-encrypted information, public Internet interfaces or over private switched networks. Continuing with the description of the Internet interface **435**, it is assumed all the information above the PSTN boundary **515** (as indicated in FIG. **6**) is information which travels within local client local area networks, remote client local area networks, or on wide area networks through the Internet. The final boundary for network transport is the PSTN boundary **515**. This is the transport interface between the wide area network (Internet) and gateways that transmit data to and from the PSTN system **433**.

Again referring to FIG. **6** and assuming the PSTN dial out call has been established as known in the art, (preferred to ITD H.323) the following detailed information regarding the audio processing follows. In one embodiment the interface between the conference application boundary **562** and the operating system interface boundary **564** and the voice over to IP application boundary **566** is taken under consideration. Preferably, the operations performed on the audio occur in real time to achieve full duplex operation. In alternate embodiments a plethora of alternative methods, operating systems application software, and input and output devices may be used to achieve the same goal as described previously. In one embodiment the operating system sound interface and API boundaries **564** are used for standard audio mixing. The audio from the local moderator client **401** is preferably mixed to be transported both to the PSTN client **412** and remote audio video clients **418**. The conference application boundary **562** is responsible for the application which controls mixing of audio to the operating system sound interface **564**. In one embodiment, the operating system sound interface also performs the interface and mixing for the voice over IP applica-

tion boundary **566**. These layers make up the application interface for achieving the operation as described herein. Input from the local moderator client **401** is input to two mixers. First, the moderator audio input **550** is connected to the voice over IP record mixer **568**. Secondly, the microphone from the moderator client **401** is also connected to another standard mixture **534**. The voice over IP record mixer **568** mixes the audio from the audio decompressors **525** and the local moderator audio **401** in preparation for transport to the voice over IP encoder **522**. In addition, the local moderator client **401** sends audio to the audio mixer **534** which mixes the audio from the voice over IP decoder **524** for output to the conference applications **562** local audio encoder **520a**. The audio encoder **520a** combines the PSTN client **412** audio with the local moderator clients **401** audio then encodes the result for compression of the data in preparation for transport across the VPN network **461**. The application software audio encoder **520a** delivers both the PSTN client's audio and the local moderator client's audio to remote audio video clients **418**.

The local moderator client **401** receives audio from the PSTN client **412**, and thus the voice over IP player mixer **569** mixes audio previously decoded by the voice over IP decoder **524** with the audio from the remote client's **418** for presentation to the local speaker **454**. All the remote audio video clients **418** hear the audio from the PSTN client **412**. The PSTN client **412** transports audio through the PSTN **433** to Internet-based voice over IP server **409**. The voice over IP server transcodes the audio data into a format suitable for transport onto the VoIP application boundary **566**. FIG. **6** also depicts how audio data from the remote audio video clients **418** is prepared for transport across a VPN network **461**. This audio data is input to the application's local decoders for audio decompression **525** prior to the mixing process. The remote audio video clients **418** audio is mixed with the local moderator client audio **401** in preparation for compression by the VoIP encoder **522**. This audio data is then placed in the virtual private network tunnel for transport to the voice over IP server **409** and onto the gateway for audio presentation to the PSTN, terminating at the PSTN client **412**.

FIG. **6** outlines multiple application software boundaries used to mix audio between local and remote clients in hybrid data networks as indicated by the multiple protocol boundaries **562**, **564**, **566**. Thus, the embodiment allows enhancements to the ability for audio video conferencing with multiple clients and the added value of dialing out to a remote telephone user located somewhere within the global dial-up network **450** (shown in FIG. **3**). Prior art techniques, such as that known in the ITU H.323 recommendations, have the compressor **522** and decompressors **524** located within the VoIP server running the H.323 network system as indicated in FIG. **2** (audio codec **211**). This poses a problem for low bit-rate networks especially when video and audio are already part of the transport data. The present embodiment uses highly compressed audio that is compressed and decompressed at the client computer. Thus, the voice over IP server can be located anywhere within the Internet **435** without concern about the limited bandwidth of the first and last mile. In addition, only a single server is required for multiple conferences. The prior art systems, as shown in FIG. **1**, place at least one or more voice over IP server behind the firewall and corporate router for transcoding information to the H.323 network. This requires additional cost when a separate server is needed in each location to run the H.323 standard. The present embodiment does not require a separate server at each site, but instead requires that the desktop computer or terminal compress the data prior to transport.

We claim:

1. A system for supporting a multi-participant conference call comprising:

- a first mixer that mixes a Public Switched Telephone Network (PSTN) client audio data stream with a moderator audio-video data stream into a first mixed data stream;
- a first transport output that transmits the first mixed data stream to at least one remote client that receives the first mixed data stream, the at least one remote client communicatively coupled to the Internet, which generates a remote client audio-video data stream;
- a second mixer that mixes the moderator audio-video data stream with the remote client audio-video data stream into a second mixed data stream; and
- a second transport output that transmits a mixed audio data stream, corresponding to the second mixed data stream, to the PSTN client.

2. The system of claim **1** further comprising a third mixer that mixes the audio data from the PSTN client with the audio-video data stream from the remote client into a third mixed data stream and communicates the third mixed data stream to the moderator.

3. The system of claim **1** further comprising a VoIP decoder that receives IP packets including the audio data stream generated by the PSTN client, the VoIP decoder decodes the IP packets including the audio data from the PSTN client.

4. The system of claim **1** further comprising at least one audio decompressor that decodes IP packets including the audio-video data stream generated by the remote client.

5. The system of claim **1** wherein the PSTN client audio data stream and the moderator audio-video data stream are transported across a virtual private network tunnel.

6. The system of claim **5** further comprising a VoIP encoder that encodes the second mixed data stream and encodes the second mixed voice data before transmitting the second mixed data stream to the PSTN client.

7. The system of claim **1** wherein the moderator audio-video data stream and the remote client audio-video data stream are transported across a virtual private network tunnel.

8. The system of claim **7** further comprising an encoder that receives the first mixed data stream and encodes the first mixed voice data before transmitting the first mixed data stream to the remote client.

9. A non-transitory computer-readable medium including instructions for a multi-participant conference process to be executed by a local moderator computer, the process comprising:

- receiving audio data from a telephone through a public switched telephone network (PSTN);
- receiving audio data and video data from a first remote computer through an Internet;
- receiving audio data and video data from a second remote computer through the Internet;
- receiving audio data from a local audio input device communicatively connected to the local moderator computer;
- receiving video data from a local video input device communicatively connected to the local moderator computer;
- mixing the audio data received from the telephone with the audio data received from the local audio input device and the video data received from the local video input device into mixed audio-video data;
- transmitting the mixed audio-video data to the first remote computer and the second remote computer;
- mixing the audio data received from the first remote computer and the audio data received from the second

11

remote computer with the audio data received from the local audio input device into mixed audio data; compressing the mixed audio data; transmitting the compressed mixed audio data to the telephone; and transmitting collaboration data to the first remote computer and the second remote computer.

10. The process of claim **9**, further comprising mixing the audio data received from the telephone with the audio data received from the first and second remote computers into a second mixed audio data.

11. The process of claim **9**, wherein the receiving audio data from the telephone includes receiving internet protocol (IP) packets, the process further comprising decoding the IP packets.

12. The process of claim **9**, wherein the receiving audio data and video data from the first remote computer includes receiving internet protocol (IP) packets, the process further including decoding the IP packets.

13. The process of claim **9**, wherein the transmitting the mixed audio-video data includes transmitting the mixed audio-video data through a Virtual Private Network (VPN).

14. The process of claim **9**, wherein the transmitting the mixed audio data includes transmitting the mixed audio data through a Virtual Private Network (VPN).

15. The process of claim **9**, further comprising encoding the mixed audio-video data before the transmitting of the mixed audio-video data to the first and second remote computers.

16. The process of claim **9**, further comprising encoding the compressed mixed audio data before the transmitting of the mixed audio data to the telephone.

17. A computer-implemented multi-participant conference system utilizing a local moderator computer, the system comprising:

a voice over IP decoder configured to decode audio data received by the local moderator computer from a telephone through a public switched telephone network (PSTN);

12

a voice over IP encoder configured to compress audio data transported from the local moderator computer to the telephone through the PSTN;

a first mixer configured to mix decoded audio data received by the local moderator computer from the telephone through the PSTN with audio data received by the local moderator computer from a local audio input device and video data received by the local moderator computer from a local video input device into an audio-video stream for transmission through an Internet to a first remote computer and a second remote computer;

a second mixer configured to mix audio data received by the local moderator computer from the first remote computer and the second remote computer through the Internet with audio data received by the local moderator computer from the local audio input device into an audio stream for transmission to the telephone through the PSTN; and

a data collaboration unit configured to transmit collaboration data from the local moderator through the internet to the first remote computer and the second remote computer.

18. The system of claim **17**, further comprising a third mixer configured to mix the decoded audio data received from the telephone with the audio data received from the first and second remote computers.

19. The system of claim **17**, wherein the audio data received by the local moderator computer from the telephone through the PSTN is transported through a virtual private network (VPN) tunnel.

20. The system of claim **17**, wherein audio data transported from the local moderator computer to the telephone is transported through a virtual private network (VPN) tunnel.

* * * * *