



US008910641B2

(12) **United States Patent**
Hon

(10) **Patent No.:** **US 8,910,641 B2**
(45) **Date of Patent:** **Dec. 16, 2014**

(54) **ELECTRONIC CIGARETTE**

(71) Applicant: **Fontem Holdings 1 B.V.**, Amsterdam (NL)

(72) Inventor: **Lik Hon**, North Point (HK)

(73) Assignee: **Fontem Holdings 1 B.V.**, Amsterdam (NL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/921,582**

(22) Filed: **Jun. 19, 2013**

(65) **Prior Publication Data**

US 2013/0276804 A1 Oct. 24, 2013

Related U.S. Application Data

(60) Continuation of application No. 13/548,659, filed on Jul. 13, 2012, now abandoned, which is a continuation of application No. 13/088,276, filed on Apr. 15, 2011, now Pat. No. 8,511,318, which is a division of application No. 10/547,244, filed as application No. PCT/CN2004/000182 on Mar. 8, 2004, now abandoned.

(30) **Foreign Application Priority Data**

Apr. 20, 2003 (CN) 03 1 11582

(51) **Int. Cl.**

A24F 47/00 (2006.01)

A61K 9/00 (2006.01)

(52) **U.S. Cl.**

CPC **A24F 47/008** (2013.01); **A24F 47/002** (2013.01); **A61K 9/007** (2013.01)

USPC **131/273**; **131/270**; **128/202.21**

(58) **Field of Classification Search**

CPC A24F 47/002; A24F 47/008; A61K 9/007

USPC 131/194, 270, 273; 128/202.21

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,775,947 A 9/1930 Robinson
2,057,353 A 10/1936 Whittemore

(Continued)

FOREIGN PATENT DOCUMENTS

CN 89207339.X 5/1989
CN 2047485 U 11/1989

(Continued)

OTHER PUBLICATIONS

Chen, Zhiyong; English Translation of Claim Charts Accompanying Request to Invalidate CN Utility Model Patent No. 200620090805.0 (citing D1-200420031182.0 and D2-CN 97190727.7), Jun. 6, 2013.

(Continued)

Primary Examiner — Richard Crispino


Assistant Examiner — Dionne Walls Mayes

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP; Kenneth H. Ohriner

(57) **ABSTRACT**

An electronic cigarette comprises nicotine without harmful tar. The cigarette includes a shell, a cell, nicotine solution, control circuit, and an electro-thermal vaporization nozzle installed in the air suction end of the shell. The advantages of the present invention are smoking without tar, reducing the risk of cancer, the user still gets a smoking experience, the cigarette is not lit, and there is no fire danger.

20 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,631,219 A 3/1953 Suchy
 3,200,819 A 8/1965 Gilbert
 3,551,643 A 12/1970 Pricenski et al.
 4,171,000 A 10/1979 Uhle
 4,207,457 A 6/1980 Haglund et al.
 4,228,925 A 10/1980 Mendelovich
 4,641,053 A 2/1987 Takeda
 4,735,217 A 4/1988 Gerth et al.
 4,756,318 A 7/1988 Clearman et al.
 4,771,796 A 9/1988 Myer
 4,819,665 A 4/1989 Roberts et al.
 4,848,374 A 7/1989 Chard et al.
 4,945,929 A 8/1990 Egilmex
 4,945,931 A 8/1990 Gori
 4,947,875 A 8/1990 Brooks et al.
 5,042,470 A 8/1991 Kanesaka
 5,060,671 A 10/1991 Counts et al.
 5,080,114 A 1/1992 Rudolph et al.
 5,095,921 A 3/1992 Losee et al.
 5,144,962 A 9/1992 Counts et al.
 5,159,940 A 11/1992 Hayward et al.
 5,190,060 A 3/1993 Gerding et al.
 5,224,498 A 7/1993 Deevi et al.
 5,249,586 A 10/1993 Morgan et al.
 5,261,424 A 11/1993 Sprinkel, Jr.
 5,285,798 A 2/1994 Banerjee et al.
 5,322,075 A 6/1994 Deevi et al.
 5,388,594 A 2/1995 Counts et al.
 5,438,978 A 8/1995 Hardester, III
 5,497,791 A 3/1996 Bowen et al.
 5,505,214 A 4/1996 Collins et al.
 5,591,368 A 1/1997 Fleischhauer et al.
 5,666,977 A 9/1997 Higgins et al.
 5,666,978 A 9/1997 Counts et al.
 5,730,158 A 3/1998 Collins et al.
 5,743,251 A 4/1998 Howell et al.
 5,746,251 A 5/1998 Bullard
 5,799,663 A 9/1998 Gross et al.
 5,819,756 A 10/1998 Mielordt
 5,878,752 A 3/1999 Adams et al.
 5,894,841 A 4/1999 Voges
 6,040,560 A 3/2000 Fleischhauer et al.
 6,041,789 A 3/2000 Bankert et al.
 6,095,153 A 8/2000 Kessler et al.
 6,164,287 A 12/2000 White
 6,178,969 B1 1/2001 St. Charles
 6,196,218 B1 3/2001 Voges
 6,354,293 B1 3/2002 Madison
 6,357,671 B1 3/2002 Cewers
 6,443,146 B1 9/2002 Voges
 6,532,965 B1 3/2003 Abhulimen et al.
 6,601,776 B1 8/2003 Oljaca et al.
 6,715,494 B1 4/2004 McCoy
 6,772,756 B2 8/2004 Shayan
 6,803,545 B2 10/2004 Blake et al.
 6,810,883 B2 11/2004 Felter et al.
 6,854,461 B2 2/2005 Nichols et al.
 6,854,470 B1 2/2005 Pu
 7,100,618 B2 9/2006 Dominguez
 7,131,599 B2 11/2006 Katase
 7,726,320 B2 6/2010 Robinson et al.
 7,832,410 B2 11/2010 Hon
 7,845,359 B2 12/2010 Montaser
 7,997,280 B2 8/2011 Rosenthal
 2003/0108342 A1 6/2003 Sherwood et al.
 2004/0175521 A1* 9/2004 Nakamura 428/35.2
 2004/0182403 A1 9/2004 Andersson et al.
 2004/0261802 A1 12/2004 Griffin et al.
 2005/0016550 A1 1/2005 Katase
 2005/0236006 A1 10/2005 Cowan
 2006/0196518 A1 9/2006 Hon
 2008/0276947 A1 11/2008 Martzel
 2009/0095311 A1 4/2009 Han
 2009/0126745 A1 5/2009 Hon
 2009/0151717 A1 6/2009 Bowen et al.

2009/0188490 A1 7/2009 Han
 2009/0230117 A1 9/2009 Fernando et al.
 2009/0260642 A1 10/2009 Monsees et al.
 2009/0272379 A1 11/2009 Thorens et al.
 2010/0031968 A1 2/2010 Sheikh et al.
 2010/0126505 A1 5/2010 Rinker
 2010/0181387 A1 7/2010 Zaffaroni et al.
 2010/0200008 A1 8/2010 Taieb
 2010/0242974 A1 9/2010 Pan
 2010/0307518 A1 12/2010 Wang
 2011/0005535 A1 1/2011 Xiu
 2011/0036346 A1 2/2011 Cohen et al.
 2012/0111347 A1 5/2012 Hon

FOREIGN PATENT DOCUMENTS

CN 1135860 11/1996
 CN 97216131 5/1997
 CN 97190727.7 6/1997
 CN 1196660 A 10/1998
 CN 2293957 Y 10/1998
 CN 1252961 A 5/2000
 CN 200420031182.0 4/2004
 CN 200410048792.6 6/2004
 CN 1575673 A 2/2005
 CN 200520089947.0 3/2005
 CN 2719043 Y 8/2005
 CN 2777995 Y 5/2006
 CN 1284493 C 11/2006
 CN 20071121524 9/2007
 CN 200997909 Y 1/2008
 CN 101116542 A 2/2008
 CN 101176805 A 5/2008
 CN 201797997 U 4/2011
 CN 202026802 U 11/2011
 CN 202026804 U 11/2011
 DE 10051792 A1 5/2002
 EP 0057243 A1 8/1982
 EP 0230420 A1 8/1987
 EP 0295122 B1 12/1988
 EP 0342538 A2 11/1989
 EP 0358002 A2 3/1990
 EP 0545186 A2 6/1993
 EP 0703735 A1 4/1996
 EP 0824927 A2 2/1998
 EP 0845220 A1 6/1998
 EP 0893071 A1 1/1999
 EP 0951219 A1 10/1999
 GB 1528391 A 10/1978
 JP 64000498 U 1/1989
 JP 06114105 A 4/1994
 JP 07506999 8/1995
 JP 09075058 A 3/1997
 UA 47514 12/1997
 WO WO-9409842 A1 5/1994
 WO WO-9421317 A1 9/1994
 WO WO-9740876 A2 11/1997
 WO WO-9748293 A1 12/1997
 WO WO-9817130 A1 4/1998
 WO WO-0049901 A2 8/2000
 WO WO-0050111 A1 8/2000
 WO WO-0105459 A1 1/2001
 WO WO-03022364 A1 3/2003
 WO WO-03034847 A1 5/2003
 WO WO-03055486 A1 7/2003
 WO WO-03101454 A1 12/2003
 WO WO-04001407 A1 12/2003
 WO WO-2004023222 3/2004
 WO WO-2004080216 9/2004
 WO WO-2006082571 8/2006
 WO WO-2007078273 7/2007
 WO WO-2008077271 7/2008
 WO WO-2008130813 10/2008
 WO WO-2009118085 10/2009
 WO WO-2009135729 11/2009
 WO WO-2010052323 5/2010
 WO WO-2010145468 12/2010

(56)

References Cited

FOREIGN PATENT DOCUMENTS

| | | |
|----|---------------|---------|
| WO | WO-2010145805 | 12/2010 |
| WO | WO-2011010334 | 1/2011 |
| WO | WO-2011022431 | 2/2011 |

OTHER PUBLICATIONS

CN Creative ; *Intellicig USA, Ruyan v. Smoking Everywhere et al.* CV11-6268 Invalidation Contentions, Apr. 12, 2012.

Cyphert, *GIL DBA NUIS, Ruyan v. Smoking Everywhere et al.* CV11-0367 Invalidation Contentions, Apr. 11, 2012.

European Patent Office, extended European Search Report for EP 07721148, Dec. 6, 2010.

European Patent Office, extended European Search Report for EP 11001479, Jul. 4, 2011.

European Patent Office, Supplementary European Search Report for EP04718242, Jul. 27, 2007.

European Patent Office, Supplementary European Search Report for EP05729107, Jul. 31, 2007.

European Patent Office, Supplementary Partial European Search Report for EP04718242, May 22, 2007.

European Patent Office, Supplementary Partial European Search Report for EP05729107, May 22, 2007.

FIN Branding Group, LLC, Request for Inter Partes Reexamination of U.S. Patent No. 8,156,944, filed Sep. 13, 2012.

FIN Branding Group, LLC, Submission of Prior Art and Miscellaneous Statement Pursuant to 376 C.F.R. §1.948, Feb. 27, 2013.

Introduction to Selecting and Using Electronic Components, ISBN7-111-13752-3.

IP Australia, Examination Report for SG 200505930-8, May 4, 2006.

IP Australia, Patent Examination Report No. 1 for AU2007250367, Jul. 30, 2012.

IP Australia, Patent Examination Report No. 1 for AU2007250368, Aug. 9, 2012.

IP Australia; Exam Report for AU2004234199, Aug. 14, 2009.

IP Australia; Search and Examination Report for SG200604498-6, Apr. 16, 2008.

IP Australia; Singapore Examination Report for Singapore Patent Application No. 0604498-6 SG 200505930-8, May 13, 2008.

Japanese Patent Office; Office Action for JP2006504199, Oct. 30, 2009.

Korean Patent Office; Notice of Preliminary Rejection for KR1020057009767, Jul. 27, 2009.

Macau Patent Office; Official Communication for MOI121, Apr. 17, 2009.

Machine translation Chinese Patent Application 200420031182 which corresponds to the priority document of WO20051099494 (Hon '494) Oct. 27, 2005.

Machine translation of Chinese Patent Application 03111582.9 which corresponds to the priority document of WO2004/095955 (Hon '955) Nov. 11, 2004.

Malaysia Intellectual Property Office; Examiner's Report for Malaysian Application No. PI 20041407, Sep. 28, 2007.

Manual for Electric Engineers, 2nd Edition, Mar. 2000.

Manual for Mechanical Designers, 4th Edition, Jan. 2002.

Materials Manual—Nonmetal, Jul. 1985.

Sottera, Inc., Ruyan v. Smoking Everywhere et al. CV11-0367 Invalidation Contentions, Apr. 12, 2012.

Sottera, Inc., Ruyan v. Smoking Everywhere et al. CV11-0367 Invalidation Contentions, Exhibit 7 (Claim 20 Claim Chart), Apr. 12, 2012.

Sottera, Inc., Ruyan v. Smoking Everywhere et al. CV11-0367 Invalidation Contentions, Exhibit 8 (Claim 24 Claim Chart), Apr. 12, 2012.

State Intellectual Property Office (China), English Translation of the Written Opinion for PCT/CN07/001575, Jul. 20, 2007.

State Intellectual Property Office (China), English Translation of the Written Opinion for PCT/CN07/001576, Aug. 3, 2007.

State Intellectual Property Office (China), International Search Report for International Application No. PCT/CN2004000182, Jun. 10, 2004.

State Intellectual Property Office (China), International Search Report for International Application No. PCT/CN2005/000337, Jul. 14, 2005.

State Intellectual Property Office (China), International Search Report for PCT/CN07/001575, Aug. 16, 2007.

State Intellectual Property Office (China), International Search Report for PCT/CN07/001576, Aug. 16, 2007.

State Intellectual Property Office International Search Report for PCT/CN10/073613, Aug. 26, 2010.

State Intellectual Property Office, International Search Report for PCT/CN10/000125, Apr. 1, 2010.

State Intellectual Property Office, Search Report for Utility Model Patent ZL 200620090805.0, Nov. 18, 2008.

Taiwan Intellectual Property Office; Official Letter for TW093111573, Apr. 24, 2009.

TechPowerUp, "What is a MOSFET, what does it look like, and how does it work?", <http://www.techpowerup.com/articles/overclocking/voltmods/21>, dated May 24, 2004, printed from the Internet of Jun. 4, 2011, 3 pages.

Ukrainian Patent Office; Examination Report for UA200511258, Feb. 4, 2009.

United States Patent and Trademark Office, Office Action in Inter Partes Reexamination of U.S. Patent No. 8,156,944, mailed Nov. 27, 2012.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1

ELECTRONIC CIGARETTE

This Application is a Continuation of U.S. patent application Ser. No. 13/548,659, filed Jul. 13, 2012 and now pending, which is a Continuation of U.S. patent application Ser. No. 13/088,276 filed Apr. 15, 2011 and now pending, which is a Division of U.S. patent application Ser. No. 10/547,244 filed Feb. 27, 2006 and now abandoned, which is the U.S. National Phase Application of International Patent Application No. PCT/CN2004/000182 filed Mar. 8, 2004, which claims priority to Chinese Patent Application No. 03111582.9 filed Apr. 29, 2003. These applications are incorporated herein by reference.

TECHNICAL FIELD

The invention relates to an electronic cigarette which contains only nicotine without tar.

BACKGROUND ART

Despite it is commonly known that “smoking is harmful to your health”, the number of smokers worldwide is up to 1 billion, and the number is increasing every year. According to the statistical data from the World Health Organization, about 4.9 million people die of diseases caused by smoking each year. Although smoking may cause serious respiratory diseases and cancer, it remains extremely difficult for smokers to quit smoking completely.

The active ingredient in a cigarette is nicotine. During smoking, nicotine, along with a lot of tar aerosol droplets produced in the burning cigarette, enters smoker’s alveolus and is rapidly absorbed. After being absorbed into the blood of a smoker, nicotine then produces an effect on the receptors of the smoker’s central nervous system, which makes him/her relax and enjoy an inebriety similar to that produced by an exhilarant.

Nicotine is a kind of alkaloid with low molecular weight. A small dose of nicotine is essentially harmless to human body and its half-life in blood is quite short. The major harmful substance in tobacco is tar, and the tar in tobacco is composed of thousands of ingredients, tens of which are cancerogenic substances. At present, it has been proven that passive smoking can be more harmful on non-smokers.

Some cigarette substitutes that contain only nicotine without tar have been proposed, and many of them, such as “nicotine patch”, “nicotine mouthwash”, “nicotine chewing gum”, “nicotine drink” etc., are made of pure nicotine. Although these cigarette substitutes are free from tar, their major disadvantage is that an effective peak concentration cannot be reached in the blood of a smoker due to slow absorption of nicotine. In addition, these cigarette substitutes cannot satisfy habitual smoking actions of a smoker, for example, inhaling action or sucking action, and thus are not likely to be widely accepted as effective substitutes for quitting smoking.

SUMMARY OF THE INVENTION

An objective of the present invention is to provide an electronic cigarette that overcomes the above-mentioned disadvantages and provides a cigarette that looks like a normal cigarette. The electronic cigarette, which is an integrated assembly resembling a cigarette holder, includes a shell, a cell, nicotine solution, a control circuit, a high temperature vaporization nozzle and accessories. An electro-thermal vaporization nozzle is arranged within an air suction end of the shell. The control circuit provides starting current to the

2

electric heater within the vaporization nozzle. Under the high temperature in the vaporization nozzle, the liquid is rapidly vaporized to form a puff of smoke. The cell which provides power to the electric heater via the control circuit can be a disposable battery or a rechargeable battery.

The advantages of the present invention include smoking without tar, significantly reducing the cancerogenic risk. Furthermore, users still feel as if they are smoking, and the cigarette has no need to be lit and has no fire risk.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a structural diagram of the device in the first example in accordance with the present invention.

FIG. 2 is a block diagram of the circuit structure.

FIG. 3 is a schematic diagram of the structure of the high temperature vaporization nozzle and the electric-thermal element.

FIG. 4 is a schematic diagram of the valve made of memory alloy.

FIG. 5 is a schematic diagram of the peristaltic pump made of memory alloy.

FIG. 6 is a schematic diagram of the peristaltic pump.

FIG. 7 is a structural diagram of the electronic cigarette in a second example.

FIG. 8 is a structural diagram of the electronic cigarette in a third example.

FIG. 9 is a structural diagram of the electronic cigarette in a fourth example.

FIG. 10 is a structural diagram of the metering cavity in the fourth example.

DETAILED DESCRIPTION OF THE INVENTION

The high frequency generator of a control circuit board **8** is composed of a capacitance connecting three point type oscillator, an inductance connecting three point type oscillator, or a transformer-type oscillating circuit, which has the frequency of 35 KHz to 3.3 MHz. The circuit includes an automatic frequency fine-adjusting circuit resonating with a piezoelectric element **20**. A nicotine solution storage container **13** is made of silicon rubber, alternatively, other polymers that can be protected against the penetration of nicotine can be used. A one-way valve for liquid injection **12** is sealed by a ball or cone member under the pressure of a spring. An airflow sensor **18** can be comprised of an array of integrated thermal sensitive resistors in the shape of film. The electrode of a resistance or capacitance sensor **19**, which is sensitive to touches of human body, is composed of an upper metal film and a lower metal film and located at the end of the cigarette holder. The changes of the resistance or capacitance parameters due to human touch are inputted into the control circuit to perform the operation of a body sensitive switch.

The electric controlled pump **11**, driven by a motor or a linear motor, drives a retarder that has a large speed ratio, via a shaft coupling, to revolve at a low speed but with large torque. The pump can be a peristaltic pump, a plunger pump, an eccentric pump or a screw pump. Alternatively, the liquid pump can use piezoelectric pump, a super magnetostrictive pump, a thermal expansion drive pump, a thermal contraction drive pump, a thermal bubble pump. The electric control pump or valve may be thermal contractible.

The valve is formed on a silicon rubber tube by nickel-titanium memory alloy or copper-based memory alloy under the force of electro-thermal contractions.

The electro-thermal vaporization nozzle **17** is made of high-temperature resistant materials with low thermal con-

3

ductivity. The nozzle **17** is a tubule, with the internal diameter of 0.05-2mm and the effective working length of 3-20 mm. An electric heating element is provided within the nozzle, and the shapes of the electric heating element and the cavity of the nozzle are designed to facilitate vaporization and ejection of liquid. The vaporization nozzle **17** may be made of conventional ceramics, or be made of aluminum silicate ceramics, titanium oxide, zirconium dioxide, yttrium oxide ceramics, molten silicon, silicon dioxide, molten aluminum oxide. The vaporization nozzle **17** may be in the shape of straight tube or spiral, and may also be made from polytetrafluoroethylene, carbon fiber, glass fiber or other materials with similar properties.

The electric heating element arranged within the vaporization nozzle **17** may be made of wires of nickel chromium alloy, iron chromium aluminum alloy, stainless steel, gold, platinum, tungsten molybdenum alloy, etc., and may be in the shape of straight line, single spiral, double spiral, cluster or spiral cluster, wherein the straight line and cluster are preferred. The heating function of the electric heating element may be achieved by applying a heating coating on the inner wall of the tube, and the coating may be made from electrothermal ceramic materials, semiconductor materials, corrosion-resistant metal films, such as gold, nickel, chromium, platinum and molybdenum. The method for coating can include a coat sintering process, a chemical deposition sintering process and an ion spraying process. The materials mentioned above can be provided within the inner wall of vaporization nozzle in any of the processes mentioned above.

The nozzle with high resistance, made of metal, can have no electric heating element being attached, and can be directly applied with heating current. Alternatively, the materials mentioned above can be arranged outside of the nozzle in any of the ways mentioned above, and an appropriate response time can also be achieved in the power supply mode of short-term preheating. Nicotine solution used in the atomization process comprises nicotine, propylene glycol, glycerol, organic acids, anti-oxidation agents, essence, water and alcohol, in which the nicotine content is 0.1%-6%, propylene glycol content 80%-90%, organic acids 0.2%-20%, the rest is glycerol, essence, anti-oxidation agents, water and alcohol.

EXAMPLE 1

The Structural Diagram of the Device Shown in FIG.

1

When a smoker puts the cigarette holder on his/her mouth, the resistance sensor **19** activates the control circuit board **8**. The control circuit board **8** then outputs two driving voltages respectively, one used to supply power to the electric heating element of the vaporization nozzle **17** and the other used to activate the micro pump **11** (shown in FIG. **6**). The stored solution is then pumped to the nozzle **17** by the solution storage container **13**. On the electric heating element of the nozzle **17**, the nicotine solution is then vaporized into high temperature vapor which is subsequently ejected from the opening end. In the air, the vapor ejected out is then expanded and condensed into micro aerosol droplets.

The effect of the ultrasonic piezoelectric element **20** mounting on the nozzle is that, firstly, the large liquid droplets in the unstable thermal airflow under high pressure will be in sufficient contact with the electric heating element, and thereby be vaporized. Secondly, the liquid droplets in the nozzle **17** are directly fragmented and atomized. Thirdly, possible bumping when the liquid is above a boiling point will be avoided. The effect of integrated atomization will allow

4

aerosol droplets with diameters of 0.2-3 um to enter into the alveolus easily and be absorbed. The airflow sensor **18** is sensitive to the diluted air which enters through air inlet **16** when a "suction" action take places. The sensed signals are transmitted to the control circuit, and the control circuit then stop to supply power to the micro pump and the electric heater after a certain time delay.

The relay relationship between the time delays of the micro pump and electric heater is as follows: after the electric heater is activated, the micro pump is activated after a time delay of 0.1-0.5 seconds; the electric heater is then turned off after a time delay of 0.2-0.5 seconds when the control circuit of the micro pump is turned off, so as to guarantee a complete vaporization of the liquid after quantitative liquid injection without any leftovers.

The nicotine solution container may be designed to be different sizes as required. The nicotine solution may be refilled once a day, or once a couple of days. The liquid crystal display screen **10** can show operating state parameters, such as cell capacity, smoking times per day, average using cycle and warnings for over smoking. A red LED **3** blinks for each smoking action, and a sawtooth wave signal that lasts for 1.2 seconds is given by the control circuit for blinking signals, which provides a gradual change of luminance to imitate the ignition and combustion process of a conventional cigarette. The charger **1**, charging jack **2**, spring **4**, shell **6**, threads **7**, switch **9**, passage tube **14** and baffle plate **15** are shown in FIG. **1**. The silicon gel tube **601**, pinch roller **602**, worm **603** and motor **604** are shown in FIG. **6**.

The control circuit and the ultrasonic micro pump may be integrated on one single chip by using a Micro Electronic Mechanical System (MEMS).

EXAMPLE 2

The Simplified Electronic Cigarette

FIG. **7** is a structural diagram of the simplified device in which the ultrasonic atomization high frequency generator and the piezoelectric ceramic element **20** are omitted. To achieve a desirable atomization effect, tiny heating wires are used in combination with the nozzle (see FIG. **3**), so that the maximum diameters of one or more vaporization cavities formed between the heating wire and the inner wall of the nozzle range from 0.02 mm to 0.6 mm. The function of the airflow sensor **18** omitted is replaced by the manner that the initial signal of the resistance or capacitance sensor **119** is delayed a certain time via the control circuit and acts as the ending signal. The electronic cigarette is configured as follows: the vaporization nozzle **117**, the thermal drive pump **111** (see FIG. **5**) made of nickel titanium memory alloy wire, and the liquid storage container **113** connected to the thermal drive pump constitute a liquid transmission system. Two outputs of the control circuit board **108** are respectively connected to the electric heater and the pump or valve. A body sensitive resistance sensor **119** is connected to the input of the control circuit. The cell **105** and red LED **103** are provided in the front end within the shell, and resemble a cigarette holder, a pipe or a pen.

The thermal drive pump is an electro-thermal shrinkable peristaltic pump, made of wires of nickel titanium memory alloy or copper based alloy, with gel tube which is pressed at three points respectively during the process of electro-thermal contraction to form a pressure cavity for pumping out liquid. The change of volume of the cavity within the thermal drive pump determines the quantity of the solution to be atomized each time. Upon contacting with user's mouth, the

5

resistance sensor 119 activates the control circuit 108, the control circuit 108 then provides operating current to the thermal drive pump and the electric heater, and the output of the control circuit is turned off after the delay of 2 seconds for reactivation at the next smoking action. Alternatively, a thermal expansion drive pump or a thermal bubble pump is also applicable. The thermal expansion drive pump forms a pressure cavity for pumping out liquid by allowing a micro hydrogen container with an embedded electric heating element to block the liquid inlet and open the liquid outlet at the time of thermal expansion. The charging jack 102, LED 103, cell 105, switch 109, liquid-refilling valve 112 and air hole 116 are shown in FIG. 7.

The electrode lead wire 401, heating wire 402, thread 403, base 404 and nozzle 405 are shown in FIG. 3. The support 501, extension spring 502, pumping-out pressure plate 503, silicon gel tube 504, stop pressure plate 505, supporting spring 506, memory alloy wire 507, electrode A 508, electrode B 509 and electrode 510 are shown in FIG. 5.

EXAMPLE 3

The Electronic Cigarette Made of a Ni-Ti Memory Alloy

FIG. 8 is a structural diagram of the electronic cigarette. The electro-thermal vaporization nozzle 217 of the device is connected to the liquid storage container 213 via a pneumatic valve 220. The super elastic member 210 is connected to the pressure plate 211 which is connected to the liquid storage container 213. The pneumatic valve is composed of a pneumatic film 214, a magnetic steel ring 218, a steel valve needle 220 and a reset spring 221. The super elastic member 210, which is made of Ni-Ti memory alloy, is used to apply a constant pressure on the liquid storage container via the pressure plate 211. When the pneumatic valve opens, the liquid with nicotine enters the vaporization nozzle from the liquid storage container via the pneumatic valve and is vaporized and condensed subsequently to form a puff of smoke at high temperature. Upon contacting with user's mouth, the resistance sensor activates the control circuit to supply power to the electric heater. When the user performs suction action, the Nd-Fe-B permanent magnetic alloy ring attracts the valve needle to move in response to the pneumatic film being subjected to negative pressure. Liquid is supplied when the valve needle opens, and after the pneumatic valve is reset, power supply to the electric heater is turned off after the delay of 0.5 seconds by the control circuit. The LED 203, charging jack 202, cell 205, control circuit 208, switch 209, refilling valve 212, baffle plate 215, air hole 216 and resistance sensor 219 are shown in FIG. 8

EXAMPLE 4

The Electronic Spray Cigarette Utilizing the Pressure of a Container

In the device (see FIG. 9), the electro-thermal vaporization nozzle 317, the electronic valve 311 connected with the metering cavity 320, and the liquid storage container 313 form a liquid transmission passage. A gas vessel filled with high-pressure nitrogen is arranged around the periphery of the liquid storage container to exert pressure thereon to facilitate the transmission of the liquid. When a control signal is applied to the electronic valve, the electronic valve is activated, and the solution with nicotine enters the metering cavity from the liquid storage container under pressure. The

6

solution pushes a piston so as to allow a constant volume of liquid at the other side of the piston to enter the vaporization nozzle via the electronic valve. The metering cavity provided at the valve is a cylinder having a liquid inlet and a liquid outlet. Located within the cylinder are the piston micro holes and the reset spring connected onto the piston. The control circuit which is activated by the resistance sensor 319 controls the states of the electronic valve and the electric heater respectively. Due to slow infiltration of the micro hole of the piston in the metering cavity and the force of the reset spring, the piston returns to its original position within 5-8 seconds after each atomization process. The cell 305, pressure vessel 321, pressure chamber 322, seal threaded-opening 323, control circuit board 308 and air hole 316 are showed in FIG. 9.

The silicon gel tube 406, pressure-stopping plate 407, memory alloy wires 408, support 409, electrode lead wire 410 and pressure spring 411 are shown in FIG. 4. The inlet 701, piston 702, micro hole of the piston 703, metering cavity 704, reset spring 705 and outlet 706 are shown in FIG. 10.

The recipes of nicotine solution used are:

1. 6% nicotine, 85% propylene glycol, 2% glycerol, 2% essence, 1% organic acid and 1% anti-oxidation agent;
2. 4% nicotine, 80% propylene glycol, 5% glycerol, 1% butyl valerate, 1% isopentyl hexonate, 0.6% lauryl laurate, 0.4% benzyl benzoate, 0.5% methyl octynicate, 0.2% ethyl heptylate, 0.3% hexyl hexanoate, 2% geranyl butyrate, 0.5% menthol, 0.5% citric acid and 4% tobacco essence;
3. 2% nicotine, 90% propylene glycol, 2.5% citric acid, 1% essence and 4.5% tobacco essence;
4. 0.1% nicotine, 80% propylene glycol, 5% glycerol, 8% alcohol, 2.9% water, 1% essence, 1% tobacco essence and 2% organic acid.

The invention claimed is:

1. An electronic cigarette, comprising: a housing having an inlet and an outlet; a battery and an atomizer in the housing, with the atomizer including a tube having a metal wire heater coil within the tube electrically linked to the battery; a liquid source in the housing and outside of the tube; with liquid in the liquid source capable of moving from the liquid source into the tube and contacting the wire heater coil to create vapor.
2. The electronic cigarette of claim 1 with the tube comprising a fiber material.
3. The electronic cigarette of claim 1 wherein the wire heating coil is in contact with the tube.
4. The electronic cigarette of claim 1 further comprising a base attached to the tube.
5. The electronic cigarette of claim 4 further comprising screw threads on the base.
6. The electronic cigarette of claim 1 with the tube having an inner diameter of .05 to 2 mm.
7. The electronic cigarette of claim 6 with the tube having a length of 3-20 mm.
8. The electronic cigarette of claim 1 with an unobstructed flow path between the tube and the outlet.
9. The electronic cigarette of claim 1 with the housing having a first section attached to a second section.
10. The electronic cigarette of claim 9 with the inlet in the first section and the outlet in the second section.
11. The electronic cigarette of claim 9 with the battery in the first section and the atomizer and the liquid source in the second section.
12. An electronic cigarette, comprising: a housing having an inlet and an outlet;

7

a battery and an atomizer in the housing including a vaporization tube, a wire heater coil within the vaporization tube electrically connectable to the battery, and with the vaporization tube having a first end connected to receive liquid from a liquid source outside of the vaporization tube, and a second open end to allow vapor, formed within the vaporization tube from liquid from the liquid source, to flow out of the vaporization tube of the atomizer, and out of the outlet of the housing; and

with a longitudinal axis of the wire heater coil substantially parallel to a longitudinal axis of the vaporization tube.

13. The electronic cigarette of claim **12** with liquid from the liquid source moving into direct contact with the wire heater coil in the vaporization tube.

14. The electronic cigarette of claim **12** wherein a central section of the heating coil is in contact with the vaporization tube.

15. The electronic cigarette of claim **12** with an unobstructed flow path between the second open end of the vaporization tube and the outlet of the housing.

16. The electronic cigarette of claim **12** with the vaporization tube comprising a fiber material and the wire heater coil comprising metal.

8

17. An electronic cigarette comprising:

a housing, an air inlet leading into the housing, and an air outlet leading out of the housing;

a battery, a control circuit, a sensor, and a vaporization nozzle in the housing, with the control circuit electrically connected to the battery and to the sensor;

the vaporization nozzle including a coil heating element within a tube and with the coil heating element electrically connected to the control circuit; and

a solution storage in the housing outside of the tube, wherein solution in the solution storage is capable of moving from the solution storage into the tube.

18. The electronic cigarette of claim **17** wherein a central section of the heating coil is in contact with the vaporization nozzle.

19. The electronic cigarette of claim **17** with an unobstructed flow path between the vaporization nozzle and the air outlet.

20. The electronic cigarette of claim **17** with the vaporization nozzle comprising a fiber material and the wire heater coil comprising metal.

* * * * *