

US009068706B2

(12) **United States Patent**
Fournier et al.

(10) **Patent No.:** **US 9,068,706 B2**
(45) **Date of Patent:** **Jun. 30, 2015**

(54) **ELECTRONIC LUMINARY DEVICE WITH SIMULATED FLAME**

1,736,820 A 11/1929 Black
1,824,388 A 9/1931 Birch
1,893,730 A 1/1933 Charles
2,131,410 A 9/1938 Newton

(71) Applicant: **WINVIC SALES INC.**, Markham (CA)

(Continued)

(72) Inventors: **Bernard Fournier**, Delson (CA);
Michael Toutant, Chateaugay (CA);
Jonathan Landry, Montreal (CA)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Winvic Sales Inc.**, Markham, Ontario (CA)

CN 2499694 Y 7/2002
CN 2562059 Y 7/2003

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 308 days.

OTHER PUBLICATIONS

(21) Appl. No.: **13/789,624**

PCT, Notification Concerning Transmittal of International Preliminary Report on Patentability, in International application No. PCT/US2012/061435, dated Sep. 18, 2014 (6 pages).

(22) Filed: **Mar. 7, 2013**

(Continued)

(65) **Prior Publication Data**

US 2014/0254148 A1 Sep. 11, 2014

Primary Examiner — Ali Alavi

(51) **Int. Cl.**
F21V 33/00 (2006.01)
F21S 9/02 (2006.01)
F21S 10/04 (2006.01)
F21S 6/00 (2006.01)
F21W 121/00 (2006.01)

(74) *Attorney, Agent, or Firm* — McAndrews, Held & Malloy, Ltd.

(52) **U.S. Cl.**
CPC **F21S 9/02** (2013.01); **F21S 10/043** (2013.01); **F21S 6/001** (2013.01); **F21W 2121/00** (2013.01)

(57) **ABSTRACT**

(58) **Field of Classification Search**
CPC F21S 10/00; F21S 10/04; F21S 10/043
USPC 362/392, 249.02, 812, 810
See application file for complete search history.


A flameless candle may include a side wall including an upper region and a lower region, a base engaged with the lower region of the side wall, and an upper surface extending from the upper region of the side wall to form an upper recess. The candle may also include a projection screen extending upwardly through an aperture in the upper surface. The position of the projection screen is fixed with respect to a position of the upper surface. Two sources of light positioned below the upper surface may project light through the aperture onto the projection screen. Circuitry may electrically connect to the first source of light and the second source of light. The circuitry may independently control each of the sources of light.

(56) **References Cited**

U.S. PATENT DOCUMENTS

212,401 A 2/1879 Requa
643,493 A 2/1900 Fuller
838,075 A 12/1906 Brown

14 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,278,816 A	4/1942	Zabel	6,926,423 B2	8/2005	Bucher	
2,435,811 A	2/1948	Waters	6,929,380 B2	8/2005	Logan	
2,811,711 A	10/1957	Cade	6,944,982 B2	9/2005	Schroeter	
2,935,041 A	5/1960	Rovere	6,953,401 B2	10/2005	Starr	
2,976,450 A	3/1961	Benoliel	6,955,440 B2	10/2005	Niskanen	
3,127,539 A	3/1964	Convertine	6,966,665 B2	11/2005	Limburg	
3,150,709 A	9/1964	Bolmgren	6,976,063 B1	12/2005	Dharmarajan	
3,233,093 A	2/1966	Gerlat	7,011,426 B2	3/2006	Gabor	
3,315,497 A	4/1967	MacDonald	7,029,146 B2	4/2006	Kitchen	
3,384,774 A	5/1968	English	7,030,748 B2	4/2006	Tanguay	
3,435,286 A	3/1969	Kayatt	7,066,637 B2	6/2006	Nozawa	
3,514,660 A	5/1970	Kopelman	7,080,472 B2	7/2006	Schroeter	
3,639,749 A	2/1972	Beckman	7,083,315 B2	8/2006	Hansler	
3,681,588 A	8/1972	Lee	7,093,949 B2	8/2006	Hart	
3,710,182 A	1/1973	Van Reenen	7,093,961 B2	8/2006	Bentley	
3,814,973 A	6/1974	Thouret	7,111,421 B2	9/2006	Corry	
3,978,598 A	9/1976	Rose	7,125,142 B2	10/2006	Wainwright	
4,026,544 A	5/1977	Plambeck	7,134,229 B2	11/2006	Hess	
4,107,763 A	8/1978	Thiel	7,159,994 B2	1/2007	Schnuckle	
4,253,045 A	2/1981	Weber	7,162,820 B2	1/2007	Hess	
4,328,534 A	5/1982	Abe	7,194,830 B2	3/2007	Hess	
4,381,455 A	4/1983	Komori	7,201,500 B2	4/2007	Mishan	
4,477,249 A	10/1984	Ruzek et al.	7,210,256 B2	5/2007	Rosserot	
4,510,556 A	4/1985	Johnson	7,261,455 B2 †	8/2007	Schnuckle	
4,550,363 A	10/1985	Sandell	7,300,179 B1	11/2007	LaDuke	
4,551,794 A	11/1985	Sandell	7,350,720 B2	4/2008	Jaworski	
4,593,232 A	6/1986	McEdwards	7,360,935 B2	4/2008	Jensen	
4,617,614 A	10/1986	Lederer	7,373,743 B1	5/2008	Hess	
4,777,571 A	10/1988	Morgan	7,377,667 B2	5/2008	Richmond	
4,839,780 A	6/1989	Chuan	7,422,355 B2	9/2008	Hirata	
4,866,580 A	9/1989	Blackerby	7,481,571 B2	1/2009	Bistrizky	
4,965,707 A	10/1990	Butterfield	7,503,668 B2	3/2009	Porchia	
5,090,892 A	2/1992	Chuang	7,670,035 B2	3/2010	Tsai	
5,097,180 A	3/1992	Ignon	7,686,471 B2	3/2010	Reichow	
5,381,325 A	1/1995	Messana	7,726,860 B2	6/2010	Harrity	
5,503,550 A	4/1996	DePalma	7,762,897 B2	7/2010	Starr	
5,575,274 A	11/1996	DePalma	7,832,906 B2	11/2010	Damman	
5,600,209 A	2/1997	St. Louis	7,837,355 B2 *	11/2010	Schnuckle	362/249.02
5,642,580 A	7/1997	Hess	7,997,772 B2	8/2011	Avtzon	
5,707,282 A	1/1998	Clements	8,021,021 B2	9/2011	Paolini	
5,848,886 A	12/1998	Michaud	8,070,319 B2	12/2011	Schnuckle	
5,858,036 A	1/1999	Chandaria	8,132,936 B2	3/2012	Patton	
5,924,784 A	7/1999	Chliwnyj	8,234,803 B2	8/2012	Gallo	
5,924,784 A	7/1999	Chliwnyj	8,550,660 B2 *	10/2013	Patton et al.	362/249.02
6,017,139 A	1/2000	Lederer	2001/0033488 A1	10/2001	Chliwnyj	
6,047,489 A	4/2000	Hess	2002/0011570 A1	1/2002	Castleman	
6,050,011 A	4/2000	Hess	2002/0023376 A1	2/2002	Hess	
6,053,795 A	4/2000	Whitney	2002/0080601 A1	6/2002	Meltzer	
6,064,064 A	5/2000	Castleman	2002/0093834 A1	7/2002	Yu	
6,066,924 A	5/2000	Lederer	2002/0139021 A1	10/2002	Hess	
RE37,168 E	5/2001	St. Louis	2002/0175215 A1	11/2002	Webster	
6,241,362 B1	6/2001	Morrison	2003/0035291 A1	2/2003	Jensen	
6,257,755 B1	7/2001	Sevelle	2003/0041491 A1	3/2003	Mix	
6,269,567 B1	8/2001	MacPherson	2003/0046837 A1	3/2003	Hess	
6,302,555 B1	10/2001	Bristow	2003/0053305 A1	3/2003	Lin	
6,312,137 B1	11/2001	Hsieh	2003/0081420 A1	5/2003	Jensen	
6,363,636 B1	4/2002	Hess	2003/0110671 A1	6/2003	Hess	
6,385,881 B1	5/2002	Hess	2003/0161145 A1	8/2003	Liu	
6,454,425 B1	9/2002	Lin	2003/0198045 A1	10/2003	Kitchen	
6,461,011 B1	10/2002	Harrison	2004/0037069 A1	2/2004	Blackbourn	
6,511,219 B2	1/2003	Sevelle	2004/0060213 A1	4/2004	Schroeter	
6,515,283 B1	2/2003	Castleman	2004/0095253 A1	5/2004	Tanguay	
6,518,574 B1	2/2003	Castleman	2004/0114351 A1	6/2004	Stokes	
6,564,485 B1	5/2003	Hess	2004/0165374 A1	8/2004	Robinson	
6,575,613 B2	6/2003	Brown	2004/0165383 A1	8/2004	Hess	
6,615,519 B2	9/2003	Hess	2004/0181983 A1	9/2004	Hess	
6,616,308 B2	9/2003	Jensen et al.	2004/0240225 A1	12/2004	Batiste	
D486,924 S	2/2004	Skradski	2004/0246711 A1	12/2004	Brenchley	
6,688,752 B2	2/2004	Moore	2004/0252498 A1	12/2004	Gutstein	
6,712,493 B2	3/2004	Tell	2004/0264169 A1	12/2004	Limburg	
6,719,443 B2	4/2004	Gutstein	2005/0072031 A1	4/2005	Hess	
6,757,487 B2	6/2004	Martin	2005/0083682 A1	4/2005	Logan	
6,799,727 B2	10/2004	Webster	2005/0086841 A1	4/2005	Schroeter	
6,871,221 B1	3/2005	Styles	2005/0097792 A1	5/2005	Naden	
6,914,534 B2	7/2005	Tanguay	2005/0097793 A1	5/2005	Hess	
6,916,110 B2	7/2005	Batiste	2005/0151663 A1	7/2005	Tanguay	
			2005/0169666 A1	8/2005	Porchia	
			2005/0196716 A1	9/2005	Haab	
			2005/0248952 A1	11/2005	Yao	

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0254232 A1 11/2005 Bentley
 2005/0254242 A1 11/2005 Baker
 2005/0285538 A1 12/2005 Jaworski
 2006/0026894 A1 2/2006 Hess
 2006/0034079 A1 2/2006 Schnuckle
 2006/0034100 A1 2/2006 Schnuckle
 2006/0098428 A1 5/2006 Rosserot
 2006/0101681 A1 5/2006 Hess
 2006/0109666 A1 5/2006 Tsai
 2006/0146544 A1 7/2006 Leung
 2006/0188831 A1 8/2006 Hess
 2006/0232958 A1 10/2006 Chang
 2007/0002560 A1 1/2007 Gutstein
 2007/0014107 A1 1/2007 Mishan
 2007/0094903 A1 5/2007 Hess
 2007/0107280 A1 5/2007 Stinson
 2007/0125367 A1 6/2007 Lim
 2007/0127249 A1 6/2007 Medley
 2007/0159422 A1 7/2007 Blandino
 2007/0177393 A1 8/2007 Hirata
 2007/0177394 A1 8/2007 Vock
 2007/0207424 A1 9/2007 Benson
 2007/0224561 A1 9/2007 Hess
 2007/0236947 A1 10/2007 Jensen
 2007/0242259 A1 10/2007 Kawakami
 2008/0004124 A1 1/2008 O'Neill
 2008/0013931 A1 1/2008 Bourne
 2008/0031784 A1 2/2008 Bistrizky
 2008/0037254 A1 2/2008 O'Neill
 2008/0074875 A1 3/2008 Jensen
 2008/0094825 A1 4/2008 Silver
 2008/0112154 A1 5/2008 Reichow
 2008/0117634 A1 5/2008 Wong
 2008/0129226 A1 6/2008 DeWitt
 2008/0130266 A1 6/2008 DeWitt
 2008/0138050 A1 6/2008 Moreland
 2008/0151534 A1 6/2008 Lin
 2008/0151563 A1 6/2008 Chen
 2008/0151571 A1 6/2008 Chen
 2008/0158863 A1 7/2008 Tsai
 2009/0135586 A1 5/2009 Yang
 2009/0310340 A1 12/2009 Betz
 2010/0001662 A1 1/2010 Nelkin
 2010/0073924 A1 3/2010 Deng
 2011/0127914 A1 6/2011 Patton et al.
 2011/0148329 A1 6/2011 Demarest
 2012/0134157 A1 5/2012 Li
 2012/0155075 A1 6/2012 Asofsky
 2013/0050985 A1 2/2013 Kwok

FOREIGN PATENT DOCUMENTS

CN 1578573 A 2/2005
 CN 1650130 A 8/2005
 CN 2755407 Y 2/2006
 CN 2769684 Y 4/2006
 CN 2781708 Y 5/2006
 CN 2828532 Y 10/2006
 CN 2859207 Y 1/2007
 CN 2906310 Y 5/2007
 CN 200979085 Y 11/2007
 CN 200999983 Y 1/2008
 CN 201000054 Y 1/2008
 CN 201034248 Y 3/2008
 CN 201034303 Y 3/2008
 CN 201053583 Y 4/2008
 CN 201066077 Y 5/2008
 CN 201069056 Y 6/2008
 CN 201137821 Y 10/2008
 CN 101865413 A 10/2010
 DE 1489617 5/1969
 EP 0138786 A1 4/1985
 EP 0600217 A1 8/1994
 EP 1199524 A2 4/2002

EP 1199525 A2 4/2002
 EP 1199526 A2 4/2002
 EP 1199527 A2 4/2002
 EP 1223385 A1 7/2002
 EP 1328761 A2 7/2003
 EP 1137900 B1 3/2004
 EP 1939003 A1 3/2004
 EP 1427968 A1 6/2004
 EP 1439351 A2 7/2004
 EP 1199526 B1 9/2004
 EP 1199527 B1 9/2004
 EP 1488447 A2 12/2004
 EP 1496306 A2 1/2005
 EP 1223385 B1 5/2005
 EP 1313987 B1 11/2005
 EP 1439351 A3 4/2006
 EP 1655543 A1 5/2006
 EP 1659340 A2 5/2006
 EP 1659340 A3 7/2006
 EP 1703210 A1 9/2006
 EP 1703211 A1 9/2006
 EP 1427968 B1 10/2006
 EP 1797371 A1 6/2007
 EP 1800064 A2 6/2007
 EP 1832815 A2 9/2007
 EP 1838110 A1 9/2007
 EP 1869360 A1 12/2007
 EP 1878449 A1 1/2008
 EP 1936277 A2 6/2008
 EP 1938018 A1 7/2008
 EP 2587127 A1 5/2013
 GB 2323159 A 9/1998
 GB 2350885 A 12/2000
 GB 2379731 A 3/2003
 GB 2438519 A 11/2007
 GB 257485 A 8/2009
 JP 06-052709 2/1994
 JP 2000-284730 10/2000
 JP 2008-180755 8/2008
 WO WO82/02756 8/1982
 WO WO87/04506 7/1987
 WO WO95/04243 2/1995
 WO WO96/25624 8/1996
 WO WO97/28671 8/1997
 WO WO97/41393 11/1997
 WO WO98/05014 2/1998
 WO WO01/04544 A1 1/2001
 WO WO01/57447 A1 8/2001
 WO WO02/18841 A3 3/2002
 WO WO02/35153 A3 5/2002
 WO WO02/099338 A1 12/2002
 WO WO03/023286 A1 3/2003
 WO WO03/073466 A2 9/2003
 WO WO2004/063625 A2 7/2004
 WO WO2005/003623 A2 1/2005
 WO WO2005/038338 A1 4/2005
 WO WO2005/045321 A1 5/2005
 WO WO2006/020839 A2 2/2006
 WO WO2006/027273 A1 3/2006
 WO WO2006/040342 A2 4/2006
 WO WO2006/074544 A1 7/2006
 WO WO2006/104898 A1 10/2006
 WO WO2006/105703 A1 10/2006
 WO WO2007/039126 A1 4/2007
 WO WO2007/120540 A1 10/2007
 WO WO2007/141013 A1 12/2007
 WO WO2007/147887 A2 12/2007
 WO WO2008/060800 A2 5/2008
 WO WO2008/062061 A2 5/2008
 WO WO2008/073786 A2 6/2008
 WO WO2008/076326 A2 6/2008
 WO WO2012/000418 A1 1/2012

OTHER PUBLICATIONS

PCT, Notification Concerning Transmittal of International Preliminary Report on Patentability, in International application No. PCT/US2012/029730, dated Sep. 18, 2014 (7 pages).
 U.S. Patent No. 8,132,936—file history. (397 pages).

(56)

References Cited

OTHER PUBLICATIONS

PCT, Notification of Transmittal of The International Search Report and the Written Opinion of the International Searching Authority, in International application No. PCT/US13/29730, dated May 13, 2013. LittleBrightLights.com, Flame Lights, Vaughan Safety, Inc. Company, Tuesday, Oct. 5, 2010; retrieved from the internet on Jan. 26, 2011. (3 pages).

“Mini Hanging Fire Bowl” by Visual Effects; from Amazon.com, retrieved from the internet on Jan. 26, 2011. (3 pages).

“New Blue Faux Flame Safe Halloween Pumpkin LED Candle” by Unknown, from Amazon.com, retrieved from the internet on Jan. 26, 2011. (3 pages).

Battery Operated Flame Light Olympic Torch, Olympic Flame Torch, Caufields, retrieved from the internet on Jan. 26, 2011. (2 pages).

“12v ac party lights,” thefind, retrieved from the internet on Jan. 26, 2011. (4 pages).

“Sensor LED 7 Color Change Flameless Candle light,” Diwali, e-bay, retrieved from the internet on Jan. 26, 2011. (4 pages).

“Home Stove Stage Silk Flame Effect Light Lamp Fire Fake,” Shopzilla.co.uk, retrieved from the internet on Jan. 26, 2011. (6 pages).

“Silk Flame Machine Hire,” IA Sound & Light, retrieved from the internet on Jan. 26, 2011. (6 pages).

“Silk Flame,” Wicked Beernut Home, Halloween Home, retrieved from the internet on Jan. 26, 2011. (7 pages).

“Silk Torches” retrieved from the internet on Jan. 26, 2011. (4 pages).

“Smart Candle,” smart Candle, Asia Ltd., retrieved from the internet on Jan. 26, 2011. (2 pages).

“2010 Updated Speeder’s Faux Flaming Caldron,” Halloween Forum.com, retrieved from the internet on Jan. 26, 2011. (2 pages).

“Faux Flame With Housing,” thefind, retrieved from the internet on Jan. 26, 2011. (2 pages).

“Flame Effect Light,” Twenga, retrieved from the internet on Jan. 26, 2011. (3 pages).

“VEI Faux Flame V-0104 Vulcan’s Fire Hanging silk Flame Effect,” Minions Web, retrieved from the internet on Jan. 26, 2011. (3 pages).

Faux Flame Hanging Light, Kijiji, Ottawa, Canada, <http://ottawa.kijiji.ca/c-buy-and-sell-furniture-lamps-lighting-Faux-Flam> retrieved from the internet on Jan. 26, 2011. (1 page).

“Silk flame ,fake, faux flame engines,” <http://www.amazingpartythemes.com/flame-fx/units/battery.htm>., retrieved from the internet on Jan. 26, 2011. (2 pages).

Shells: User’s Guide, HP 9000 Computers, Hewlett Packard, HP Part No. B2355-90046, Printed in USA, Aug. 1992, Second Edition E0892. (432 pages).

U.S. Patent No. 8,132,936—file history. (397 pages), Publication date: Mar. 13, 2012.

European Patent Office, European Search Report, in Application No. EP12185984, Dec. 4, 2012. (2 pages).

PCT, International Search Report, in Application No. PCTUS2009/054401, dated Oct. 16, 2009. (4 pages).

* cited by examiner

† cited by third party





FIGURE 1

FIGURE 2






FIGURE 3A




FIGURE 3B

1

**ELECTRONIC LUMINARY DEVICE WITH
SIMULATED FLAME****CROSS REFERENCE TO RELATED
APPLICATIONS**

This application claims priority to U.S. Patent Application Ser. No. 61/607,942 filed on Mar. 7, 2012, the entirety of which is herein incorporated by reference.

**FEDERALLY SPONSORED RESEARCH OR
DEVELOPMENT**

[Not Applicable]

JOINT RESEARCH AGREEMENT

[Not Applicable]

SEQUENCE LISTING

[Not Applicable]

BACKGROUND

Generally, this application relates to flameless candles. Specifically, this application discloses techniques for simulating a candle flame without use of moving parts.

Flameless candles may provide an illusion of a real (flamed) candle, but without the risk of fire damage. A real candle flame moves in physical space. In order to simulate such movement, some have used an element or part that moves in physical space. Moving elements or parts, however, may be undesirable for various reasons. For example, moving parts may tend to become damaged, such as during shipping, by mishandling, or by unintentional events, and may be subject to wear and tear on repeated use.

Furthermore, flameless candles with moving parts may require additional components or systems to cause the moving parts to move. Such components or systems may include fans or magnetic systems. These components or systems may add cost to a flameless candle device.

SUMMARY

According to techniques of this application, a device includes a side wall, a base, an upper surface, a riser, an opaque disk, a projection screen, a first source of light, a second source of light, and circuitry. The side wall may have a minimum height, an upper region, and a lower region. The base may engage with the lower region of the side wall. The upper surface may extend from the upper region of the side wall to form an upper recess. The riser may extend upwardly away from the base. The opaque disk may be located at a top of the riser. The opaque disk may include a first tunnel and a second tunnel, wherein each of the tunnels has a top end and a bottom end and is diagonally oriented in both a vertical and a horizontal dimension and further oriented such that the bottom ends of the tunnels are further apart than the top ends of the tunnels.

The projection screen may include a flame shape with a front side having convexity, relative to a source of light which projects upon it. The projection screen may extend upwardly from the opaque disk through an aperture in the upper surface and positioned off of a central axis of the aperture through the upper surface. The projection screen may include a fixed end and a free end. The fixed end of the projection screen may be

2

fixedly attached to the opaque disk, whereby the projection screen is fixed with respect to a position of the upper surface. The free end of the projection screen may be located at a height below the maximum or minimum height of the side-wall.

The first source of light may be positioned below the upper surface and configured to project light through the aperture onto the projection screen. The first source of light may be located at a fixed distance from the projection screen that is at least partially within the second tunnel such that a top end of the second source of light is located at a height below the top end of the second tunnel.

The second source of light positioned below the upper surface and configured to project light through the aperture onto the projection screen. The second source of light may be located at a fixed distance from the projection screen that is at least partially within the first tunnel such that a top end of the first source of light is located at a height below the top end of the first tunnel. The tunnels may have interior surfaces that encourage specular reflection or diffusion depending on the desired optical effect.

The circuitry may be electrically connected to the first source of light and the second source of light. The circuitry may be configured to independently control intensities of the light projected by the first source of light and the second source of light.

The projection screen may include a primary plane. The first source of light may emit light including a beam axis and a beam width. The beam axis of the first source of light may intersect the primary plane of the projection screen at an angle between 20° to 40°. The second source of light may emit light including a beam axis and a beam width. The beam axis of the first source of light may intersect the primary plane of the projection screen at an angle between 20° to 40°.

The beam width of the light emitted by the first source of light may be between 30° to 35°. The beam width of the light may be emitted by the second source of light is between 30° to 35°. The projection screen may include a translucent material that allows light from the first source of light to penetrate to the back side of the projection screen and may allow light from the second source of light to penetrate to the front side of the projection screen. The projection screen may have a static shape. The projection screen may be rigid. The projection screen may include plastic.

The first area may be offset from the second area along a vertical dimension. The first area may be offset from the second area along a horizontal dimension. The first source of light may be positioned to project light onto a front side of the projection screen in a first area, the second source of light may be positioned to project light through the aperture onto the front side of the projection screen in a second area, wherein the second area may be overlapping but different than the first area.

According to techniques of the application, a device may include a side wall, a base, and an upper surface. The side wall may have an upper region and a lower region. The base may be engaged with the lower region of the side wall. The upper surface may extend from the upper region of the side wall to form an upper recess.

The device may include a projection screen extending upwardly through an aperture in the upper surface. The position of the projection screen may be fixed with respect to the position of the upper surface. The projection screen may be flat or may have a concavity or convexity. The projection screen may have a general two-dimensional or three-dimensional appearance. The projection screen may be shaped like a flame. The projection screen may have a primary plane, but,

alternatively may be ovoid. The projection screen may be translucent. The projection screen may be formed from a material such as plastic, glass, or metal.

A first source of light may be positioned below the upper surface and may project light through the aperture onto the projection screen. A second source of light may be positioned below the upper surface and may project light through the aperture onto the projection screen. The positions of the first source of light and the second source of light may also be fixed with respect to the position of the projection screen.

The light from the first and second sources of light may be projected onto the front side of the projection screen or onto the front and back side of the projection screen. Light projected onto one side of the projection screen may penetrate through to the other side of the projection screen. Each of the sources of light may emit light with a beam axis and a beam width. One or more of the beam axes may intersect with the primary plane of the projection screen at an angle between 20° to 40°. One or more of the beam widths may be between 30° to 35°.

The sources of light may be positioned to project light onto different areas of the projection screen. These areas may be distinct or may overlap.

Circuitry may electrically connect to the first source of light and the second source of light. The circuitry may independently control intensities of the light projected by the first source of light and the second source of light.

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 illustrates an electronic candle, according to techniques of the present application.

FIG. 2 illustrates a portion of an electronic candle, according to techniques of the present application.

FIGS. 3A and 3B illustrate a projection screen and sources of light, according to techniques of the present application.

The foregoing summary, as well as the following detailed description of certain techniques of the present application, will be better understood when read in conjunction with the appended drawings. For the purposes of illustration, certain techniques are shown in the drawings. It should be understood, however, that the claims are not limited to the arrangements and instrumentality shown in the attached drawings. Furthermore, the appearance shown in the drawings is one of many ornamental appearances that can be employed to achieve the stated functions of the system.

DETAILED DESCRIPTION

FIGS. 1-3B illustrate an electronic candle 100, according to techniques of the present application. As shown in FIG. 1, the electronic candle 100 may include a side wall 102 having an upper region and a lower region. A base 150 (see FIG. 2) may be engaged with the lower region of the side wall 102. An upper surface 106 may extend from the upper region of the sidewall 102 to form an upper recess 104. The upper recess 104 may have a variety of different shapes. The upper recess 104 may be shaped like a bowl or a portion of a bowl. For example, the upper region of the side wall 102 may have a varying height around the top perimeter of the electronic candle 100. The upper recess 104 may have a rounded or flat bottom surface. The upper recess 104 may have a smooth or textured bottom surface. The upper recess 104 may have a cylindrical shape.

A projection screen 110 may be adjacent to and/or extend upwardly through an aperture 108 in the upper surface 106.

The projection screen 110 may be offset with respect to or positioned off of a central axis of the aperture 108. The position of the projection screen 110 may be fixed with respect to the upper surface 106. Of course, an undue amount of force could cause the projection screen 110 to deflect or otherwise change position with respect to the upper surface 106. However, an anticipated movement of the electronic candle 100 (for example, picking up or putting down the candle, rotating the candle, or turning the candle upside down) may not influence the position of the projection screen with respect to the upper surface 106.

As shown in FIG. 2, the electronic candle 100 may include a base 150. The base 150 may accommodate batteries in a battery compartment 160. The base 150 may also accommodate circuitry 170. The battery compartment 160 and circuitry 170 need not be located in or around the base 150, and could be located at other areas of the electronic candle 100. For example, the circuitry 170 may be embedded in one or more of sources of light 120, 130. The circuitry 170 and sources of light 120, 130 may receive power from one or more batteries in the battery compartment 160.

A riser 140 may extend upwardly away from the base 150. An opaque disk 190 may be located at a top of the riser 140. As shown in FIG. 2, the opaque may include two tunnels. The tunnels may each be diagonally oriented in a vertical dimension and/or a horizontal dimension. The tunnels may traverse the height of the opaque disk 190, creating an open path in the interior of the opaque disk, from the top to the bottom. The opaque disk 190 may substantially attenuate the intensity of light that is emitted through the portion of the sidewall 102 located below the opaque disk 190.

The sources of light 120 and 130 may be located near or at the top of the riser 140 or opaque disk 190. The sources of light 120, 130 may include a light-emitting diode (“LED”) an incandescent bulb, or a laser. In certain configurations, a riser 149 or opaque disk 190 may not be necessary. For example, the sources of light 120, 130 may be embedded in other parts of the candle 100.

Each of the sources of light 120, 130 may be located at least partially within a respective tunnel. A given source of light may be located such that the top end of the source of light is located at a height below a top end of the given tunnel. In such a configuration, a tunnel may be employed to collimate a beam of light emitted by a source of light, thereby reducing the beam width of the beam of light.

The projection screen 110 may include a fixed end and a free end. The free end of the projection screen 110 may extend upwardly from the riser 140 or opaque disk 190. The fixed end of the projection screen 110 may be rigidly affixed to the riser 140 or opaque disk 190 at or near the top of the riser 140 or opaque disk 190. For example, the projection screen 110 may be integral with the riser 140 or opaque disk 190. The projection screen 110 may be a separate portion rigidly or fixedly attached to the riser 140 or opaque disk 190 (for example, glued or attached at more than one place). For example, the fixed end of the projection screen 110 may be part of a tab that is inserted into one slot (or one of a plurality of slots) in the riser 140 or opaque disk 190.

By rigidly or fixedly affixing the projection screen 110 with the riser 140 or opaque disk 190, it may be possible to fix the position of the projection screen 110 with respect to the upper surface 106. There may be other ways to fix the positions of the projection screen 110 and the upper surface 106. For example, the projection screen 110 may be affixed to the upper surface 106 or to the sidewall 102 instead of the riser 140.

5

The free end of the projection screen **110** may be located at a height above the base **150** of the candle. This height may be less than a minimum or maximum height of the sidewall **102**. This may prevent the projection screen **110** from becoming damaged if the candle **100**, for example, is turned upside down.

The projection screen **110** may be rigid. The projection screen **110** may be formed from one or more materials, such as glass, plastic, metal, or foil. Such material(s) may be at least partially reflective. The projection screen **110** may be opaque, semi-opaque, clear, frosted, or translucent. The projection screen **110** may have a mesh or other textured surface. The projection screen **110** may facilitate display of holographic images.

The surface of the projection screen **110** may be flat, concave, or convex. The surface of the projection screen **110** may be various combinations of flat, concave, and/or convex. The projection screen **110** may have a two-dimensional or three-dimensional appearance. The projection screen **110** may have a flame shape. Such a shape may be static, in that it does not change. The projection screen **110** may have one or more projection surfaces. For example, the projection screen **110** may have two projection surfaces—front and back. The projection screen **110** may have additional projection surfaces. For example, the projection screen **110** may have three or more surfaces, each receiving light from one or more sources of light. The projection screen **110** may have surfaces that wrap around to form a shape with substantial depth. For example, the projection screen **110** may have a three-dimensional shape resembling an actual candle flame and may be substantially convex around the perimeter of the three-dimensional projection screen (for example, bulbously shaped). In such an example, sources of light may be located around the projection screen **110** and may project onto the projection screen **110**. In one example, when light is projected upwardly towards a convex projection screen **110**, the illusion of a “hot spot” in a flame may be created.

The projection screen **110** may be of uniform color or may have different colors. For example, the projection screen **110** may be painted or patterned to show a simulated wick. As one way to provide an illusion of a real candle flame, the projection screen **110** may have darker colors near an area where a wick would be expected. The projection screen **110** may have different colors (for example, blue, white, orange, or yellow) to simulate different flame temperatures and intensities as a viewer may expect in a real candle flame. The colors may be chosen in combination with light colors emitted from the sources of light **120**, **130**.

The sources of light **120**, **130** may be electrically connected to circuitry **170** through one or more conductors **180**. The circuitry **170** may include a processor and one or more computer-readable storage devices that store software instructions for execution by the processor. The circuitry **170** may independently control one or more different aspects of the light projected by the sources of light **120**, **130**. For example, the circuitry **170** may be capable of separately controlling the intensity or color for each source of light **120**, **130**. The intensities of each source of light **120**, **130** may be adjusted by varying a pulse-code modulated signal or a pulse-width modulated signal provided to the given source of light **120**, **130**.

The circuitry **170** may illuminate each source of light **120**, **130** with different sequences of intensities. Such sequences may include random sequences, semi-random sequences, or predetermined sequences. A sequence may include a repeating loop (for example, a 5-10 second loop). Such sequences may include frequencies that are out of phase from each other.

6

For example, one predetermined sequence may be applied to the source of light **120**, and the same predetermined sequence may be applied to the source of light **130**, but out of phase. As another example, a first predetermined sequence may be applied to the source of light **120** and second predetermined sequence may be synchronously applied to the source of light **130**. The second predetermined sequence may result from filtering or adjusting the first predetermined sequence. Such filtering may include high-pass and low-pass filtering, and such adjusting may include attenuating the amplitudes of the first predetermined sequence.

Sequences may be dynamically influenced by other factors or inputs. For example, an output signal from a light sensor (not shown) could be received by the circuitry **170**, which may, in turn, adjust the intensity levels in sequences according to the light sensor output signal (for example, boost the intensities under higher light). As another example, an output signal from a sound sensor (not shown) could be received by the circuitry **170**, which may, in turn, adjust the intensity levels in sequences according to the sound sensor output signal (for example, adjust the frequency of the intensity changes in response to the character of received sound).

According to one example, it may be possible to provide a separate controller for each source of light **120**, **130**. Each separate controller may be integrated into an epoxy case that houses a light-emitting diode. The two separate controllers may be synchronized through a synchronization signal provided to each controller or between the controllers. For example, an additional lead may extend from the controller and to outside of the epoxy case. The additional leads from two LED assemblies may be connected together and a synchronization signal may be communicated between via this connection to enable synchronous operation.

As illustrated in FIG. 3A, the projection screen **110** extends upwardly through the aperture **108** in the upper surface **106**. While not shown in this example, the position of the projection screen **110** is fixed with respect to the upper surface **106**. The sources of light **120**, **130** may be positioned below the upper surface **106**. They may be positioned and configured in such a manner to project light onto the projection screen **110**, which may be through the aperture **108**. The positions of the sources of light **120**, **130** may also be fixed with respect to the position of the projection screen **110**.

The projection screen **110** may have a primary plane. Such a plane may be substantially vertical and may generally face the direction of emitted light from the sources of light **120**, **130**. Even if the projection screen **110** is not entirely flat, it should be understood that the projection screen **110** still may have a primary plane.

Referring to FIG. 3B, each source of light **120**, **130** may project light (either completely or partially) through the aperture **108** in the upper surface **106** and onto the projection screen **110**. The light emitted from each source of light **120**, **130** may radiate according to a beam width. For example, the beam widths for the light emitted from the sources of light **120**, **130** may be between 30-35 degrees. In the case of certain types of LEDs, such as amber LEDs, the beam widths may be between 10-20 degrees. The beam axis for the light emitted from each of the sources of light may intersect with the primary plane of the projection screen **110**. Such an intersection may have an angle between 20-40 degrees. The sources of light **120**, **130** may project light onto the same side or different sides of the projection screen **110**. For example, the source of light **120** may project light onto the front side of the projection screen **110**, while the source of light **130** may project light onto the back side of the projection screen **110**.

If the projection screen **110** is translucent, light projected onto one side may penetrate to the other side.

The source of light **120** may project light onto an area **122** on the projection screen **110**. The source of light **130** may project light onto an area **132** on the projection screen **110**. The areas **122**, **132** may be coextensive, overlapping, or separate from each other. The areas **122** may have different or similar shapes. The shapes may be influenced by the beam width of projected light, angle of incidence of the beam axis with the primary plane of the projection screen **110**, the distance of a source of light **120**, **130** from the projection screen **110**, the contour of the light-receiving surface of the projection screen **110**, or by other factors. For example, it may be possible to provide lenses, apertures, or the like to form a beam of light having a particular shape. Such shape(s) may influence the shape of area(s) **122**, **132**.

According to one example, area **122** is offset from area **132**. The approximate center of area **122** may be offset from the approximate center of area **132** by about 1-2 mm along a horizontal axis and by about 3-4 mm along a vertical axis.

At least some of the light emitted from the sources of light **120**, **130** may be reflected off of the projection screen **110** and towards a viewer's eye. For example, the light may be reflected directly off of the projection screen **110** and to the viewer's eye without passing through any intervening materials. The light may also be reflected at or within the upper surface **106**. The light may also pass through the sidewall before reaching the viewer's eye.

As discussed above, the intensities or colors of each of the sources of light **120**, **130** may be independently controlled by circuitry **170**. Through such independent control, it may be possible to simulate a candle flame. For example, it may be possible to simulate the physical movement and varying intensity profiles of a candle flame without employing moving parts.

More than two sources of light may be used. For example, three sources of light may be projected onto one side of the projection screen **110**. Each of these sources of light may be independently controlled, such as by the techniques discussed above. As another example, four sources of light may be used. Two of the sources may project light onto one side of the projection screen **110** and the other two sources may project light onto another side of the projection screen **110**.

It will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the novel techniques disclosed in this application. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the novel techniques without departing from its scope. For example, while an electronic candle has been primarily disclosed, similar techniques could be applied to other luminary devices, such as wall sconces, lanterns, paper candles, or tiki torches. Therefore, it is intended that the novel techniques not be limited to the particular techniques disclosed, but that they will include all techniques falling within the scope of the appended claims.

The invention claimed is:

1. A device comprising:

- a side wall including an upper region and a lower region;
- a base engaged with the lower region of the side wall;
- an upper surface extending from the upper region of the side wall to form an upper recess, wherein the upper surface includes an aperture;
- a projection screen, which does not move in physical space, wherein:
 - the projection screen extends upwardly from the upper surface; and

a position of the projection screen is fixed with respect to a position of the upper surface;

a first source of light positioned below the upper surface, wherein the first source of light projects light through the aperture onto the projection screen;

a second source of light positioned below the upper surface, wherein the second source of light projects light through the aperture onto the projection screen; and

circuitry electrically connected to the first source of light and the second source of light, wherein the circuitry independently controls intensities of the light projected by the first source of light and the second source of light onto the projection screen.

2. The device of claim **1**, wherein positions of the first source of light and the second source of light are fixed with respect to the position of the projection screen.

3. The device of claim **1**, wherein the projection screen is flat.

4. The device of claim **1**, wherein the projection screen includes a concavity.

5. The device of claim **1**, wherein the projection screen comprises a flame shape.

6. The device of claim **1**, wherein the projection screen includes a convexity.

7. The device of claim **1**, wherein:

the projection screen includes a primary plane;

the first source of light emits light including a beam axis and a beam width;

the beam axis of the first source of light intersects the primary plane of the projection screen at an angle between 20° to 40°;

the second source of light emits light including a beam axis and a beam width; and

the beam axis of the second source of light intersects the primary plane of the projection screen at an angle between 20° to 40°.

8. The device of claim **7**, wherein:

the beam width of the light emitted by the first source of light is between 30° to 35°; and

the beam width of the light emitted by the second source of light is between 30° to 35°.

9. The device of claim **1**, wherein:

the first source of light is positioned to project light through the aperture onto a front side of the projection screen; and

the second source of light is positioned to project light through the aperture onto a back side of the projection screen.

10. The device of claim **9**, wherein the projection screen comprises a translucent material that allows light from the first source of light to penetrate to the back side of the projection screen and allows light from the second source of light to penetrate to the front side of the projection screen.

11. The device of claim **1**, wherein the projection screen is rigid.

12. The device of claim **11**, wherein the projection screen comprises plastic.

13. The device of claim **1**, wherein:

the first source of light is positioned to project light onto a front side of the projection screen in a first area;

the second source of light is positioned to project light onto the front side of the projection screen in a second area; and

the second area is different than the first area.

14. The device of claim 13, wherein a portion of the first area overlaps a portion of the second area.

* * * * *