



(19) **United States**

(12) **Patent Application Publication**
Bhargava et al.

(10) **Pub. No.: US 2019/0329151 A1**

(43) **Pub. Date: Oct. 31, 2019**

(54) **NETWORK OF DIVIDING-WALL COLUMNS
IN COMPLEX PROCESSING UNITS**

(52) **U.S. Cl.**
CPC *B01D 3/141* (2013.01); *B01D 3/146*
(2013.01)

(71) Applicant: **GTC Technology US LLC**, Houston,
TX (US)

(57) **ABSTRACT**

(72) Inventors: **Manish Bhargava**, Katy, TX (US);
Roomi Kalita, Houston, TX (US);
Amit Kanda, Katy, TX (US)

A processing unit includes a naphtha hydrotreating unit comprising a first divided wall column. The first divided wall column includes a wall dividing a top portion of the first divided wall column, an outlet associated with the second top section of the first divided wall column for recovery of liquid petroleum gas, and an outlet associated with a bottoms portion of the first divided wall column and coupled to a naphtha splitter system. The processing unit also includes a deisopentanizer column coupled to an output of a naphtha splitter of the naphtha splitter system, an isomerization unit coupled to an outlet of the deisopentanizer column, and a second divided wall column. The second divided wall column includes a wall dividing a top portion of the second divided wall column, an inlet coupled to an outlet of a stabilizer column of the isomerization unit, an outlet for recovery of a first isomerate stream, and an outlet associated with a bottoms portion of the second divided wall column for recovery of a second isomerate stream. The processing unit also includes an isomerization reactor coupled between the deisopentanizer column and the stabilizer column.

(21) Appl. No.: **16/396,663**


(22) Filed: **Apr. 27, 2019**

Related U.S. Application Data

(60) Provisional application No. 62/664,762, filed on Apr. 30, 2018.

Publication Classification

(51) **Int. Cl.**
B01D 3/14 (2006.01)






FIG. 1
PRIOR ART




FIG. 2




FIG. 3A
PRIOR ART




FIG. 3B




FIG. 4A
PRIOR ART




FIG. 4B




FIG. 5




FIG. 6A
PRIOR ART

FIG. 6B

NETWORK OF DIVIDING-WALL COLUMNS IN COMPLEX PROCESSING UNITS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This patent application claims priority from, and incorporates by reference the entire disclosure of, U.S. Provisional Patent Application No. 62/664,762 filed on Apr. 30, 2018.

BACKGROUND

[0002] This section provides background information to facilitate a better understanding of the various aspects of the disclosure. It should be understood that the statements in this section of this document are to be read in this light, and not as admissions of prior art.

[0003] The majority of dividing wall column (DWC) applications in the refining industry consist of standalone columns, whether a retrofit or a grassroots column. Functional DWCs are commonly encountered in naphtha splitters and reformate splitters.

SUMMARY

[0004] An illustrative processing unit includes a naphtha hydrotreating unit comprising a first divided wall column. The first divided wall column includes: a wall dividing a top portion of the first divided wall column into a first top section and a second top section; an outlet associated with the second top section of the first divided wall column for recovery of liquid petroleum gas; an outlet associated with a bottoms portion of the first divided wall column and coupled to a naphtha splitter system. The illustrative processing unit also includes a deisopentanizer column coupled to an output of the naphtha splitter, an isomerization unit coupled to an outlet of the deisopentanizer column and including a second divided wall column. The second divided wall column includes: a wall dividing a top portion of the second divided wall column into a first top section and a second top section; an inlet coupled to an outlet of a stabilizer column of the isomerization unit; an outlet associated with the second top section of the second divided wall column for recovery of a first isomerate stream; and an outlet associated with a bottoms portion of the second divided wall column for recovery of a second isomerate stream. The illustrative process also includes an isomerization reactor coupled between the deisopentanizer column and the stabilizer column.

[0005] An illustrative heat-integrated process for a system including a naphtha hydrotreating unit and an isomerization unit includes providing a feed to a first divided wall column. The first divided wall column includes: a wall dividing a top portion of the first divided wall column into a first top section and a second top section, an outlet associated with the second top section of the first divided wall column for recovery of liquid petroleum gas; an outlet associated with a bottoms portion of the first divided wall column and coupled to a naphtha splitter system. The illustrative process includes removing liquid petroleum gas from the second top section of the first divided wall column and feeding a bottoms product from the first divided wall column to a second divided wall column. The second divided wall column includes: a wall dividing a middle portion of the second divided wall column into a first middle section and a second

middle section; an inlet coupled to the bottoms portion of the first divided wall column; an outlet associated with a top portion of the second divided wall column for recovery of a first naphtha stream; an outlet associated with the second middle section for recovery of a second naphtha stream; and an outlet associated with a bottoms portion of the second divided wall column for recovery of a third naphtha stream. The illustrative process includes feeding the first naphtha stream from the top portion of the second divided wall column to a deisopentanizer column, feeding a bottoms fraction from the deisopentanizer column to an isomerization reactor, and feeding a product from the isomerization reactor to a stabilizer column, feeding isomerate from the stabilizer column to a third divided wall column. The third divided wall column includes: a wall dividing a top portion of the third divided wall column into a first top section and a second top section; an inlet coupled to an outlet of a stabilizer column of the isomerization unit; an outlet associated with the second top section of the third divided wall column for recovery of a first isomerate stream; and an outlet associated with a bottoms portion of the third divided wall column for recovery of a second isomerate stream. The illustrative method includes recovering isomerate from the third divided wall column.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] The disclosure is best understood from the following detailed description when read with the accompanying figures. It is emphasized that, in accordance with standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of various features may be arbitrarily increased or reduced for clarity of discussion.

[0007] FIG. 1 illustrates a conventional naphtha hydrotreating and isomerization process scheme;

[0008] FIG. 2 illustrates a heat-integrated DWC process scheme for NHT and ISOM units according to aspects of the disclosure;

[0009] FIG. 3A illustrates a conventional naphtha splitter and FIG. 3B illustrates a DWC naphtha splitter according to aspects of the disclosure;

[0010] FIG. 4A illustrates a conventional splitter and FIG. 4B illustrates a DWC for LPG recovery according to aspects of the disclosure;

[0011] FIG. 5 illustrates an overhead heat integration between deisopentanizer and a deisohexanizer DWC according to aspects of the disclosure; and

[0012] FIG. 6A illustrates conventional depentanizer and deisohexanizer columns FIG. 6B illustrates a depentanizer/deisohexanizer DWC according to aspects of the disclosure.

DETAILED DESCRIPTION

[0013] It is to be understood that the following disclosure provides many different embodiments, or examples, for implementing different features of various embodiments. Specific examples of components and arrangements are described below to simplify the disclosure. These are, of course, merely examples and are not intended to be limiting. In addition, the disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

[0014] DWC technology can improve the efficiency and profitability of complex refinery units. One such area is complex processes, like naphtha hydrotreating (NHT) and isomerization (ISOM), which generally comprise a network of columns. Incorporation of DWC technology to combine two or more columns in NHT and ISOM processes to improve overall profitability is discussed herein.

[0015] NHT and ISOM units often operate at high pressures and temperatures that result in a costly and energy-intensive operation. With the demand for NHT and ISOM units ramping up in the refining industry, DWCs can revolutionize these process schemes. DWCs not only improve the energy efficiency of the processes, but DWC can also provide a host of other benefits. These benefits include lower capital investment and the need for a relatively smaller plot area as compared to full-fledged conventional schemes.

Process Background

[0016] In exemplary NHT units, such as NHT unit **100** of FIG. 1, a stabilizer column **102** removes non-condensable gases from a feed **104** from a reactor section. A top liquid product **106** is fed from stabilizer column **102** to deethanizer column **108** to recover liquefied petroleum gas (LPG) product **110**. A bottoms product **112** is fed from stabilizer column **102** to a two-column naphtha splitter sequence comprising a first naphtha splitter **114** and a second naphtha splitter **116**. The two-column naphtha splitter sequence separates a light naphtha (mostly C5-C6 components) **118**, a mid-cut naphtha (C7) **120**, and a heavy naphtha (C8 and heavier) **122**. The light naphtha **118** is processed by a deisopentanizer column **124** to separate an i-C5 rich stream **126** from the top of deisopentanizer column **124**. An n-C5 and heavier or bottoms fraction **128** is fed to an ISOM reactor **130**.

[0017] In most process schemes, stabilizer column **102** operates at a high pressure, which requires the use of relatively expensive medium-pressure (MP) steam. Additionally, due to the use of partial condensation, significant C3-C4 losses are observed in the offgas.

[0018] This leads to the use of the supplementary deethanizer column **108** to recover LPG product **110** from the offgas. An isomerization feed is prepared from the bottoms product **112** in the two-column naphtha splitter sequence.

[0019] Still referring to FIG. 1, an ISOM unit **150** comprises a multitude of columns including stabilizer column **154**, depentanizer column **156**, and deisohexanizer column **158**. Deisopentanizer column **124** separates high-octane i-C5 **126** components from the feed and recycle streams. Low-octane components (the n-C5 and heavier fraction **128**) from deisopentanizer column **124** bottoms are sent to the ISOM reactor **130** to produce high-octane components, along with some light components. Product **131** from ISOM reactor **130** is fed to stabilizer column **154**. Stabilizer column **154** removes lighter hydrocarbons (C4-) **160** in the offgas.

[0020] Stabilized isomerate **162** is fed to depentanizer column **156** to concentrate C5. C5 **157** is recycled from depentanizer column **156** to deisopentanizer column **124**. In some aspects, a portion of C5 **157** is recycled to depentanizer column **156**. Downstream deisohexanizer column **158** then separates a light isomerate **164** (mainly i-C6) and a heavy isomerate **166** (mainly C7+ cut), along with a concentrated n-C6 cut **168**. The concentrated n-C6 cut **168** is recycled to ISOM reactor **130** for octane upgrading.

[0021] DWCs work on the principle of removing intrinsic thermodynamic design flaws in conventional distillation columns. One of these flaws arises due to back-mixing of the feed with a side cut based on a location of the two streams. Quality of the side cut is affected by contamination of lighter or heavier components. Using a DWC eliminates this problem and produces a better-quality side cut. Therefore, the two-naphtha-splitter operation of FIG. 1 is made possible in a single DWC of the instant invention. The series of columns of FIG. 1 present a good opportunity to incorporate DWC technology to improve the efficiency of the entire process. DWCs can be utilized to combine the operation of two or more columns while achieving the same product specifications as the conventional scheme. As a result, capital investment is lowered by 20%-30%. Moreover, these columns can either be operated at lower temperatures or have lower utility requirements. Energy savings in the range of 20%-30% are expected with a DWC configuration.

Dividing Wall Columns in NHT and ISOM Units

[0022] Compared to NHT unit **100** and ISOM unit **150** of FIG. 1, NHT unit **100** and ISOM unit **150** of FIG. 2 have been modified to include DWCs. For example: the stabilizer column **102** and the deethanizer **108** of FIG. 1 have been replaced with a top dividing wall LPG recovery column **202**; the naphtha splitters **114**, **116** have been replaced with a DWC naphtha splitter **220**; and the depentanizer column **156** and the deisohexanizer column **158** have been replaced with a DWC depentanizer/deisohexanizer column **250**. The top dividing wall LPG recovery column **202** includes within it a wall **203** that isolates a top portion of the top dividing wall LPG recovery column **202** into two halves (a top section **204** and a top section **206**) that basically operate as independent columns. Wall **203** prevents any intermixing or leakage between the two sides. As a result, separate unit operations can be performed within the top dividing wall LPG recovery column **202**.

[0023] FIGS. 3A and 3B illustrate a side-by-side comparison of the two naphtha splitters **114**, **116** of FIG. 1 with DWC naphtha splitter **220** of FIG. 2. DWC naphtha splitter **220** has a middle wall **222** that divides DWC naphtha splitter **220** into two middle sections **224**, **226**. Bottoms product **112** from top dividing wall LPG recovery column **202** is fed to middle section **224** of DWC naphtha splitter **220**. Light naphtha **118** is fed from a top of DWC naphtha splitter **220** to deisopentanizer **124**. DWC naphtha splitter **220** also separates out mid-cut naphtha **120** as a side cut and heavy naphtha **122** as a bottoms product.

[0024] FIGS. 4A and 4B illustrate a side-by-side comparison of stabilizer **102** and deethanizer **108** of FIG. 1 with top dividing wall LPG recovery column **202** of FIG. 2. The top dividing wall LPG recovery column **202** has a top wall **203** that divides the top dividing wall LPG recovery column **202** into two top sections **204**, **206**. Feed **104** and optionally ISOM stream **216** enters top section **204**. In an embodiment of top dividing wall LPG recovery column **202**, top section **204** is used for absorption and top section **206** is used for distillation. In addition, the parallel separation zones that have been created by wall **203** tend to minimize an overall height of top dividing wall LPG recovery column **202** as compared to the NHT unit **100** that includes individual columns (i.e., stabilizer column **102** and deethanizer column **108**). A similar number of theoretical stages (or trays) can be accommodated in the two zones for a desired separation.

[0025] A heavy hydrocarbon stream strips offgas **208** of C3-C4 components from the absorption section **204** of top dividing wall LPG recovery column **202**. These components are concentrated and removed on distillation side **206** as LPG product **110**. A portion **214** of bottom product **112** from the top dividing wall LPG recovery column **202** can be recycled back to absorption section **204** and used for absorption if the feed contains a suitable amount of C5. Alternatively, a lean naphtha stream can be used alongside the heavier C5 stream or independently as the absorption medium. Other offgas streams in the refinery that are rich in C3-C4 components, such as an ISOM stream **216**, can be fed to top dividing wall LPG recovery column **202** to improve LPG recovery (see FIG. 2 and FIG. 4). As a result, other stabilizers can be operated under relatively lower pressures and a lower-temperature heating utility.

[0026] FIG. 5 illustrates a top DWC concept that combines operation of depentanizer and deisohexanizer columns, such as depentanizer column **156** and deisohexanizer column **158**. A first top section **252** of DWC depentanizer/deisohexanizer column **250** acts as a prefractionation column to concentrate C5 components (e.g., C5 components from stabilizer **154**). Middle boiling components (C6) and heavy boiling components (C7 and heavier) are pushed down DWC depentanizer/deisohexanizer column **250** to a second top section **254** that acts as a main fractionation side. C6 isomerate is separated as top product **164** from top section **254**. Concentrated n-C6 stream **168** is removed as a side cut from a location below a bottom of a dividing wall **251** and recycled to ISOM reactor **130**. A bottom product of C7+ cut is obtained as heavy isomerate **166**. In some embodiments, second top section **254** is heat-integrated with deisopentanizer column **124** via lines **260**, **261**. Lines **260**, **261** are coupled to a heat exchanger **262** that exchanges heat between a fluid from second top section **254** and a bottoms product of deisopentanizer column **124**. FIG. 2-6 illustrate other heat exchangers associated with the depicted columns. In various embodiments, these heat exchangers can be used as needed to transfer heat between fluids of the processes described herein. FIGS. 6A and 6B illustrate a side-by-side comparison of deethanizer column **108** and deisopentanizer column **124** of FIG. 1 with DWC depentanizer/deisohexanizer column **250** of FIG. 2.

[0027] For regions with high utility costs, further energy savings are possible through the overhead heat integration of a top DWC (e.g., see FIGS. 5 and 6). The DWC depentanizer/deisohexanizer column **250** operates at an elevated pressure. As a result, hot overhead vapors on the main fractionation side **254** can be used to provide heating duty to the deisopentanizer column **124** in the NHT unit (See FIGS. 5 and 6). The stream is capable of providing the entire duty required by the deisopentanizer column **124**; otherwise, the column typically operates on low-pressure steam.

[0028] In various embodiments, aspects of FIGS. 2-6 may be incorporated into the NHT unit **100** and the ISOM unit **150** to create new systems that include the inventive DWCs discussed herein.

[0029] Benefits of a network of DWCs in NHT and ISOM units are summarized in.

[0030] TABLES 1 and 2 below:

TABLE 1

Equipment Count, CAPEX and OPEX Comparison			
Parameters	Units	Conventional Design	DWC Design
No. of Columns	—	8	5
Energy Savings	%	—	24%
Capital Cost	%	Base	70% of Base

TABLE 2

Heating Utility Comparison			
Parameters	Units	Conventional Design	Instant DWC with Heat Integration
Feed Rate to NHT Unit	TPH	57	57
Isomerate product	TPH	28.6	28.6
RON of isomerate product	—	92	92
LPG Product Rate	TPH	5.00	7.5
Off Gas Rate	TPH	3.7	1.2
NHT Stabilizer	MMKcal/hr	7.0	7.3
Deethanizer	MMKcal/hr	2.0	
Naphtha Splitter 1 & 2	MMKcal/hr	16.6	13.3
Deisopentanizer	MMKcal/hr	12.7	0.9
ISOM Stabilizer	MMKcal/hr	3.0	3.0
Depentanizer	MMKcal/hr	8.0	20.9
Deisohexanizer	MMKcal/hr	10.4	
Total Heating Duty	MMKcal/hr	59.7	45.4

[0031] DWCs provide an innovative method of reducing the capital and energy costs of complex refinery processes such as isomerization and naphtha hydrotreating. Integrating DWC technology into an NHT/ISOM process scheme can provide substantial benefits, including: a lesser number of columns and associated equipment for the entire configuration; improved LPG recovery; reduced energy costs due to low temperature utility used for heating; and better heat integration within the columns.

[0032] The term “substantially” is defined as largely but not necessarily wholly what is specified (and includes what is specified; e.g., substantially 90 degrees includes 90 degrees and substantially parallel includes parallel), as understood by a person of ordinary skill in the art. In any disclosed embodiment, the terms “substantially,” “approximately,” “generally,” and “about” may be substituted with “within [a percentage] of” what is specified, where the percentage includes 0.1, 1, 5, and 10 percent.

[0033] The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the disclosure. Those skilled in the art should appreciate that they may readily use the disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the disclosure, and that they may make various changes, substitutions and alterations herein without departing from the spirit and scope of the disclosure. The scope of the invention should be determined only by the language of the claims that follow. The term “comprising” within the claims is intended to mean “including at least” such that the recited listing of elements in a claim are an open group. The terms “a,” “an” and other singular terms are intended to include the plural forms thereof unless specifically excluded.

What is claimed is:

1. A processing unit comprising:
 - a naphtha hydrotreating unit comprising a first divided wall column, the first divided wall column comprising:
 - a wall dividing a top portion of the first divided wall column into a first top section and a second top section;
 - an outlet associated with the second top section of the first divided wall column for recovery of liquid petroleum gas; and
 - an outlet associated with a bottoms portion of the first divided wall column and coupled to a naphtha splitter system;
 - a deisopentanizer column coupled to an output of a naphtha splitter of the naphtha splitter system;
 - an isomerization unit coupled to an outlet of the deisopentanizer column and comprising a second divided wall column, the second divided wall column comprising:
 - a wall dividing a top portion of the second divided wall column into a first top section and a second top section;
 - an inlet coupled to an outlet of a stabilizer column of the isomerization unit;
 - an outlet associated with the second top section of the second divided wall column for recovery of a first isomerate stream; and
 - an outlet associated with a bottoms portion of the second divided wall column for recovery of a second isomerate stream;
 - an isomerization reactor coupled between the deisopentanizer column and the stabilizer column.
2. The processing unit of claim 1, wherein the naphtha splitter system comprises a third divided wall column, the third divided wall column comprising:
 - a wall dividing a middle portion of the third divided wall column into a first middle section and a second middle section;
 - an inlet coupled to the bottoms portion of the first divided wall column;
 - an outlet associated with a top portion of the third divided wall column for recovery of a first naphtha stream;
 - an outlet associated with the second middle section for recovery of a second naphtha stream; and
 - an outlet associated with a bottoms portion of the third divided wall column for recovery of a third naphtha stream.
3. The processing unit of claim 1, wherein the stabilizer column is coupled to the first divided wall column.
4. The processing unit of claim 1, wherein the isomerization reactor is coupled to the bottoms portion of the second divided wall column.
5. The processing unit of claim 1, wherein the second divided wall column is heat integrated with the deisopentanizer column.
6. The processing unit of claim 1, further comprising an inlet associated with the first top section of the first divided wall column and coupled to the bottoms portion of the first divided wall column.
7. The processing unit of claim 1, further comprising an outlet associated with the first top section of the second divided wall column and coupled to the deisopentanizer column.
8. The processing unit of claim 1, wherein the first top section of the first divided wall column is configured to perform as a stabilizer and the second top section of the first divided wall column is configured to perform as deethanizer.
9. The processing unit of claim 1, wherein the first top section of the second divided wall column is configured to perform as a depentanizer and the second top section of the second divided wall column is configured to perform as a deisohexanizer.
10. A heat-integrated process for a system comprising a naphtha hydrotreating unit and an isomerization unit, the process comprising:
 - providing a feed to a first divided wall column, the first divided wall column comprising:
 - a wall dividing a top portion of the first divided wall column into a first top section and a second top section;
 - an outlet associated with the second top section of the first divided wall column for recovery of liquid petroleum gas; and
 - an outlet associated with a bottoms portion of the first divided wall column and coupled to a naphtha splitter system;
 - removing liquid petroleum gas from the second top section of the first divided wall column;
 - feeding a bottoms product from the first divided wall column to a second divided wall column, the second divided wall column comprising:
 - a wall dividing a middle portion of the second divided wall column into a first middle section and a second middle section;
 - an inlet coupled to the bottoms portion of the first divided wall column;
 - an outlet associated with a top portion of the second divided wall column for recovery of a first naphtha stream;
 - an outlet associated with the second middle section for recovery of a second naphtha stream; and
 - an outlet associated with a bottoms portion of the second divided wall column for recovery of a third naphtha stream;
 - feeding the first naphtha stream from the top portion of the second divided wall column to a deisopentanizer column;
 - feeding a bottoms fraction from the deisopentanizer column to an isomerization reactor;
 - feeding a product from the isomerization reactor to a stabilizer column;
 - feeding isomerate from the stabilizer column to a third divided wall column, the third divided wall column comprising:
 - a wall dividing a top portion of the third divided wall column into a first top section and a second top section;
 - an inlet coupled to an outlet of a stabilizer column of the isomerization unit;
 - an outlet associated with the second top section of the third divided wall column for recovery of a first isomerate stream; and
 - an outlet associated with a bottoms portion of the third divided wall column for recovery of a second isomerate stream;
 - recovering isomerate from the third divided wall column.

11. The process of claim **10**, further comprising feeding an ISOM stream from the stabilizer column to the first top section of the first divided wall column.

12. The process of claim **10**, further comprising exchanging heat between a fluid from the second top section of the third divided wall column and a bottoms product of the deisopentanizer column.

13. The process of claim **10**, further comprising feeding C5 from the first top section of the third divided wall column to the deisopentanizer column.

14. The process of claim **10**, further comprising feeding C6 from the third divided wall column to the isomerization reactor.

15. The process of claim **10**, further comprising feeding a bottoms product of the first divided wall column to the first top section of the first divided wall column.

16. The process of claim **10**, wherein the second divided wall column is heat integrated with the deisopentanizer column.

17. The process of claim **10**, wherein the first divided wall column further comprises an inlet associated with the first top section of the first divided wall column and coupled to the bottoms portion of the first divided wall column.

18. The process of claim **10**, wherein the second divided wall column further comprises an outlet associated with the first top section of the second divided wall column and coupled to the deisopentanizer column.

19. The process of claim **10**, wherein the first top section of the first divided wall column is configured to perform as a stabilizer and the second top section of the first divided wall column is configured to perform as deethanizer.

20. The process of claim **10**, wherein the first top section of the second divided wall column is configured to perform as a depentanizer and the second top section of the second divided wall column is configured to perform as a deisohexanizer.

* * * * *