



US009285180B2

(12) **United States Patent**  
**McPherson**

(10) **Patent No.:** **US 9,285,180 B2**  
(45) **Date of Patent:** **Mar. 15, 2016**

(54) **BOW LIMB RETAINING SYSTEM**

(56) **References Cited**

(71) Applicant: **MCP IP, LLC**, Sparta, WI (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Mathew A. McPherson**, Norwalk, WI (US)

480,879 A	8/1892	Stevenson	
RE13,844 E	12/1914	Sawyer	
1,371,619 A	3/1921	Greenstreet	
3,161,189 A *	12/1964	Chessman	F41B 5/0005 124/23.1
3,486,495 A *	12/1969	Allen	F41B 5/10 124/25.6
4,178,905 A *	12/1979	Groner	F41B 5/10 116/294
4,261,320 A *	4/1981	Barna	F41B 5/105 124/25.6
4,574,766 A *	3/1986	Izuta	F41B 5/0026 124/23.1
4,644,929 A *	2/1987	Peck	F41B 5/10 124/23.1
4,674,468 A *	6/1987	Izuta	F41B 5/0026 124/23.1
5,025,774 A *	6/1991	Martin	F41B 5/143 124/23.1
5,099,819 A *	3/1992	Simonds	F41B 5/10 124/23.1
5,172,679 A	12/1992	Mussack	
5,231,970 A *	8/1993	Ploot	F41B 5/10 124/23.1
5,280,779 A *	1/1994	Smith	F41B 5/0026 124/23.1

(73) Assignee: **MCP IP, LLC**, Sparta, WI (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/257,593**

(22) Filed: **Apr. 21, 2014**

(65) **Prior Publication Data**

US 2014/0224236 A1 Aug. 14, 2014

**Related U.S. Application Data**

(63) Continuation of application No. 13/909,663, filed on Jun. 4, 2013, now Pat. No. 8,701,644, which is a continuation of application No. 12/916,261, filed on Oct. 29, 2010, now Pat. No. 8,453,635.

(60) Provisional application No. 61/256,844, filed on Oct. 30, 2009.

(51) **Int. Cl.**  
**F41B 5/00** (2006.01)  
**F41B 5/14** (2006.01)  
**F41B 5/10** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **F41B 5/1403** (2013.01); **F41B 5/10** (2013.01); **F41B 5/14** (2013.01); **F41B 5/0026** (2013.01)

(58) **Field of Classification Search**  
CPC ..... F41B 5/10; F41B 5/0026; F41B 5/14  
USPC ..... 124/23.1, 25, 25.6, 86, 88  
See application file for complete search history.

(Continued)

**OTHER PUBLICATIONS**

U.S. Appl. No. 61/256,844, filed Oct. 30, 2009; Inventor: Mathew A. McPherson.


(Continued)

*Primary Examiner* — Alexander Niconovich

(57) **ABSTRACT**

A bow limb retaining assembly comprises a limb and a retainer having a cavity for receiving the limb. The retainer comprises opposed lateral surfaces, a first abutting surface arranged to contact a compression surface of the limb and a second abutting surface arranged to contact a tension surface of the limb. A first length portion of the retainer includes the first abutting surface and excludes the second abutting surface, and a second length portion of the retainer includes the second abutting surface and excludes the first abutting surface.

**20 Claims, 10 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

5,339,790	A *	8/1994	Smith	.....	F41B 5/10	6,786,214	B2 *	9/2004	Andrews	.....	F41B 5/0026
					124/23.1						124/23.1
5,368,006	A	11/1994	McPherson			6,886,549	B2 *	5/2005	McPherson	.....	F41B 5/0026
5,377,658	A *	1/1995	Shepley, Jr.	.....	F41B 5/10						124/23.1
					124/23.1	6,941,937	B2 *	9/2005	Wheeler	.....	F41B 5/10
5,408,982	A *	4/1995	Doornenbal	.....	F41B 5/0094						124/23.1
					124/23.1	6,964,271	B2	11/2005	Andrews		
5,411,008	A *	5/1995	Hsu	.....	F41B 5/14	7,025,051	B1 *	4/2006	Gallops, Jr.	.....	F41B 5/10
					124/23.1						124/23.1
5,429,106	A *	7/1995	Martin	.....	F41B 5/0026	7,077,116	B1 *	7/2006	Darlington	.....	F41B 5/10
					124/23.1						124/23.1
5,433,792	A *	7/1995	Darlington	.....	F41B 5/10	7,308,890	B1 *	12/2007	Wheeler	.....	F41B 5/10
					124/23.1						124/23.1
5,464,001	A *	11/1995	Peck	.....	F41B 5/10	7,334,575	B2 *	2/2008	McPherson	.....	F41B 5/0026
					124/23.1						124/23.1
5,487,373	A *	1/1996	Smith	.....	F41B 5/10	7,584,750	B2 *	9/2009	Chang	.....	F41B 5/12
					124/23.1						124/23.1
5,507,270	A *	4/1996	Smith	.....	F41B 5/0026	7,784,452	B1 *	8/2010	Kronengold	.....	F41B 5/10
					124/23.1						124/23.1
5,515,836	A *	5/1996	Martin	.....	F41B 5/0026	7,918,218	B1 *	4/2011	Kronengold	.....	F41B 5/10
					124/23.1						124/23.1
5,546,923	A	8/1996	Duncan			8,047,189	B2 *	11/2011	McPherson	.....	F41B 5/10
5,592,929	A *	1/1997	Hoyt, Jr.	.....	F41B 5/1438						124/23.1
					124/23.1	8,069,847	B2 *	12/2011	Blosser	.....	F41B 5/0026
5,660,158	A *	8/1997	Rudolph	.....	F41B 5/0026						124/23.1
					124/23.1	8,347,869	B2 *	1/2013	Sims	.....	F41B 5/10
5,697,355	A *	12/1997	Schaffer	.....	F41B 5/105						124/23.1
					124/25.6	8,448,630	B1 *	5/2013	McPherson	.....	F41B 5/1403
5,697,358	A *	12/1997	Campisi	.....	F41B 5/10						124/23.1
					124/23.1	8,453,635	B1	6/2013	McPherson		
5,720,267	A *	2/1998	Walk	.....	F41B 5/10	8,701,644	B2	4/2014	McPherson		
					124/23.1	8,776,770	B2 *	7/2014	Batdorf	.....	F41B 5/10
5,722,380	A *	3/1998	Land	.....	F41B 5/10						124/23.1
					124/23.1	2003/0084893	A1	5/2003	Andrews		
5,947,099	A	9/1999	Derus			2004/0077440	A1	4/2004	Kronfeld		
6,024,076	A *	2/2000	Laborde	.....	F41B 5/0026	2008/0072888	A1 *	3/2008	Chang	.....	F41B 5/12
					124/23.1						124/25
6,244,259	B1 *	6/2001	Adkins	.....	F41B 5/0026	2008/0127961	A1 *	6/2008	McPherson	.....	F41B 5/10
					124/23.1						124/88
6,257,220	B1	7/2001	McPherson et al.			2008/0156310	A1	7/2008	Leven		
6,267,108	B1	7/2001	McPherson et al.			2008/0236557	A1	10/2008	Budd		
6,360,734	B1 *	3/2002	Andrews	.....	F41B 5/10	2009/0071457	A1	3/2009	Gordon et al.		
					124/23.1	2009/0071458	A1	3/2009	Gordon et al.		
6,371,098	B1	4/2002	Winther			2009/0145411	A1 *	6/2009	Sims	.....	F41B 5/10
6,470,870	B1 *	10/2002	Schaar	.....	F41B 5/10						124/25.6
					124/25.6	2009/0241928	A1 *	10/2009	Blosser	.....	F41B 5/10
6,543,432	B2 *	4/2003	Andrews	.....	F41B 5/10						124/25.6
					124/23.1	2010/0263650	A1 *	10/2010	Dahl, II	.....	F41B 5/10
6,571,785	B1 *	6/2003	Choma	.....	F41B 5/123						124/25.6
					124/23.1						
6,712,057	B2 *	3/2004	Andrews	.....	F41B 5/0026						
					124/23.1						

OTHER PUBLICATIONS

Jennings Archery, Advertisement, FNT(TM) Limbs, Date Unknown.

\* cited by examiner




FIG. 1




FIG. 2







FIG. 4






FIG. 6






FIG. 7






FIG. 8








FIG. 10

**BOW LIMB RETAINING SYSTEM****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 13/909663, filed Jun. 4, 2013, which is a continuation of U.S. patent application Ser. No. 12/916261, filed Oct. 29, 2010, now U.S. Pat. No. 8,453,635, which claims the benefit of U.S. Provisional Patent Application No. 61/256844, filed Oct. 30, 2009, the entire disclosures of which are hereby incorporated herein by reference

**BACKGROUND OF THE INVENTION**

This invention relates to an archery bow and more specifically a system for retaining archery bow limbs.

All US patents and applications and all other published documents mentioned anywhere in this application are incorporated herein by reference in their entirety.

Prior art archery bows are known to have bow limbs anchored to a bow handle. In many cases, these archery bows use a limb pocket to attach the bow limbs to the bow handle. In order to retain a limb in the limb pocket, known limb pockets sandwich a portion of the bow limb between a floor of the limb pocket and an opposing ceiling. Alternatively, known limb pockets sandwich a limb between the floor of the limb pocket and the head of a threaded bolt.

These prior art limb pockets and limbs have a number of disadvantages. For example, removal of the limb can be difficult, and may include first removing a number of other components, including bolts, washers, spacers, and alignment plates. Another disadvantage is the manner in which prior art limbs are secured to the bow handle. For example, the "sandwiched limbs" of the prior art utilize a bolt that is placed in an undesirable single-shear condition.

In light of these and other disadvantages found in prior art archery bows, there remains a need for improved limb retainers.

Without limiting the scope of the invention a brief summary of some of the claimed embodiments of the invention is set forth below. Additional details of the summarized embodiments of the invention and/or additional embodiments of the invention may be found in the Detailed Description of the Invention below.

A brief abstract of the technical disclosure in the specification is provided as well only for the purposes of complying with 37 C.F.R. 1.72. The abstract is not intended to be used for interpreting the scope of the claims.

**BRIEF SUMMARY OF THE INVENTION**

In some embodiments, a limb retainer comprises first and second surfaces and shaped sidewall portions. A limb comprises shaped sidewall portions configured to engage the sidewall portions of the limb retainer to prevent longitudinal movement of the limb. The limb is received in the limb retainer such that one of the surfaces abuts a compression side of the limb and the other surface abuts a tension side of the limb. The first and second surfaces provide forces that counteract forces applied to a distal end of the limb, such as forces applied by a bowstring.

In some embodiments, a bow limb retaining assembly comprises a limb and a retainer having a cavity for receiving the limb. The retainer comprises a first lateral surface and a second lateral surface opposed to the first lateral surface. The first lateral surface comprising an interlocking portion and the

second lateral surface comprising an interlocking portion. The bow limb has a tension surface, a compression surface and first and second outer sides. The first outer side comprises a first limb interlocking portion and the second outer side comprises a second limb interlocking portion. The first lateral surface interlocking portion is configured to matingly engage the first limb interlocking portion. The second lateral surface interlocking portion configured to matingly engaged the second limb interlocking portion.

In some embodiments, a bow limb retaining assembly comprises a limb and a retainer having a cavity for receiving the limb. The retainer comprises opposed lateral surfaces, a first abutting surface arranged to contact a compression surface of the limb and a second abutting surface arranged to contact a tension surface of the limb. A first length portion of the retainer includes the first abutting surface and excludes the second abutting surface, and a second length portion of the retainer includes the second abutting surface and excludes the first abutting surface.

These and other embodiments which characterize the invention are pointed out with particularity in the claims annexed hereto and forming a part hereof. However, for a better understanding of the invention, its advantages and objectives obtained by its use, reference can be made to the drawings which form a further part hereof and the accompanying descriptive matter, in which there are illustrated and described various embodiments of the invention.

**BRIEF DESCRIPTION OF THE INVENTION**

A detailed description of the invention is hereafter described with specific reference being made to the drawings.

FIG. 1 shows an embodiment of an archery bow.

FIG. 2 shows an embodiment of an assembly comprising a limb retainer and a limb.

FIG. 3 shows another view of a limb retainer and a limb.

FIG. 4 shows another embodiment of an archery bow.

FIG. 5 shows an embodiment of an assembly comprising a limb retainer and a plurality of limbs.

FIG. 6 shows another view of the limb retainer of FIG. 5.

FIG. 7 shows another view of the assembly of FIG. 5.

FIGS. 8-10 depict the assembly of FIG. 5 at various stages of assembly.

**DETAILED DESCRIPTION OF THE INVENTION**

While this invention may be embodied in many different forms, there are described in detail herein specific embodiments of the invention. This description is an exemplification of the principles of the invention and is not intended to limit the invention to the particular embodiments illustrated.

For the purposes of this disclosure, like reference numerals in the figures shall refer to like features unless otherwise indicated.

FIG. 1 shows an embodiment of an archery bow **10** comprising a limb retaining assembly **30**. The retaining assembly **30** retains a limb **14**, securing it to a bow handle **12**.

An archery bow **10** comprises a riser or handle **12**, a first limb **14** and a second limb **16**. In some embodiments, each limb **14**, **16** supports a respective rotatable member **20**, **22**, for example where the bow is a compound bow. In some embodiments, each rotatable member **20**, **22** can comprise a cam or pulley.

The archery bow **10** further comprises a bowstring **18**. The bowstring **18** extends between the first and second limbs **14**, **16** and, in some embodiments, engages rotatable members **20**, **22**, for example as in a compound archery bow. In some

embodiments, the bowstring extends between first and second limbs for attachment to the limbs, for example in a recurve archery bow (not shown).

Each limb **14**, **16** has a compression surface **32** and a tension surface **34**. The compression surface **32** of a first limb **14** faces the compression surface **32** of the second limb **16**, while the tension surfaces **34** of the first and second limbs **14**, **16** face outwardly away from each other.

Turning to FIG. 2, an embodiment of a limb retaining assembly **30** is shown in an exploded view. In some embodiments, the limb retaining system **30** comprises a limb retainer **40** and a first bow limb **14**. The limb retainer **40** comprises a first limb pocket **45**. The first limb pocket **45** comprises a first lateral surface **43** and a second lateral surface **44** opposite the first lateral surface **43** (FIG. 3). The first limb pocket **45** further comprises an abutting surface **24**. The first abutting surface **24** adjoins at least a portion of the first lateral surface **43** and the second lateral surface **44**. In some embodiments, the first and second lateral surfaces **43**, **44** are perpendicular to at least a portion of the abutting surface **24**. In some embodiments, the first and second lateral surfaces **43**, **44** form a V-shape, for example as disclosed in U.S. Pat. No. 6,886,549, the entire disclosure of which is hereby incorporated herein by reference.

In some embodiments, the first lateral surface **43** comprises a first interlocking portion **38**. In some embodiments, the first interlocking portion **38** comprises a protrusion extending into the limb cavity and outwardly from the first lateral surface **43**. The first interlocking portion **38** can also comprise any other suitable configuration arranged to mate with the limb **14**. For example, the first interlocking portion **38** can comprise a recess, groove, or notch cut into the first lateral surface **43**. The first interlocking portion **38** can further comprise any suitably shaped protrusion or engagement mechanism suitable to engage the limb **14**. For example, a protrusion can be semi-cylindrical, oblong, rectangular, or semi-spherical. Various recesses or cavities could also be used.

In some embodiments, the second lateral surface **44** comprises an interlocking portion **39**. In some embodiments, the interlocking portion **39** comprises a protrusion extending inwardly away from the second lateral surface **44** and toward the first lateral surface **43**. The interlocking portion **39** can also comprise any other suitable configuration. For example the interlocking portion **39** can comprise a recess, groove, or notch cut into the second lateral surface **44**. The second interlocking portion **39** can further comprise any suitably shaped protrusion. For example, the protrusion can be semi-cylindrical, oblong, rectangular, or semi-spherical.

In some embodiments, the interlocking portions **38**, **39** can be similarly shaped, for example being mirror images of one another. In some embodiments, the interlocking portions **38**, **39** can be different from one another.

In some embodiments, the first bow limb **14** comprises a first limb interlocking portion **36** and a second limb interlocking portion **37**. The first limb interlocking portion **36** is configured to engage the first interlocking portion **38** of the first lateral surface **43**. The second limb interlocking portion **37** is configured to engage the second interlocking portion **39** of the second lateral surface **44**. Desirably, the various interlocking portions engage one another and prevent movement of the limb **14** with respect to the limb retainer **40** in the limb **14** longitudinal direction.

In some embodiments, the first and second limb interlocking portions **36**, **37** comprise recesses that are complimentary with the protrusion of the first and second interlocking portions **38**, **39** of the first and second lateral surfaces **43**, **44**. In some embodiments, the first and second limb interlocking

portions **36**, **37** comprise protrusions that are complimentary with recesses of the first and second interlocking portions **38**, **39**. The first and second limb interlocking portions **36**, **37** can comprise any suitable shape, for example a recess, groove, or notch. Moreover, the first and second limb interlocking portions can comprise a protrusion in any suitable configuration, for example, semi-circular, oblong, rectangular, or semi-spherical. In some embodiments, the limb interlocking portions **36**, **37** extend from the compression surface to the tension surface **34** of the first limb **14**, for example as shown in FIG. 2.

In some embodiments, the lateral surfaces **43**, **44** can include curvature along one axis and be substantially straight in an orthogonal direction. For example, a lateral surface **43** can include curvature in a horizontal direction and be straight in a vertical direction. This allows a limb **14** to be easily inserted into the limb retainer **40**.

The first limb pocket **45** can further comprise any suitable number of interlocking portions, for example between 1 and 8 and the limb **14** can further comprise any suitable number of limb interlocking portions, for example between 1 and 8.

In some embodiments, the abutting surface **24** engages at least a portion of the bow limb compression surface **32**, providing support for the bow limb **14** when mounted in the first limb pocket **45**. In some embodiments, the abutting surface **24** can be shaped to mate with the compression side of the limb **14** in a way similar to the interlocking portions **38**, **39**. For example, the abutting surface **24** can comprise a protrusion that mates with a groove in the compression surface of the limb **14**, or vice versa.

The first and second interlocking portions **38**, **39** prevent the first limb **14** from moving longitudinally out of the limb pocket **45**, for example by counteracting forces applied at a distal end **56** of the bow limb **14**. In some embodiments, interlocking portions **38**, **39** are located along a proximal portion **46** of the limb retainer **40**. In some embodiments (not shown), the interlocking portions **38**, **39** are located at a distal portion **48** of the limb retainer **40** or in between the proximal portion **46** and the distal portion **48** of the limb retainer **40**, or at any other suitable location.

In some embodiments, the limb retainer **40** comprises a raised surface **42** or a plurality of raised surfaces **42**. As shown in FIG. 2, the raised surfaces **42** project from the first and second lateral surfaces **43**, **44** of the limb pocket **45**. The raised surface **42** is arranged to contact a portion of the limb lateral wall **50**. In this way, the raised surface(s) **42** prevent the first limb **14** from moving laterally within the limb pocket **45** and provide support for the first limb **14** at a desired region on the first limb **14**.

In some embodiments, the retaining assembly **30** comprises a fastener **52**, such as a cap screw. In some embodiments, the fastener **52** can hold the first bow limb **14** in the limb pocket **45** and fasten the retaining assembly **30** to the bow handle. In some embodiments, the fastener **52** can be threadably engaged to a portion of the handle, for example to adjust draw weight.

In some embodiments, the retaining assembly **30** can comprise a pivot **54**. The pivot **54** is configured to allow the limb retainer **40** to rotate about a pivot axis with respect to the riser **12**, for example to change the bow draw weight. The retaining assembly **30** can further comprise a fastener **64** which can be threadably engaged with a portion of the limb retainer **40**, the riser, or both. In some embodiments, a fastener **64** extends through the limb retainer **40** and engages the riser.

Turning now to FIG. 3, a top view of an embodiment of the limb retainer **40** is shown a proximal end of a first bow limb **14** in the limb retainer **40**. In some embodiments, at least a

5

portion of each of the limb lateral walls **50** contacts a raised surface **42**, providing a gap **58** between a portion of the limb lateral wall **50** and a portion of the first and second lateral surfaces **43**, **44**. The raised surfaces **42** permit the limb **14** to be positively located on a desired region of the lateral walls **50** of the first limb **14**. For example, as shown in FIG. 3 the raised surfaces **42** are positioned along the distal portion **48** of the limb retainer **40** to provide lateral stability for the first limb **14**.

In some embodiments, the first limb **14** has a tapered proximal end **55**, for example, as shown in FIG. 3. In some embodiments, the limb proximal end **55** can be provided without a taper. In some embodiments, the limb proximal end **55** is rounded, arcuate, or comprises any other suitable shape.

In some embodiments, a space **60** is defined between the proximal end **61** of the first bow limb **14** and the opposing wall **62** of the limb retainer **40**. The space **60** permits clearance proximal end **61** of the first bow limb **14** and the opposing wall **62**. In addition, the space **60** allows for proper alignment of the limb interlocking portions **36**, **37** with the retainer interlocking portions **38**, **39**, as the proximal end **61** does not directly contact the opposing wall **62**.

In some embodiments, a tapered configuration of the lateral surfaces **43**, **44**, and complimentary shape of the limb, allows for self-centering of the limb **14** with respect to the limb retainer **40** as the tapered limb **14** abuts the tapered lateral surfaces **43**, **44**. Further, in some embodiments, portions **66** of the first and second interlocking portions **38**, **39** can provide a reverse taper configuration. While the tapered lateral surfaces **43**, **44** of the limb retainer **40** provide a taper in the proximal direction of the limb **14**, the reverse tapered portions **66** of the first and second interlocking portions **38**, **39** provide a taper in the distal direction of the limb **14**. Thus, forces acting to displace the limb **14** in the proximal direction can cause the limb to self-center via the tapered lateral surfaces **43**, **44**, and forces acting to displace the limb **14** in the distal direction can cause the limb to self-center via the reverse tapered portions **66** of the first and second interlocking portions **38**, **39**.

In some alternative embodiments, the proximal end **61** of the limb **14** contacts the opposing wall **62**. In this way, there is no space **60**.

In some embodiments, the limb **14** comprises an aperture **15**, for example to receive a fastener **52** (see FIG. 2). In some embodiments, the limb **14** comprises a continuous structure that extends fully about the aperture **15**.

Turning to FIG. 4, an embodiment of an archery bow **110** is shown wherein multiple limb portions can be received by each limb retainer. The bow **110** comprises a limb retaining assembly **130**, a handle **112**, a third bow limb **115** and a fourth bow limb **117**. The retaining assembly **130** retains a third limb **115** by securing the limb **115** to an end of the bow handle **112**. The fourth bow limb **117** is shown with a compression surface **132** and a tension surface **134**. The archery bow **110** is generally referred to as a split-limb bow, having a first limb **114** (FIG. 5) disposed adjacent to a third limb **115** and a second bow limb **116** disposed adjacent to a fourth bow limb **117**. Although in some embodiments the archery bow **110** comprises a split-limb configuration, for example as shown in FIG. 4, various embodiments of the retaining assembly can be configured to work with a single limb (e.g., solid limb), while others are suited for split-limbs. Additionally, some embodiments of the retaining assembly can be configured to work with any suitable number of limbs.

Turning now to FIG. 5, an embodiment of the retaining assembly **130** is shown. In some embodiments, the retaining assembly **130** comprises a limb retainer **140**. The limb

6

retainer **140** comprises a first limb pocket **145** and a second limb pocket **146**. In some embodiments, each limb pocket **145**, **146** provided in the limb retainer **140** comprises the features described with respect to the limb pocket **45** described with respect to FIGS. 2 and 3.

In some embodiments, the first limb pocket **145** comprises a first lateral surface **143** and a second lateral surface **144** opposite the first lateral surface **143** (FIG. 6). The second limb pocket **146** comprises a first lateral surface **143** and a second lateral surface **144** opposite the first lateral surface **143**.

In some embodiments, the first limb pocket further comprises a first abutting surface **124** and a second abutting surface **125**. The first abutting surface **124** of the first limb pocket **145** adjoins at least a portion of the first and second lateral surfaces **143**, **144**. In some embodiments, the first and second lateral surfaces **143**, **144** of the first limb pocket **145** are perpendicular to at least a portion of the first abutting surface **124**. The second abutting surface **125** of the first limb pocket **145** adjoins at least a portion of the first and second lateral surfaces **143**, **144**. In some embodiments, the first and second lateral surfaces **143**, **144** of the first limb pocket **145** are perpendicular to at least a portion of the second abutting surface **125**.

In some embodiments, the second limb pocket **146** further comprises a first abutting surface **124** and a second abutting surface **125**. The first abutting surface **124** of the second limb pocket **146** adjoins at least a portion of the first and second lateral surfaces **143**, **144**. In some embodiments, the first and second lateral surfaces **143**, **144** of the second limb pocket **146** are perpendicular to at least a portion of the first abutting surface **124**. The second abutting surface **125** of the second limb pocket **146** adjoins at least a portion of the first and second lateral surfaces **143**, **144**. In some embodiments, the first and second lateral surfaces **143**, **144** of the second limb pocket **146** are perpendicular to at least a portion of the second abutting surface **125**.

In some embodiments, the first and second lateral surfaces **143**, **144** of the first limb pocket **145** comprise first and second interlocking portions **38**, **39**, respectively. In some embodiments, the first and second interlocking portions **38**, **39** comprise protrusions each extending inwardly from the respective first and second lateral surfaces **143**, **144**. The first and second interlocking portions **38**, **39** can comprise any other suitable configuration. For example, the first interlocking portion **38** can comprise a recess, groove, or notch cut into the first lateral surface **143**. The second interlocking portion **39** can further comprise any suitably shaped protrusion. For example, the protrusion can be semi-cylindrical, oblong, rectangular, or semi-spherical. The interlocking portion **39** can also comprise any other suitable configuration. For example the interlocking portion **39** can comprise a recess, groove, or notch cut into the second lateral surface **144**. The second interlocking portion **39** can further comprise any suitably shaped protrusion. For example, the protrusion can be semi-cylindrical, oblong, rectangular, or semi-spherical.

In some embodiments, the first bow limb **114** comprises a first limb interlocking portion **36** and a second limb interlocking portion **37** (FIG. 5). The first limb interlocking portion **36** is configured to engage the first interlocking portion **38** of the first lateral surface **143**. The second limb interlocking portion **37** is configured to engage the second interlocking portion **39** of the second lateral surface **144**.

In some embodiments, the first and second limb interlocking portions **36**, **37** comprise recesses that are complimentary with the protrusion of the first and second interlocking portions **38**, **39** of the first and second lateral surfaces **143**, **144**. In some embodiments, the first and second limb interlocking

portions **36, 37** comprise protrusions that are complimentary with recesses of the first and second interlocking portions **38, 39**. The first and second limb interlocking portions **36, 37** can comprise any suitable shape, for example a recess, groove, or notch. Moreover, the first and second limb interlocking portions can comprise a protrusion in any suitable configuration, for example, semi-circular, oblong, rectangular, or semi-spherical. In some embodiments, the limb interlocking portions **36, 37** extend from the compression surface to the tension surface **34** of the first limb **114**.

In some embodiments, each limb pocket **145, 146** comprises tapered wall portions **68** that provide for self-centering of the limb **56** with respect to the pocket (e.g. **145**). In some embodiments, the interlocking portions **38, 39** of each limb pocket **145, 146** can include reverse tapered portions **66** that provide for a reverse taper.

The first limb pocket **145** can further comprise any suitable number of interlocking portions, for example between 1 and 8 and the limb first **114** can further comprise any suitable number of limb interlocking portions, for example between 1 and 8.

In some embodiments, the first abutting surface **124** engages at least a portion of the bow limb compression surface **32**, providing support for the bow limb **114** when mounted in the first limb pocket **145**. In some embodiments, the second abutting surface **125** engages at least a portion of the bow limb tension surface **34**. In some embodiments, the first abutting surface **124** is located distally with respect to the second abutting surface **125** (thus, the second abutting surface **125** is located proximally with respect to the first abutting surface **124**). In some embodiments, the first abutting surface **124** and the second abutting surface **125** occupy separate length portions of the limb retainer **140**, and are not coextensive.

In some embodiments, the limb retainer **130** does not comprise any structure positioned opposite the first abutting surface **124** (e.g. does not include any structure that would contact the tension side of the limb opposite the first abutting surface **124**). Similarly, in some embodiments, the limb retainer **130** does not comprise any structure positioned opposite the second abutting surface **125** (e.g. does not include any structure that would contact the compression side of the limb opposite the second abutting surface **125**).

The first and second interlocking portions **38, 39** of the first limb pocket **145** prevent the first limb **114** from moving longitudinally out of the limb retainer **140** by counteracting the force applied at a distal end **56** of the bow limb **114**. In some embodiments, interlocking portions **38, 39** are located along a proximal portion **46** of the first limb pocket **145**. In some embodiments (not shown), the interlocking portions **38, 39** are located at a distal portion **48** of the first limb pocket **145** or in between the proximal portion **46** and the distal portion **48** of the limb retainer **140**, or at any other suitable location.

In some embodiments, the second limb pocket **146** can comprise any suitable number of interlocking portions, for example between 1 and 8 and the third bow limb **115** can further comprise any suitable number of limb interlocking portions, for example between 1 and 8.

In some embodiments, the first abutting surface **124** engages at least a portion of the bow limb compression surface **32**, providing support for the third bow limb **115** when mounted in the second limb pocket **146**. In some embodiments, the second abutting surface **125** engages at least a portion of the bow limb tension surface **34**.

The first and second interlocking portions **38, 39** of the second limb pocket **146** prevent the third limb **115** from moving longitudinally out of the limb retainer **140** by coun-

teracting the force applied at a distal end **56** of the third bow limb **115**. In some embodiments, interlocking portions **38, 39** are located along a proximal portion **46** of the second limb pocket **146**. In some embodiments (not shown), the interlocking portions **38, 39** are located at a distal portion **48** of the second limb pocket **146** or in between the proximal portion **46** and the distal portion **48** of the limb retainer **140**, or at any other suitable location.

In some embodiments, for example as shown in FIGS. **5** and **6**, the first abutting surface **124** is longitudinally offset from the second abutting surface **125** along the length of the limb retainer **140**. In some embodiments, the first abutting surface **124** is distal to the second abutting surface **125**, the second abutting surface **125** engaging a portion of the bow limb proximal to the first abutting surface **124**.

In some embodiments, the abutting surfaces **124, 125** are arranged to support the limb **114** by applying forces that counteract forces applied to the distal end **56** of the limb, for example by a bowstring.

In some embodiments, the third bow limb **115** is paired with the first bow limb **114**. In some embodiments, the first and third bow limbs **114, 115** can be interchangeable with one another. In some embodiments, the first slot **142** and the third slot **143** can be mirror images of one another.

In some embodiments, the retaining assembly **130** can define a hole **59** therethrough. The hole **59** can be disposed through a portion of the limb retainer **140** and can be circular, for example, or it can be oblong as shown in FIG. **5**; the hole **59** can be configured in any suitable shape. A fastener **52** can be positioned in the hole **59** to engage a portion of the handle (not shown). For example, the fastener **52** can comprise a bolt threadably engaged with a portion of the handle (not shown), wherein the draw weight of the bow can be adjusted by turning the bolt in or out as desired.

The retaining assembly **130** can comprise a pivot **54**. The pivot **54** permits the retaining assembly **130** to pivot on the bow handle (not shown), for example if the draw weight is changed.

As shown in FIGS. **5** and **6**, the first limb **114** is prevented from moving longitudinally within in the limb pocket by engagement of the interlocking portions **38, 39** with the first and second limb interlocking portions **36, 37**. The first limb **114** is further restrained by the first and second abutting surfaces **124, 125** which are configured to prevent the first limb **114** from moving relative to the first limb pocket as long as the bow is strung and the bowstring is in tension. Furthermore, the first limb **114** is restrained laterally by the first and second lateral surfaces **143, 144**. In this way, the first limb **114** can be easily removed from the first limb pocket **145** of the limb retainer **140** without having to remove fastener **52**. In order to remove the limb from the limb pocket, an archer or technician must first relieve the tension in the bowstrings, for example with a bow press as is known in the art. Then, the limb or limbs can simply be rotated and removed from the limb pocket or pockets, as explained below in greater detail and shown with respect to progressive steps of FIGS. **8-9**.

As shown in FIG. **7**, in some embodiments, the retaining assembly **130** can comprise a wear member **70**. In some embodiments, the wear member **70** is disposed between the compression surface **32** of the bow limb **114, 115** and a distal portion **48** of the first and second limb pockets **145, 146**. In some embodiments, the wear member **70** can comprise an insert disposed in the limb pocket.

The wear member **70** can have a wear surface **74**. In some embodiments, the wear surface **74** is curved, for example as shown in FIG. **7**. In some embodiments, the wear surface **74** has a convex shape, permitting a portion of the bow limb **114**,



**115** to smoothly translate across the wear surface **74** as the bow limb flexes, for example when the bow is drawn back. In some embodiments, the first retaining surface **74** is convex only along its length, but is substantially flat along its width. The wear surface **74** can be flat or substantially flat along its width and/or length. The wear surface can also comprise any other suitable shape. The wear member **70** can be constructed from any suitable material, for example low friction materials such as Nylon and/or other various polymers.

In some embodiments, the limb pocket **145**, **146** can comprise a recessed area **72**. The recessed area **72** can be configured such that a portion of the wear member **70** is located in the recessed area **72**. The recessed area **72** ensures that the wear member **70** is properly situated in the limb pocket **145**, **146**. In some embodiments, the recessed area **72** is made by machining or milling away material in the limb **145**, **146**. Other suitable methods can also be employed.

In some embodiments, the wear member **70** comprises an insert that is shaped to be inserted in the recessed area **72**.

Turning to FIGS. **8** and **9**, a method of inserting a first bow limb **114** in a retaining assembly **130** is shown. FIG. **8** shows a first bow limb **114** being aligned with a first limb pocket **145** such that the length of the bow limb **114** is perpendicular to axis **80**. In some embodiments, axis **80** extends through the retainer **140** parallel to the first abutting surface **124**.

As shown in FIG. **9**, the first limb **114** is inserted into the retainer **140**. More specifically, the first limb **114** is inserted into the first limb pocket **145**. The first limb **114** is then rotated about the axis **80** until the compression surface **32** contacts the first abutting surface **124** (FIG. **8**), the tension surface **34** contacts the second abutting surface **125** and the first and second retainer interlocking portions **38**, **39** matingly engage the first and second limb interlocking portions **36**, **37**, respectively.

FIG. **10** shows the first and third bow limbs **114**, **115** residing in the first and second limb pockets **145**, **146** of the retainer **140**.

These steps can be repeated for inserting a third bow limb in a similar fashion. Furthermore, the steps can be repeated with a second limb retainer and second and fourth bow limbs. In addition, where the limb retainer is configured to accept more than two limbs, the steps can be repeated for each additional limb.

Although not explicitly shown, in some embodiments the retaining assembly can comprise a limb pocket having first and second abutting surfaces for contacting respective compression and tension sides and retaining a single limb or solid-limb, as opposed to the split limb configuration shown in FIGS. **5** and **6**. Thus, the limb may be inserted according to the method disclosed above, and a second limb may be similarly inserted in a second limb retainer on the opposite end of the handle.

Any feature disclosed with respect to any particular embodiment of a limb and/or limb retainer disclosed herein can be combined with any other suitable embodiment of a limb and/or limb retainer.

In some embodiments, an abutting surface **124** engages at least a portion of the bow limb compression surface **32**, providing support for the bow limb **14** when mounted in the first limb pocket **45**. In some embodiments, the abutting surface **124** can be shaped to mate with the compression side of the limb **14** in a way similar to the interlocking portions **38**, **39**. For example, the abutting surface **124** can comprise a protrusion that mates with a groove in the compression surface of the limb **14**, or vice versa. Similarly, an abutting surface **125** can be shaped to mate with the tension side of the limb **14** in a way similar to the interlocking portions **38**, **39**. For example,

the abutting surface **125** can comprise a protrusion that mates with a groove in the tension surface of the limb **14**, or vice versa.

In some embodiments, an abutting surface **125** can be shaped to mate with another object or device that is arranged to engage a limb **14**. For example, referring to FIG. **2**, a limb **14** and fastener **52** can be provided, and the fastener **52** can be disposed through the limb **14**. A limb retainer can comprise an abutting surface **125** (see e.g. FIG. **9**) that is shaped to receive a portion of the fastener **52**, for example having a cavity shaped to mate with the fastener **52** head.

The above disclosure is intended to be illustrative and not exhaustive. This description will suggest many variations and alternatives to one of ordinary skill in this field of art. All these alternatives and variations are intended to be included within the scope of the claims where the term "comprising" means "including, but not limited to". Those familiar with the art may recognize other equivalents to the specific embodiments described herein which equivalents are also intended to be encompassed by the claims.

Further, the particular features presented in the dependent claims can be combined with each other in other manners within the scope of the invention such that the invention should be recognized as also specifically directed to other embodiments having any other possible combination of the features of the dependent claims. For instance, for purposes of claim publication, any dependent claim which follows should be taken as alternatively written in a multiple dependent form from all prior claims which possess all antecedents referenced in such dependent claim if such multiple dependent format is an accepted format within the jurisdiction (e.g. each claim depending directly from claim **1** should be alternatively taken as depending from all previous claims). In jurisdictions where multiple dependent claim formats are restricted, the following dependent claims should each be also taken as alternatively written in each singly dependent claim format which creates a dependency from a prior antecedent-possessing claim other than the specific claim listed in such dependent claim below.

This completes the description of the preferred and alternate embodiments of the invention. Those skilled in the art may recognize other equivalents to the specific embodiment described herein which equivalents are intended to be encompassed by the claims attached hereto.

The invention claimed is:

**1.** A bow limb retaining assembly comprising:

a retainer having a first limb pocket, the first limb pocket comprising a first lateral surface and a second lateral surface opposed to the first lateral surface, the first lateral surface comprising an interlocking portion comprising a protrusion or recess; and

a first bow limb having a tension surface, a compression surface and first and second outer sides, the first outer side comprising a first limb interlocking portion; the first lateral surface interlocking portion configured to matingly engage the first limb interlocking portion.

**2.** The bow limb retaining assembly of claim **1**, wherein the first limb pocket further comprises a first abutting surface and a second abutting surface, the first abutting surface contacting the compression surface and the second abutting surface contacting the tension surface.

**3.** The bow limb retaining assembly of claim **2**, wherein a first length portion of the retainer includes the first abutting surface and excludes the second abutting surface, and a second length portion of the retainer includes the second abutting surface and excludes the first abutting surface.

## 11

4. The bow limb retaining assembly of claim 1, wherein the first limb pocket defines an open space between the first lateral surface and the second lateral surface.

5. The bow limb retaining assembly of claim 1, wherein at least a portion of said first lateral surface is non-parallel to at least a portion of said second lateral surface.

6. The bow limb retaining assembly of claim 1, wherein said first lateral surface interlocking portion comprises a protrusion and a recess.

7. The bow limb retaining assembly of claim 1, wherein the retainer further comprises a second limb pocket, the second limb pocket having a first lateral surface and a second lateral surface opposed to the first lateral surface, the first lateral surface comprising an interlocking portion and the second lateral surface comprising an interlocking portion; and

a second bow limb comprising a first limb interlocking portion and a second limb interlocking portion;

the first lateral surface interlocking portion of the second limb pocket configured to matingly engage the first limb interlocking portion of the second bow limb, the second lateral surface interlocking portion of the second limb pocket configured to matingly engaged the second limb interlocking portion of the second bow limb.

8. The bow limb retaining assembly of claim 1, wherein the first lateral surface and the second lateral surface form a tapered portion.

9. The bow limb retaining assembly of claim 8, wherein the interlocking portions of the first lateral surface and the second lateral surface form a reverse-tapered portion, said reverse-tapered portion tapering in a direction opposite the tapered portion.

10. A bow limb retaining assembly comprising:

a limb having lateral sides, a tension surface and a compression surface; and

a retainer comprising a first lateral surface, a second lateral surface opposite said first lateral surface, a first abutting surface arranged to contact the compression surface of the limb and a second abutting surface arranged to contact the tension surface of the limb;

a portion of said retainer comprising a cavity arranged to receive said limb, said cavity defined by said first lateral surface, said second lateral surface, said second abutting surface and an aperture located opposite said second abutting surface;

wherein said aperture is sized to allow a portion of said limb to pass through said aperture as said limb is inserted into said cavity, said first lateral surface comprises an interlocking portion comprising a protrusion or recess, and at least one of said lateral sides of said limb comprises a complimentary interlocking portion.

11. The bow limb retaining assembly of claim 10, wherein said first lateral surface interlocking portion comprises a protrusion and a recess.

## 12

12. An archery bow comprising:

a riser;

a retainer attached to the riser, the retainer comprising a first lateral surface and a second lateral surface, the first lateral surface comprising a protrusion; and

a limb comprising a first side surface and a second side surface, the first side surface comprising a recess, a portion of the limb oriented between the first lateral surface and a second lateral surface of the retainer, the protrusion of the retainer engaging the recess of the limb.

13. The archery bow of claim 12, the second lateral surface of the retainer comprising a second protrusion, the second side surface of the limb comprising a second recess, the second protrusion of the retainer engaging the second recess of the limb.

14. The archery bow of claim 13, wherein the protrusion and the second protrusion are aligned with one another along a length of the limb.

15. The archery bow of claim 13, the retainer comprising a third lateral surface and a fourth lateral surface, the third lateral surface comprising a third protrusion, the bow comprising a second limb, the second limb comprising a third side surface and a fourth side surface, the third side surface comprising a third recess, a portion of the second limb oriented between the third lateral surface and the fourth lateral surface of the retainer, the third protrusion engaging the third recess.

16. The archery bow of claim 15, wherein the protrusion, second protrusion and the third protrusion are aligned with one another.

17. The archery bow of claim 15, the fourth lateral surface of the retainer comprising a fourth protrusion, the fourth side surface of the second limb comprising a fourth recess, the fourth protrusion engaging the fourth recess.

18. The archery bow of claim 12, the limb comprising a tension surface, the retainer abutting the tension surface.

19. The archery bow of claim 12, the archery bow further comprising:

a second retainer attached to the riser, the second retainer comprising a third lateral surface and a fourth lateral surface, the third lateral surface comprising a protrusion; and

a second limb comprising a third side surface and a fourth side surface, the third side surface comprising a third recess, a portion of the second limb oriented between the third lateral surface and the fourth lateral surface of the second retainer, the third protrusion engaging the third recess.

20. The archery bow of claim 19, the fourth lateral surface of the second retainer comprising a fourth protrusion, the fourth side surface of the second limb comprising a fourth recess, the fourth protrusion engaging the fourth recess.

\* \* \* \* \*