



US009430075B2

(12) **United States Patent**  
**Kim**

(10) **Patent No.:** **US 9,430,075 B2**  
(45) **Date of Patent:** **\*Aug. 30, 2016**

(54) **SIGNAL ENHANCEMENT**

(71) Applicant: **Empire Technology Development LLC**,  
Wilmington, DE (US)

(72) Inventor: **Seungil Kim**, Seoul (KR)

(73) Assignee: **EMPIRE TECHNOLOGY  
DEVELOPMENT LLC**, Wilmington,  
DE (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **14/701,460**

(22) Filed: **Apr. 30, 2015**

(65) **Prior Publication Data**  
US 2015/0261335 A1 Sep. 17, 2015

**Related U.S. Application Data**

(63) Continuation of application No. 13/700,078, filed as  
application No. PCT/US2012/024175 on Feb. 7, 2012,  
now Pat. No. 9,037,090.

(51) **Int. Cl.**  
**H04B 15/00** (2006.01)  
**G06F 3/041** (2006.01)  
**G06F 1/16** (2006.01)  
**G06F 3/044** (2006.01)  
**G06F 3/045** (2006.01)  
**H04W 4/00** (2009.01)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/041** (2013.01); **G06F 1/1613**  
(2013.01); **G06F 3/044** (2013.01); **G06F 3/045**  
(2013.01); **G06F 3/0416** (2013.01); **H04B**  
**15/00** (2013.01); **H04W 4/008** (2013.01)

(58) **Field of Classification Search**

CPC ..... H04B 15/00  
USPC ..... 455/63.1, 456.1, 457; 345/173  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2002/0050983 A1 5/2002 Liu et al.  
2005/0113953 A1 5/2005 Smaragdis  
2008/0246736 A1 10/2008 Han  
2009/0137204 A1 5/2009 Chang

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 101286913 A 10/2008  
KR 10-2008-0091598 A 10/2008  
WO 2008121905 A2 9/2008

**OTHER PUBLICATIONS**

Non-Final Rejection mailed on Aug. 8, 2014 for U.S. Appl. No.  
13/700,078.

(Continued)


*Primary Examiner* — Tuan H Nguyen

(74) *Attorney, Agent, or Firm* — Brundidge & Stanger, P.C.

(57) **ABSTRACT**

Technologies and implementations for signal enhancement  
are generally disclosed. In some examples, a method to  
enhance a signal may include receiving a determined location  
of a device on a surface of a touch screen, detecting a first  
signal and a direction of the first signal from the device with  
two or more wireless signal detectors, and enhancing a sec-  
ond signal from the device with beamforming. Enhancing the  
second signal may be based, at least in part, on the location of  
the device and the detected first signal from the device.

**25 Claims, 6 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2010/0167664 A1 7/2010 Szini  
2010/0289752 A1 11/2010 Birkler  
2011/0058676 A1 3/2011 Visser

OTHER PUBLICATIONS

Kurita, S., et al., "Evaluation of blind signal separation method using directivity pattern under reverberant conditions", ICASSP 2000, Pro-

ceedings of the Acoustics, Speech, and Signal Processing, pp. 3140-3143, Jun. 2000, IEEE Computer Society, Washington DC, USA.

International search Report and Written Opinion of the International Searching Authority received for International Application No. PCT/US2012/024175, mailed on May 18, 2012.

International Preliminary Report on Patentability received for International Application No. PCT/US2012/024175, mailed on Aug. 12, 2014.

Notice of Allowance received for U.S. Appl. No. 13/700,078, mailed on Jan. 20, 2015.






FIG. 2




FIG. 3




FIG. 4

500 A computer program product.

502 A signal bearing medium.

504 Machine-readable non-transitory medium having stored therein instructions that, when executed by one or more processors, operatively enable a computing device to:

receive an indication of a device on a surface of a touch screen;

determine a location of the device on the surface of a touch screen;

detect a signal from the device; and

enhance the signal based, at least in part, on the determined location of the device and the detected signal from the device.

506 a computer-readable medium.

508 a recordable medium.

510 a communications medium.

FIG. 5






FIG. 6



## SIGNAL ENHANCEMENT

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation 35 U.S.C. §120 of U.S. patent application Ser. No. 13/700,078, filed on Nov. 26, 2012, entitled SIGNAL ENHANCEMENT, now U.S. Pat. No. 9,037,090, which is a U.S. national stage filing under 35 U.S.C. §371 of International Application No. PCT/US12/241756, filed on Feb. 7, 2012. The entire disclosures of these documents are incorporated by reference herein.

## BACKGROUND

Unless otherwise indicated herein, the approaches described in this section are not prior art to the claims in this application and are not admitted to be prior art by inclusion in this section.

Handheld devices such as, but not limited to, tablet computers, mobile phones, handheld gaming devices, etc. have increased data capacity. In order to facilitate sharing or accessing data on the handheld devices, methods of communication with handheld devices have become more important. Some examples may include near field communication, Bluetooth, Wi-Fi, and various other methods to facilitate wireless communication between electronic devices.

## SUMMARY

The present disclosure describes example methods, apparatus, and systems related to signal enhancement between electronic devices. Such an apparatus may include a touch screen, a number of wireless signal detectors located approximately around a perimeter of the touch screen, a machine readable non-transitory medium, and a processor. The processor may be communicatively coupled to the touch screen, the machine readable non-transitory medium, and the number of wireless signal detectors. The machine readable non-transitory medium may have stored therein instructions that, if executed by the processor, may operatively enable a computing device to receive an indication of a device on a surface of a touch screen. The computing device may determine a location of the device on the surface of the touch screen, and from the device, a signal may be detected. The signal may be enhanced based, at least in part, on the determined location and the detected signal.

The foregoing summary is illustrative only and is not intended to be in any way limiting. In addition to the illustrative aspects, embodiments, and features described above, further aspects, embodiments, and features will become apparent by reference to the drawings and the following detailed description.

## BRIEF DESCRIPTION OF THE DRAWINGS

Subject matter is particularly pointed out and distinctly claimed in the concluding portion of the specification. The foregoing and other features of the present disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only several embodiments in accordance with the disclosure and are, therefore, not to be considered limiting of its scope, the disclosure will be described with additional specificity and detail through use of the accompanying drawings.

In the drawings:

FIG. 1 illustrates an example apparatus that is arranged in accordance with at least some embodiments of the present disclosure;

5 FIG. 2 illustrates a plan view of another example apparatus that is arranged in accordance with various embodiments of the present disclosure;

FIG. 3 illustrates a block diagram of another example apparatus that is arranged in accordance with at least some embodiments of the present disclosure;

10 FIG. 4 illustrates an example process for enhancing a signal in accordance with at least some embodiments of the present disclosure;

FIG. 5 illustrates an example computer program product that is arranged in accordance with at least some examples of the present disclosure; and

15 FIG. 6 is a block diagram illustrating an example computing device, such as might be embodied by a person skilled in the art, which is arranged in accordance with at least some embodiments of the present disclosure.

## DETAILED DESCRIPTION

The following description sets forth various examples along with specific details to provide a thorough understanding of claimed subject matter. It will be understood by those skilled in the art, however, that claimed subject matter may be practiced without some or more of the specific details disclosed herein. Further, in some circumstances, well-known methods, procedures, systems, components and/or circuits have not been described in detail in order to avoid unnecessarily obscuring claimed subject matter.

25 In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the Figures, can be arranged, substituted, combined, and designed in a wide variety of different configurations, all of which are explicitly contemplated and make part of this disclosure.

This disclosure is drawn, inter alia, to methods, apparatus, and systems related signal enhancement.

As discussed above, examples of signal enhancement technology described herein may include utilizing a touch screen and locating a device on the touch screen. Signal from the device may be enhanced based, at least in part, on the location of the device on the touch screen.

55 FIG. 1 illustrates an example apparatus **100** that is arranged in accordance with at least some embodiments of the present disclosure. In the illustrated example, the apparatus **100** may include a touch screen **102** having a surface **104**. The touch screen **102** may also include a number of wireless signal detectors **108** located approximately around the perimeter of the touch screen **102**. Additionally, a device **110** is shown placed on the surface **104** of the touch screen **102**.

In the illustrated example of FIG. 1, a computing device communicatively coupled with the touch screen **102**, may receive an indication that the device **110** is on the surface **104**. A location of the device **110** on the surface **104** may then be determined. Additionally, a signal may be detected



from the device **110** by one or more wireless signal detectors **108**. The signal may then be enhanced, where the enhancement may be based, at least in part, on the location of the device **110** on the surface **104** of the touch screen **102** and the detected signal, in accordance with various embodiments of the disclosure. Additionally in some embodiments, detecting the signal may facilitate determining a direction of the signal from the device **110**.

In FIG. **1**, the touch screen **102** may be a wide variety of touch screens employing various technologies such as, but not limited to, resistive type touch screens or capacitive type touch screens. The surface **104** may be a wide variety of surfaces such as, but not limited to, transparent flexible surface, a rigid glass-type surface, and so forth, and accordingly, the claimed subject matter is not limited in these respects.

The device **110** may include a wide variety of devices capable of emitting some form of wireless signal such as, but not limited to, mobile phones, smart type mobile phones, personal digital assistants, tablet computers, and so forth.

In the embodiment illustrated in FIG. **1**, the wireless signal detectors **108** are shown located approximately around the perimeter of the touch screen **102**. The wireless signal detectors **108** may be a wide variety of detectors suitable for detecting wireless signals such as, but not limited to, detectors utilizing antenna and radios to facilitate scanning capabilities. Accordingly, the location of the detectors **108** may be any location on, in, and/or near the touch screen **102** and in a wide variety of patterns. Additionally, even though the number of detectors shown may be eight, it is contemplated within the scope of the claimed subject matter that the number of detectors may be any number.

As will be described in more detail, in FIG. **1**, signals from the device **110** may be enhanced in accordance with various embodiments of the present disclosure.

FIG. **2** illustrates a plan view of another example apparatus **200** that is arranged in accordance with various embodiments of the present disclosure. As shown in FIG. **2**, the apparatus **200** may include a touch screen **202** having a generally rectangular shape. The touch screen **202** may have a surface **204**, and on the surface **204**, there may be placed a device **210**. As illustrated, the device **210** may have a center point **212**. Additionally, a number of wireless signal detectors **220-227** (numbered clockwise and approximately equally spaced) may be located approximately around a perimeter of the touch screen **202**. In FIG. **2**, a representation of a wireless signal **230** being emitted by the device **210** may be shown.

In FIG. **2**, the touch screen **202** may receive an indication that the device **210** is on the surface **204**. The indication of the device **210** on the surface **204** may include an indication of distortion on the surface **204**, and from the indication of distortion on the surface **204**, an approximate size of the device **210** may be determined. Accordingly, in one embodiment, the location of the device **210** may be determined by determining a center point **212** of the device **210**.

As illustrated in FIG. **2**, the center point **212** of the device **210** may be located approximately towards a left side of the touch screen **202** closer to the wireless signal detectors **224**, **225**, and **226**. Accordingly, the wireless signal detectors **224**, **225**, and **226** may be capable of detecting the signal **230** from the device **210**. As will be described in detail further below, the signal **230** may be enhanced based, at least in part, on the location of the device **210** (e.g., the center point **212**) and the detected signal from the device **210** in accordance with various embodiments. Additionally, because it may be difficult to determine the position of the antenna

included in the device **210** for facilitating the emission of the signal **230**, the utilization of the number of wireless signal detectors **224**, **225**, and **226** along with the center point **212** may facilitate signal enhancement by reducing effects of position estimation errors.

With continued reference to FIG. **2**, the touch screen **202** may be shown as having a substantially rectangular shape, but it should be appreciated that the touch screen **202** may be a wide variety of touch screens having a variety of polygonal shapes or may be of a random shape. As previously described with reference to the surface **104**, the surface **204** may be of a wide variety of surfaces. As alluded to previously, the surface **204** may include one or more sensors capable of detecting an object on the surface **204**. The detection may include detecting a distortion on the surface **204** of the touch screen **202**. One or more such sensors may include sensors such as, but not limited to, a piezoelectric type sensor capable of detecting minute distortions (e.g., pressure) on a surface, an optical type sensors capable of detecting objects obscuring light (i.e., capable of determining an approximate size of an object by a shadow cast by the object on a surface), a sensor capable of detecting a change in a magnetic field of a surface, an optical image capturing sensor (e.g., image capturing sensor capable of object recognition), etc., and accordingly, the claimed subject matter is not limited in these respects. As may be appreciated, such sensors may be utilized to facilitate determination of the center point **212** of the device **210**.

The device **210** may be a wide variety of devices capable of emitting some form of wireless signal as previously described, and accordingly, the signal **230** may be a wide variety of wireless signals. The signal **230** may be a wireless signal such as, but not limited to, radio frequency identification (RFID) type signal, near field communication type signal, Infrared Data Association (IrDA) type signal, Bluetooth type signal, or a wide variety of personal area network (PAN) capable signals, and accordingly, is not limited in these respects.

FIG. **3** illustrates a block diagram of another example apparatus **300** that is arranged in accordance with at least some embodiments of the present disclosure. In the illustrated example, the apparatus **300** may include a touch screen **302**, a number of wireless signal detectors **304**, a transmit and receive (TX/RX) module **306**, a processor **308**, and a machine readable non-transitory medium **312**. The processor **308** may be communicatively coupled to the touch screen **302**, the number of wireless signal detectors **304**, the TX/RX module **306**, and the machine readable non-transitory medium **312** via a communication medium **310**.

In FIG. **3**, as will be described in more detail, the machine readable non-transitory medium **312** may have instructions that, when executed by processor **308**, operatively enable the apparatus **300** to receive an indication of a device (e.g., the device **110** in FIG. **1** or the device **210** in FIG. **2**) on a surface (e.g., the surface **104** in FIG. **1** or the surface **204** in FIG. **2**) of the touch screen **302**. The apparatus **300** may then determine a location of the device on the surface of the touch screen **302**. Additionally, the apparatus **300** may detect a signal (e.g., the signal **230** in FIG. **2**) via the TX/RX module **306** and determine a direction of the signal from the device. As will be describe in more detail, based, at least in part, on the determined location of the device and the detected signal from the device, the apparatus **300** may enhance the signal.

In FIG. **3**, the apparatus **300** may be configured to facilitate utilization of a wide variety of signal management techniques such as, but not limited to, multi-channel enhancement techniques, in accordance with various



## 5

embodiments. In one embodiment, the wireless signal detectors **304** may be configured for beamforming. For example, briefly referring back to FIG. **2**, the wireless signal detectors **224**, **225**, and **226** may be utilized as an array of detectors for detection of the signal **230**, and accordingly, the apparatus **300** may transmit wireless signals via the TX/RX module **306** by managing a directionality of the wireless signal detectors **224**, **225**, and **226** utilizing beamforming techniques. In one embodiment, the apparatus **300** may be configured to utilize independent component analysis techniques based, at least in part, on a location of a device and a detected signal from the device as previously described. These signal management techniques are but a few examples, and accordingly, the claimed subject matter is not limited in these respects.

In the embodiment illustrated in FIG. **3**, the apparatus **300** may be included in a wide variety of computing devices such as, but not limited to, a mobile device, a client device, a server type device, ubiquitous type computing environment (e.g., cloud type computing), and so forth, and accordingly, the claimed subject matter is not limited in these respects. For the purposes of describing the disclosed subject matter, the apparatus **300** may be included in a device having a touch screen such as, but not limited to, a table like device. It follows that the communication medium **310** may be a wide variety of communication mediums to facilitate communicative coupling of various components/modules such as, but not limited to, a bus type medium (i.e., physical) or WiFi type medium (i.e., wireless).

The processor **308** may represent one or more processors, which may include a wide variety of processors such as, but not limited to a computer, a microprocessor, a microcontroller, a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), a sequestered thread or a core of a multi-core/multi-threaded microprocessor or a combination thereof.

It should be appreciated by those skilled in the art, that in order to not obscure the disclosed subject matter and to facilitate understanding of the disclosed subject matter, the apparatus **300** (shown in FIG. **3**) and their respective components are illustrated as functional blocks. That is, it is contemplated that the apparatus **300** may be implemented in a wide variety of manners within the scope of the claimed subject matter without detracting the disclosed subject matter, and accordingly, the disclosed subject matter is not limited in these respects.

FIG. **4** illustrates another example of a process **400** for signal enhancement in accordance with at least some embodiments of the present disclosure. In the illustrated example, the process **400** may include one or more of functional operations as indicated by example operations **402**, **404**, **406**, and/or **410**.

As illustrated, the process **400** may be implemented for signal enhancement. Processing may begin at an operation **402**, "RECEIVE INDICATION OF DEVICE", where an indication of a device on a surface of a touch screen may be received.

The processing may continue from the operation **402** to an operation **404**, "DETERMINE LOCATION OF DEVICE", where a location of the device on the surface of the touch screen may be determined.

The processing may continue from the operation **404** to an operation **406**, "DETECT SIGNAL FROM DEVICE", where a signal from the device may be detected.

The processing may continue from the operation **406** to an operation **410**, "ENHANCE SIGNAL", where based, at

## 6

least in part, on the determined location of the device and the detected signal from the device, the signal may be enhanced.

As previously described, in some embodiments, a direction of the signal from the device may be determined.

It should be appreciated that the above described process **400** may be implemented in a wide variety of manners such as, but not limited to, the various embodiments of the present disclosure and variations thereof.

FIG. **5** illustrates an example of a computer program product **500** that is arranged in accordance with at least some examples of the present disclosure. The computer program product **500** may include a signal bearing medium **502**. The signal bearing medium **502** may include a machine readable non-transitory medium having stored therein instructions **504** that, if executed by one or more processors, may operatively enable a computing device to provide the functionality described above with respect to FIG. **4**. Thus, for example, the apparatus **300** (see, e.g., FIG. **3**) may undertake one or more of the actions shown in FIG. **4** in response to the execution of the instructions **504** conveyed by the signal bearing medium **502**.

In some implementations, the signal bearing medium **502** may encompass a non-transitory computer-readable medium **506**, such as, but not limited to, a hard disk drive, a Compact Disc (CD), a Digital Versatile Disk (DVD), a digital tape, memory, etc. In some implementations, the signal bearing medium **502** may encompass a recordable medium **508**, such as, but not limited to, memory, read/write (R/W) CDs, R/W DVDs, etc. In some implementations, the signal bearing medium **502** may encompass a communications medium **510**, such as, but not limited to, a digital and/or an analog communication medium (e.g., a fiber optic cable, a waveguide, a wired communications link, a wireless communication link, etc.).

FIG. **6** is a block diagram illustrating an example computing device **600**, such as might be embodied by a person skilled in the art, which is arranged in accordance with at least some embodiments of the present disclosure. In one example of a basic configuration **601**, the computing device **600** may include one or more processors **610** and a system memory **620**. A memory bus **630** may be used for communicating between the one or more processor **610** and the system memory **620**.

Depending on the desired configuration, the one or more processor **610** may be of any type including but not limited to a microprocessor ( $\mu$ P), a microcontroller ( $\mu$ C), a digital signal processor (DSP), or any combination thereof. The one or more processor **610** may include one or more levels of caching, such as a level one cache **611** and a level two cache **612**, a processor core **613**, and registers **614**. The processor core **613** may include an arithmetic logic unit (ALU), a floating point unit (FPU), a digital signal processing core (DSP Core), or any combination thereof. A memory controller **615** may also be used with the one or more processor **610**, or in some implementations the memory controller **615** may be an internal part of the one or more processor **610**.

Depending on the desired configuration, the system memory **620** may be of any type including but not limited to volatile memory (such as RAM), non-volatile memory (such as ROM, flash memory, etc.) or any combination thereof. The system memory **620** may include an operating system **621**, one or more applications **622**, and program data **624**. The one or more applications **622** may include a signal enhancement algorithm **623** that is arranged to perform the functions as described herein including the functional blocks and/or actions described with respect to the process **400** of FIG. **4**. The program data **624** may include signal enhance-



ment data 625 for use with the signal enhancement algorithm 623. In some example embodiments, the one or more applications 622 may be arranged to operate with program data 624 on the operating system 621 such that implementations of signal enhancement may be provided as described herein. For example, the apparatus 100 (see, e.g., FIG. 1) and/or the apparatus 300 (see, e.g., FIG. 3) may comprise all or a portion of the computing device 600 and may be capable of performing all or a portion of the one or more applications 622 such that implementations of signal enhancement may be provided as described herein. This described basic configuration 601 is illustrated in FIG. 6 by those components within dashed line.

The computing device 600 may have additional features or functionality, and additional interfaces to facilitate communications between the basic configuration 601 and any required devices and interfaces. For example, a bus/interface controller 640 may be used to facilitate communications between the basic configuration 601 and one or more data storage devices 650 via a storage interface bus 641. The one or more data storage devices 650 may be removable storage devices 651, non-removable storage devices 652, or a combination thereof. Examples of removable storage and non-removable storage devices include magnetic disk devices such as flexible disk drives and hard-disk drives (HDD), optical disk drives such as compact disk (CD) drives or digital versatile disk (DVD) drives, solid state drives (SSD), and tape drives to name a few. Example computer storage media may include volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data.

The system memory 620, the removable storage devices 651 and the non-removable storage devices 652 are all examples of computer storage media. The computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which may be used to store the desired information and which may be accessed by the computing device 600. Any such computer storage media may be a part of the computing device 600.

The computing device 600 may also include an interface bus 642 for facilitating communication from various interface devices (e.g., output interfaces, peripheral interfaces, and communication interfaces) with the basic configuration 601 via the bus/interface controller 640. Example output interfaces 660 may include a graphics processing unit 661 and an audio processing unit 662, which may be configured to communicate to various external devices such as a display or speakers via one or more A/V ports 663. Example peripheral interfaces 670 may include a serial interface controller 671 or a parallel interface controller 672, which may be configured to communicate with external devices such as input devices (e.g., keyboard, mouse, pen, voice input device, touch input device, etc.) or other peripheral devices (e.g., printer, scanner, etc.) via one or more I/O ports 673. An example communication interface 680 includes a network controller 681, which may be arranged to facilitate communications with one or more other computing devices 690 over a network communication via one or more communication ports 682. A communication connection is one example of a communication media. The communication media may typically be embodied by computer readable

instructions, data structures, program modules, or other data in a modulated data signal, such as a carrier wave or other transport mechanism, and may include any information delivery media. A “modulated data signal” may be a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media may include wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, radio frequency (RF), infrared (IR) and other wireless media. The term computer readable media as used herein may include both storage media and communication media.

The computing device 600 may be implemented as a portion of a small-form factor portable (or mobile) electronic device such as a cell phone, a personal data assistant (PDA), a personal media player device, a wireless web-watch device, a personal headset device, an application specific device, or a hybrid device that may include any of the above functions. The computing device 600 may also be implemented as a personal computer including both laptop computer and non-laptop computer configurations. In addition, the computing device 600 may be implemented as part of a wireless base station or other wireless system or device.

Some portions of the foregoing detailed description are presented in terms of algorithms or symbolic representations of operations on data bits or binary digital signals stored within a computing system memory, such as a computer memory. These algorithmic descriptions or representations are examples of techniques used by those of ordinary skill in the data processing arts to convey the substance of their work to others skilled in the art. An algorithm is here, and generally, is considered to be a self-consistent sequence of operations or similar processing leading to a desired result. In this context, operations or processing involve physical manipulation of physical quantities. Typically, although not necessarily, such quantities may take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared or otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to such signals as bits, data, values, elements, symbols, characters, terms, numbers, numerals or the like. It should be understood, however, that all of these and similar terms are to be associated with appropriate physical quantities and are merely convenient labels. Unless specifically stated otherwise, as apparent from the following discussion, it is appreciated that throughout this specification discussions utilizing terms such as “processing,” “computing,” “calculating,” “determining” or the like refer to actions or processes of a computing device, that manipulates or transforms data represented as physical electronic or magnetic quantities within memories, registers, or other information storage devices, transmission devices, or display devices of the computing device.

The claimed subject matter is not limited in scope to the particular implementations described herein. For example, some implementations may be in hardware, such as employed to operate on a device or combination of devices, for example, whereas other implementations may be in software and/or firmware. Likewise, although claimed subject matter is not limited in scope in this respect, some implementations may include one or more articles, such as a signal bearing medium, a storage medium and/or storage media. This storage media, such as CD-ROMs, computer disks, flash memory, or the like, for example, may have instructions stored thereon, that, when executed by a computing device, such as a computing system, computing platform, or other system, for example, may result in execu-



tion of a processor in accordance with the claimed subject matter, such as one of the implementations previously described, for example. As one possibility, a computing device may include one or more processing units or processors, one or more input/output devices, such as a display, a keyboard and/or a mouse, and one or more memories, such as static random access memory, dynamic random access memory, flash memory, and/or a hard drive.

There is little distinction left between hardware and software implementations of aspects of systems; the use of hardware or software is generally (but not always, in that in certain contexts the choice between hardware and software can become significant) a design choice representing cost vs. efficiency tradeoffs. There are various vehicles by which processes and/or systems and/or other technologies described herein can be affected (e.g., hardware, software, and/or firmware), and that the preferred vehicle will vary with the context in which the processes and/or systems and/or other technologies are deployed. For example, if an implementer determines that speed and accuracy are paramount, the implementer may opt for a mainly hardware and/or firmware vehicle; if flexibility is paramount, the implementer may opt for a mainly software implementation; or, yet again alternatively, the implementer may opt for some combination of hardware, software, and/or firmware.

The foregoing detailed description has set forth various embodiments of the devices and/or processes via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such block diagrams, flowcharts, or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. In one embodiment, several portions of the subject matter described herein may be implemented via Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), digital signal processors (DSPs), or other integrated formats. However, those skilled in the art will recognize that some aspects of the embodiments disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and/or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that the mechanisms of the subject matter described herein are capable of being distributed as a program product in a variety of forms, and that an illustrative embodiment of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution. Examples of a signal bearing medium include, but are not limited to, the following: a recordable type medium such as a flexible disk, a hard disk drive (HDD), a Compact Disc (CD), a Digital Versatile Disk (DVD), a digital tape, a computer memory, etc.; and a transmission type medium such as a digital and/or an analog communication medium (e.g., a fiber optic cable, a waveguide, a wired communications link, a wireless communication link, etc.).

Those skilled in the art will recognize that it is common within the art to describe devices and/or processes in the

fashion set forth herein, and thereafter use engineering practices to integrate such described devices and/or processes into data processing systems. That is, at least a portion of the devices and/or processes described herein can be integrated into a data processing system via a reasonable amount of experimentation. Those having skill in the art will recognize that a typical data processing system generally includes one or more of a system unit housing, a video display device, a memory such as volatile and non-volatile memory, processors such as microprocessors and digital signal processors, computational entities such as operating systems, drivers, graphical user interfaces, and applications programs, one or more interaction devices, such as a touch pad or screen, and/or control systems including feedback loops and control motors (e.g., feedback for sensing position and/or velocity; control motors for moving and/or adjusting components and/or quantities). A typical data processing system may be implemented utilizing any suitable commercially available components, such as those typically found in data computing/communication and/or network computing/communication systems.

The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely examples, and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected”, or “operably coupled”, to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable”, to each other to achieve the desired functionality. Specific examples of operably couplable include but are not limited to physically mateable and/or physically interacting components and/or wirelessly interactable and/or wirelessly interacting components and/or logically interacting and/or logically interactable components.

With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an”



limits any particular claim containing such introduced claim recitation to inventions containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

Reference in the specification to “an implementation,” “one implementation,” “some implementations,” or “other implementations” may mean that a particular feature, structure, or characteristic described in connection with one or more implementations may be included in at least some implementations, but not necessarily in all implementations. The various appearances of “an implementation,” “one implementation,” or “some implementations” in the preceding description are not necessarily all referring to the same implementations.

While certain example techniques have been described and shown herein using various methods and systems, it should be understood by those skilled in the art that various other modifications may be made, and equivalents may be substituted, without departing from claimed subject matter. Additionally, many modifications may be made to adapt a particular situation to the teachings of claimed subject matter without departing from the central concept described herein. Therefore, it is intended that claimed subject matter not be limited to the particular examples disclosed, but that such claimed subject matter also may include all implementations falling within the scope of the appended claims, and equivalents thereof.

The invention claimed is:

1. A method to enhance a signal comprising:

receiving a determined location of a device on a surface of a touch screen, wherein the location is determined based on detection of the device on the surface of the touch screen;

detecting a first signal and a direction of the first signal from the device with two or more wireless signal

detectors, wherein the two or more wireless signal detectors are located on or near the touch screen, and wherein the two or more wireless signal detectors are configured for beamforming; and

enhancing a second signal from the device with beamforming based, at least in part, on the location of the device and the detected first signal from the device.

2. The method of claim 1, wherein the touch screen in a resistive type touch screen or a capacitive type touch screen.

3. The method of claim 1, wherein the surface of the touch screen includes one or more sensors for detection of the device on the surface of the touch screen.

4. The method of claim 1, wherein the touch screen is part of a table like device.

5. The method of claim 1, wherein the device is a mobile phone or a tablet computer.

6. The method of claim 1, wherein the two or more wireless signal detectors are located approximately around the perimeter of the touch screen.

7. The method of claim 1, wherein the two or more wireless signal detectors include one or more antennas to facilitate scanning.

8. The method of claim 1, wherein the first signal or the second signal is a radio frequency identification (RFID) type signal, a near field communication type signal, an infrared data association (IrDA) type signal, a Bluetooth type signal, or a personal area network (PAN) type signal.

9. A machine readable non-transitory medium having stored therein instructions that, when executed by one or more processors, operatively enable a computing device to: receive a determined location of a device on a surface of a touch screen, wherein the location is determined based on detection of the device on the surface of the touch screen;

detect a first signal and a direction of the first signal from the device with two or more wireless signal detectors, wherein the two or more wireless signal detectors are located on or near the touch screen, and wherein the two or more wireless signal detectors are configured for beamforming; and

enhance a second signal from the device with beamforming based, at least in part, on the location of the device and the detected first signal from the device.

10. The machine readable non-transitory medium of claim 9, wherein the touch screen in a resistive type touch screen or a capacitive type touch screen.

11. The machine readable non-transitory medium of claim 9, wherein the surface of the touch screen includes one or more sensors for detection of the device on the surface of the touch screen.

12. The machine readable non-transitory medium of claim 9, wherein the touch screen is part of a table like device.

13. The machine readable non-transitory medium of claim 9, wherein the device is a mobile phone or a tablet computer.

14. The machine readable non-transitory medium of claim 9, wherein the two or more wireless signal detectors are located approximately around the perimeter of the touch screen.

15. The machine readable non-transitory medium of claim 9, wherein the two or more wireless signal detectors include one or more antennas to facilitate scanning.

16. The machine readable non-transitory medium of claim 9, wherein the first signal or the second signal is a radio frequency identification (RFID) type signal, a near field communication type signal, an infrared data association (IrDA) type signal, a Bluetooth type signal, or a personal area network (PAN) type signal.



## 13

17. A system comprising:  
 a touch screen having a surface;  
 a plurality of wireless signal detectors located approxi-  
 mately around a perimeter of the touch screen; and  
 a processor communicatively coupled to the touch screen 5  
 and the plurality of wireless signal detectors, the pro-  
 cessor being configured to:  
 receive a determined location of a device on a surface  
 of a touch screen, wherein the location is determined 10  
 based on detection of the device on the surface of the  
 touch screen;  
 detect a first signal and a direction of the first signal  
 from the device with two or more wireless signal  
 detectors, wherein the two or more wireless signal 15  
 detectors are located on or near the touch screen, and  
 wherein the two or more wireless signal detectors are  
 configured for beamforming; and  
 enhance a second signal from the device with beam-  
 forming based, at least in part, on the location of the 20  
 device and the detected first signal from the device.
18. The system of claim 17, wherein the touch screen in  
 a resistive type touch screen or a capacitive type touch  
 screen.
19. The system of claim 17, wherein the surface of the 25  
 touch screen includes one or more sensors for detection of  
 the device on the surface of the touch screen.
20. The system of claim 17, wherein the touch screen is  
 part of a table like device.

## 14

21. The system of claim 17, wherein the device is a  
 mobile phone or a tablet computer.
22. The system of claim 17, wherein the two or more  
 wireless signal detectors are located approximately around  
 the perimeter of the touch screen.
23. system of claim 17, wherein the two or more wireless  
 signal detectors include one or more antennas to facilitate  
 scanning.
24. The system of claim 17, wherein the first signal or the  
 second signal is a radio frequency identification (RFID) type  
 signal, a near field communication type signal, an infrared  
 data association (IrDA) type signal, a Bluetooth type signal,  
 or a personal area network (PAN) type signal.
25. A method to enhance a signal comprising:  
 receiving a determined location of a device on a surface  
 of a touch screen, wherein the location is determined  
 based on detection of the device on the surface of the  
 touch screen;  
 detecting a first signal and a direction of the first signal  
 from the device with two or more wireless signal  
 detectors, wherein the two or more wireless signal  
 detectors are located on or near the touch screen, and  
 wherein the two or more wireless signal detectors are  
 configured for independent component analysis; and  
 enhancing a second signal from the device with indepen-  
 dent component analysis based, at least in part, on the  
 location of the device and the detected first signal from  
 the device.

\* \* \* \* \*