



US 20160083121A1

(19) **United States**

(12) **Patent Application Publication**
MALONE

(10) **Pub. No.: US 2016/0083121 A1**

(43) **Pub. Date: Mar. 24, 2016**

(54) **SYSTEM AND METHOD FOR FILLING CONTAINERS WITH FLUIDS**

Publication Classification

(71) Applicant: **TINNUS ENTERPRISES, LLC,**
PLANO, TX (US)

(51) **Int. Cl.**
B65B 3/04 (2006.01)
A61J 1/10 (2006.01)
B65B 3/26 (2006.01)

(72) Inventor: **JOSHUA MALONE,** PLANO, TX (US)

(52) **U.S. Cl.**
CPC ... *B65B 3/04* (2013.01); *B65B 3/26* (2013.01);
A61J 1/10 (2013.01)

(21) Appl. No.: **14/678,878**


(57) **ABSTRACT**


(22) Filed: **Apr. 3, 2015**

An example embodiment of an apparatus includes a housing with an opening at a first end and a plurality of holes at a second end, a plurality of hollow tubes attached to the plurality of holes, a plurality of containers removably attached to the hollow tubes, and a plurality of elastic fasteners, each elastic fastener clamping each container to a corresponding hollow tube, such that when the containers are filled with fluid and detached from the corresponding hollow tubes, each elastic fastener seals each container with the fluid inside.

Related U.S. Application Data

(63) Continuation of application No. 14/492,487, filed on Sep. 22, 2014, now Pat. No. 9,051,066.










FIG. 2






FIG. 5




FIG. 6




FIG. 7




FIG. 8

SYSTEM AND METHOD FOR FILLING CONTAINERS WITH FLUIDS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of priority under 35 U.S.C. §119(e) to U.S. Provisional Application Ser. No. 61/937,083 entitled “SYSTEM AND METHOD FOR FILLING INFLATABLE CONTAINERS WITH LIQUID” filed Feb. 7, 2014 and to U.S. Provisional Application Ser. No. 61/942,193 entitled “SYSTEM AND METHOD FOR FILLING INFLATABLE CONTAINERS WITH FLUIDS” filed Feb. 20, 2014, which are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

[0002] The present disclosure relates generally to fluid inflatable systems and more particularly, to a system and method for filling containers with fluids.

BACKGROUND

[0003] Inflatable containers such as balloons can be filled with a variety of fluids, such as air, helium, water, medicines, etc. In some cases, a lot of inflatable containers may need to be filled with fluids. For example, balloons used as props in conventions, large parties, etc. may number in the hundreds and may require substantial human effort to fill them all in a timely manner. In another example, water balloons used as kids’ toys may need to be filled in large numbers to aid in various games. Various methods may be employed to fill such inflatable containers. For example, an individual may blow up and tie each balloon by hand or use a tank of compressed air or helium to inflate the balloon, which then has to be tied. In another example, an individual may fill water balloons with water by hand one at a time, and then tie the balloons, which can all be quite time-consuming. Moreover, the inflatable containers may be damaged or filled to different volumes.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] To provide a more complete understanding of the present disclosure and features and advantages thereof, reference is made to the following description, taken in conjunction with the accompanying figures, wherein like reference numerals represent like parts, in which:

[0005] FIG. 1 is a simplified perspective view illustrating an example configuration of an embodiment of a system for filling containers with fluids;

[0006] FIG. 2 is a simplified diagram illustrating a cross-sectional view of example details of an embodiment of the system;

[0007] FIG. 3 is a simplified diagram illustrating other example details of an embodiment of the system;

[0008] FIG. 4 is a simplified diagram illustrating yet other example details of an embodiment of the system;

[0009] FIG. 5 is a simplified diagram illustrating yet other example details of an embodiment of the system;

[0010] FIG. 6 is a simplified diagram illustrating yet other example details of an embodiment of the system;

[0011] FIG. 7 is a simplified diagram illustrating yet other example details of an embodiment of the system; and

[0012] FIG. 8 is a simplified flow diagram illustrating example operations that may be associated with an embodiment of the system.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS OVERVIEW

[0013] An example embodiment of an apparatus includes a housing (e.g., casing, covering, etc. with a cavity inside) with an opening at a first end and a plurality of holes at a second end, a plurality of hollow tubes attached to the plurality of holes, a plurality of containers (e.g., receptacles, vessels, ampules, test-tubes, balloons, etc.) removably attached to the hollow tubes, and a plurality of elastic fasteners, each elastic fastener clamping each container to a corresponding hollow tube, such that when the containers are filled with fluid and detached from the corresponding hollow tubes, each elastic fastener seals each container with the fluid inside.

Example Embodiments

[0014] It is to be understood that the following disclosure describes several example embodiments for implementing different features, structures, or functions of the system. Example embodiments of components, arrangements, and configurations are described herein to simplify the present disclosure. However, these example embodiments are provided merely as examples and are not intended to limit the scope of the invention.

[0015] The present disclosure may repeat reference numerals and/or letters in the various exemplary embodiments and across the Figures provided herein. This repetition is for the purpose of simplicity and clarity and does not in itself indicate a relationship between the various exemplary embodiments and/or configurations discussed in the various Figures.

[0016] FIG. 1 is a simplified diagram illustrating an example embodiment of a system **10** for filling containers with fluids. System **10** includes a housing **12** removably attached to a hose **14** (e.g., tube, pipe, etc.) on a first end A and to a plurality of hollow tubes **16** on a second end B. As used herein, the term “housing” encompasses a hollow space enclosed by a rigid or semi-rigid casing (e.g., covering, skin, sleeve, sheath, etc.). In some embodiments, end A may include a threaded opening configured to mate with corresponding threads on hose **14**. In some embodiments, end A may be smaller in circumference or area than end B. Hose **14** may be connected to a fluid source, such as a water tank, gas tank, water supply line, etc. on end A. End B may include a plurality of holes (e.g., configured in an array), configured to fit tubes **16**. In some embodiments, tubes **16** may be permanently attached (e.g., welded, brazed, stuck with adhesives, press-fitted, etc.) to housing **12**. In other embodiments, tubes **16** may be removably attached (e.g., with threads, pressure, etc.) to housing **12**.

[0017] A plurality of containers **18** may be clamped (e.g., attached, fastened, held, clinched, secured, etc.) to plurality of tubes **16** using elastic valves **20**. As used herein, the term “container” refers to an object that can hold something, such as fluids. The term “valve” refers to an object that regulates, directs, or controls the flow of fluids, by opening, closing, or partially obstructing passageways of fluid flow. In an example embodiment, elastic valves **20** comprise elastic fasteners, such as O-rings. In another example embodiment, elastic valves **20** comprise corrugations, smocking, elastic fibers, etc. fabricated into the necks of containers **18** such that force is required to pull open the necks of containers **18**, and removal of the force causes the necks to constrict and close. In yet another example embodiment, elastic valves comprise

internal or external plugs affixed to the necks of containers **18**, through which tubes **16** may be pushed through to clamp containers **18** thereto.

[0018] Note that each of containers **18** have an opening to facilitate clamping to tubes **16** and a cavity for containing fluid. For example, one end of an example tube **16A** may be fitted through a hole in end B of housing **12**, and the other end of tube **16A** may be inserted into an example container **18A**. An example elastic valve **20A** (e.g., O-ring, comprising a mechanical gasket typically in a toroid shape; elastic ring, such as a rubber-band) of sufficient size to expand and clamp around tube **16A** may be disposed around (e.g., placed over) a neck (e.g., portion just below opening) of container **18A**, clamping and sealing container **18A** to tube **16A**. Thus, elastic valve **20A** may be in an open configuration when container **18A** is attached to tube **16A**; in elastic valve **20A**'s open configuration, the neck of container **18A** is open, allowing container **18A** to fill with fluid. After container **18A** is filled with fluid, it may be removed from tube **16A**, whereupon elastic valve **20A** closes, thereby closing the neck of container **18A** and sealing the fluid inside.

[0019] In one example embodiment, containers **18** may comprise inflatable balloons that may be filled with fluids such as water, air or helium. In another example embodiment, containers **18** may comprise flexible (e.g., stretchy, springy, etc.) elastic containers that may be filled with gaseous or liquid medications. As used herein, the term "elastic" is meant to refer to a property of a material that allows the material to resume its normal shape spontaneously after contraction, dilation, or distortion. In an example, an elastic material may be stretched to 200% of its original length, and the material may return to its original length when the stretching force is removed.

[0020] In yet another example embodiment, containers **18** may comprise flexible containers that may be filled with body fluids (e.g., urine, blood) for example, to collect multiple samples simultaneously for testing. Virtually any type and kind of fluid may be used within the broad scope of the embodiments. Note that in some embodiments, containers **18** need not be inflatable or flexible in their entireties. For example, a bottom portion of containers **18** may be inelastic (e.g., glass, plastic, metal, etc., of fixed shape and size), and a top portion may be flexible enough to be inserted around tubes **16** and clamped thereon.

[0021] When the fluid source is turned on, fluid may flow through housing **12**, tubes **16** and fill containers **18**. In some embodiments, when housing **12** is connected to a stream of liquid, containers **18** may be filled with the liquid. In some embodiments, the fluid may be supplied at high pressure. Virtually any mechanism that facilitates fluid flow through tubes **16** at sufficient pressure to fill containers **18** may be used within the broad scope of the embodiments. After containers **18** have reached a desired size or volume, they may be detached from tubes **16**. In one example embodiment, filled containers **18** may be detached by pulling them away from tubes **16**.

[0022] In another example embodiment, the connecting force holding filled containers **18** to tubes **16** may be overcome by an upward acceleration on tubes **16**, for example, when they are shaken. Thus, filled containers **18** may be detached by shaking housing **12** (or tubes **16**) sufficiently vigorously to cause containers **18** to fall off from tubes **16**. In some embodiments, the connecting force holding filled container to its corresponding tube is not less than the weight of

the filled container; in a specific embodiment, the connecting force holding each container to its corresponding tube is exactly equal to the weight of the filled container. The connecting force may be provided by a combination of constricting forces and friction forces from elastic valves **20**.

[0023] In yet other embodiments, containers **18** may fall off under gravity; for example, when filled containers **18** reach a threshold weight, they slip off tubes **16** due to gravity. The threshold weight may be based upon the tightness of elastic valves **20**, friction between tubes **16** and containers **18**, and force from the weight of containers **18** (among other parameters). In various embodiments, containers **14** may slide off tubes **16** and elastic valves **20** may constrict the necks of containers **18**, sealing them. In some embodiments, containers **18** may be marked with volumetric measurements, and fluid flow may be turned off when the fluid has filled containers **18** to a desired volume.

[0024] In some embodiments, hollow tubes **16** may be made of a rigid material (e.g., steel, glass); in other embodiments, tubes **16** may be made of a flexible material (e.g., thin plastic). In some embodiments, tubes **16** may be thick, short and rigid; in other embodiments, tubes **16** may be slender, long and flexible. Thus, hollow tubes **16** may be flexible, semi-rigid, or rigid, based on its material of construction, design, or a combination thereof. Note that tubes **16** may be of different lengths, for example, to prevent crowding and to accommodate a larger number of containers **18** than would be possible if tubes **16** were of the same length. Thus, at least some of hollow tubes **16** may be of different lengths than the others.

[0025] Also, tubes **16** may be flexible to enable containers **18** to expand. Thus, as containers **18** fill with fluid and expand, they may push against each other, flexing tubes **16**. The outermost tubes **16** may be flexed more than the innermost tubes **16** (outer and inner being in reference to a center-point of housing **12**, with the inner tubes **16** being closer to the center-point, and the outer tubes **16** being farther from the center-point).

[0026] Turning to FIG. 2, FIG. 2 is a simplified cross-sectional view of a portion of an embodiment of system **10**. Housing **12** comprises a threaded opening **22** at end A, an internal cavity **24**, and an array of holes **26** at end B. Internal cavity **24** facilitates distributing the fluid entering at threaded opening **22** to array of holes **26** at end B. In some embodiments, threaded opening **22** may be configured for attaching to a fluid supply hose **14** (e.g., garden hose, plastic tube, etc.). In other embodiments, threaded opening **22** may be attached to corresponding threads in a valve. Array of holes **26** may be configured for connecting first ends **28** of tubes **16** by any suitable means. In some embodiments, first ends **28** of tubes **16** may be connected to corresponding holes **26** by compressing or gluing. In some embodiments, a number of holes **26** in housing **12** and a number of tubes **16** can correspond to a number of containers **18** that are desired to be filled and sealed substantially simultaneously.

[0027] To clarify further, only one example tube **16A** is shown in the figure. A first end **28A** of tube **16A** is fitted through a corresponding hole **26A** in housing **12**. A second end **29A** of tube **16A** is inserted into container **18A**. Elastic valve **20A** may be placed around the neck of container **18A** clamping the neck to tube **16A**. An internal volume **30A** of container **18A** may be filled with fluid appropriately.

[0028] To fill and seal containers **18**, housing **12** may be attached to a fluid supply tube (e.g., garden hose) and the fluid

supply may be turned on. The fluid enters housing 12, is distributed to holes 26, travels down tubes 16, and fills containers 18. Containers 18 may be filled and may expand substantially simultaneously. When containers 18 have reached a desired size and/or they are filled with the desired volume of fluid, they may be removed from tubes 16. They can be removed by falling off, by shaking them off, by pulling them off by hand, etc. As each container 18A is removed from corresponding tube 16A, respective elastic valve 20A may constrict and close the neck of container 18A, sealing it with the fluid inside.

[0029] Turning to FIG. 3, FIG. 3 is a simplified diagram illustrating example details of a valve 31 that may be attached between hose 14 and housing 12 according to an embodiment of system 10. One end of valve 31 may be attached to hose 14 and the other end may be attached to threaded opening 22 of housing 12 (e.g., using threads). A lever 32 may be turned from one side (of valve 31) to another (e.g., as indicated by arrow C) to turn on and turn off fluid flow to housing 12. For example, to turn on the fluid flow, lever 32 may be turned to a first position; lever 32 may be turned to a second position (e.g., different from the first position) to turn off fluid flow.

[0030] Turning to FIG. 4, FIG. 4 is a simplified diagram illustrating example details of an embodiment of system 10. Housing 12 may be attached to a spigot 33 (e.g., nozzle, faucet, outlet, etc.) that connects to the fluid source. Spigot 33 may be turned on or turned off to start or stop fluid flow to housing 12.

[0031] Turning to FIG. 5, FIG. 5 is a simplified diagram illustrating example details of an application of an embodiment of system 10. Embodiments of system 10 may be used in a variety of applications, such as for collecting numerous blood samples substantially simultaneously. Blood 34 may be drawn from a human (or animal) and blood 34 may collect substantially simultaneously in plurality of containers 18. The substantial simultaneous collection of blood in such manner can ease patient pain, speed up sampling time, and enable taking multiple samples substantially simultaneously without cross-contamination from one container to another or messy transfers between containers.

[0032] Turning to FIG. 6, FIG. 6 is a simplified diagram illustrating example details of an application of an embodiment of system 10. Embodiments of system 10 may be used in a variety of applications, such as for collecting numerous urine samples substantially simultaneously. Urine 36 may be drawn from a human (or animal) through a suitable catheter 38, and may collect substantially simultaneously in plurality of containers 18.

[0033] Turning to FIG. 7, FIG. 7 is a simplified diagram illustrating example details of an embodiment of system 10. Example container 18A may comprise a flexible portion 40 and an inflexible portion 42. Flexible portion 40 may be clamped on to example tube 16A using example elastic valve 20A. In some embodiments, container 18A may comprise volumetric measurement markings 44. When fluid fills container 18A to a desired volume, for example, as indicated by volumetric measurement marking 44, container 18A may be detached from tube 16A, whereupon elastic valve 20A may close container 18A, sealing the fluid inside.

[0034] Turning to FIG. 8, FIG. 8 is a simplified flow diagram 50 illustrating example operations that may be associated with an embodiment of system 10. At 52, housing 12 may be attached to a fluid source (e.g., through hose 14, spigot 33, etc.) At 54, fluid may be supplied from the fluid source to

housing 12. At 56, plurality of containers 18 may be filled with the fluid. At 58, containers 18 may be detached from corresponding tubes 16.

[0035] Note that in this Specification, references to various features (e.g., elements, structures, modules, components, steps, operations, characteristics, etc.) included in “one embodiment”, “example embodiment”, “an embodiment”, “another embodiment”, “some embodiments”, “various embodiments”, “other embodiments”, “alternative embodiment”, and the like are intended to mean that any such features are included in one or more embodiments of the present disclosure, but may or may not necessarily be combined in the same embodiments.

[0036] The elements described herein may be made of any suitable materials, including metal (e.g., stainless steel, copper, brass, bronze, aluminum, etc.), plastic, glass, elastomers, or any suitable combination thereof. Each element may also be made of a combination of different materials (e.g., housing and tubes may be made of plastic and containers may be made of elastic rubber; housing and tubes may be made of stainless steel and containers may be made of a combination of glass and flexible plastic; etc.). Any suitable material or combination of materials may be used for the components described herein without departing from the broad scope of the present disclosure.

[0037] In addition, the shapes shown and illustrated in the various FIGURES are for example purposes only. Various other shapes may be used herein without changing the scope of the present disclosure. For example, housing 12 may be conical, cylindrical, pyramidal, etc., without departing from the broad scope of the embodiments. Likewise, tubes 16 may be rigid, or flexible 18 without departing from the scope of the broad embodiments.

[0038] While the disclosure references several particular embodiments, those skilled in the art will be able to make various modifications to the described embodiments without departing from the true spirit and scope of the disclosure. It is intended that all elements or steps which are insubstantially different from those recited in the claims but perform substantially the same functions, respectively, in substantially the same way to achieve the same result as what is claimed are within the scope of the disclosure.

1-28. (canceled)

29. An apparatus comprising:

- a housing comprising a plurality of holes extending through the housing;
- a plurality of hollow tubes, each hollow tube attached to the housing at a respective one of the holes;
- a plurality of containers, each container removably attached to a respective one of the hollow tubes; and
- a plurality of elastic fasteners, each elastic fastener clamping a respective one of the plurality of containers to a respective tube, and each elastic fastener configured to restrict detachment of its respective container from its respective tube and to automatically seal its respective container upon detachment of the container from its respective tube, the restriction of each elastic fastener being sufficiently limited to permit its respective container to detach from its respective tube upon one or more of (1) at least partially filling the container with fluid and (2) shaking the housing;

wherein the apparatus is configured to fill the containers substantially simultaneously with fluid.

30. The apparatus of claim **31**, wherein the apparatus is sufficiently compact to be operated while being held by hand of a single operator.

31. The apparatus of claim **31**, wherein at least first and second ones of the plurality of containers are disposed sufficiently close to each other such that they press against each other, regardless whether the first and second ones of the plurality of containers are in a filled state or an unfilled state.

32. The apparatus of claim **31**, wherein each container is a water balloon.

* * * * *