



US006651780B1

(12) **United States Patent**
Hakala et al.

(10) **Patent No.:** **US 6,651,780 B1**
(45) **Date of Patent:** ***Nov. 25, 2003**

(54) **TRACTION SHEAVE ELEVATOR, HOISTING UNIT AND MACHINE SPACE**

(75) Inventors: **Harri Hakala**, Hyvinkää (FI); **Jorma Mustalahti**, Hyvinkää (FI); **Esko Aulanko**, Kerava (FI)

(73) Assignee: **Kone Oy**, Helsinki (FI)

(*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/333,678**

(22) Filed: **Jun. 16, 1999**

Related U.S. Application Data

(63) Continuation of application No. 08/896,531, filed on Jul. 18, 1997, now Pat. No. 6,148,962, which is a continuation of application No. 08/433,077, filed on May 3, 1995, now abandoned, which is a continuation-in-part of application No. 08/264,343, filed on Jun. 23, 1994, now Pat. No. 5,429,211.

(30) **Foreign Application Priority Data**

Jun. 28, 1993 (FI) 932977
Apr. 14, 1994 (FI) 941719
May 4, 1994 (FI) 942062

(51) **Int. Cl.**⁷ **B66B 11/08**

(52) **U.S. Cl.** **187/254**

(58) **Field of Search** 187/254, 266,
187/333, 325, 406

(56) **References Cited**

U.S. PATENT DOCUMENTS

12,640 A 4/1855 Murtaugh

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

CA A12127873 7/1993
CH 436629 11/1967

(List continued on next page.)

OTHER PUBLICATIONS

Title—Elevator Machinery; inventors: Ing. Fuller and Ing. Knorzler dated Sep. 16, 1954, 15 pages.

“PC Brushless Motor and Control Circuit” Table of Contents and pp. 42, 43 and 204; Nov. 01, 1994.


Primary Examiner—Khoi H. Tran

(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

Traction sheave elevator consisting of an elevator car moving along elevator guide rails, a counterweight moving along counterweight guide rails, a set of hoisting ropes (3) on which the elevator car and counterweight are suspended, and a drive machine unit (6) driving a traction sheave (7) acting on the hoisting ropes (3) and placed in the elevator shaft. The drive machine unit (6) is of a flat construction. A wall of the elevator shaft is provided with a machine space with its open side facing towards the shaft, the essential parts of the drive machine unit (6) being placed in the space. The hoisting unit (9) of the traction sheave elevator consists of a substantially discoidal drive machine unit (6) and an instrument panel (8) mounted on the frame (20) of the hoisting unit.

118 Claims, 3 Drawing Sheets



US 6,651,780 B1

Page 2

U.S. PATENT DOCUMENTS

568,567 A 9/1896 Herdman
789,765 A 5/1905 Smith
799,337 A 9/1905 De Buren
1,126,260 A 1/1915 Neenan
1,566,385 A 12/1925 Dunn
3,101,130 A 8/1963 Bianca
4,085,823 A 4/1978 Caputo et al.
4,739,969 A 4/1988 Eckersley et al.
H702 H 11/1989 Shively et al.
4,960,186 A 10/1990 Honda
4,977,980 A 12/1990 Hifumi
5,018,603 A 5/1991 Ito
5,036,954 A 8/1991 Haahtikivi et al.
5,140,212 A 8/1992 Iwasaki et al.
5,144,183 A 9/1992 Farrenkopf
5,152,369 A 10/1992 Nakaoka
5,299,662 A 4/1994 Reddy et al.
5,589,722 A 12/1996 Sakaguchi et al.
6,148,962 A * 11/2000 Hakala et al. 187/254

FOREIGN PATENT DOCUMENTS

DE U 7395 9/1954
DE 1033383 7/1958
DE 3802386 A1 8/1988
DE 3922798 C1 9/1990
EP 415218 3/1991
EP 0631967 1/1995

GB 2201657 9/1988
GB 2201657 9/1998
JP 51-20351 2/1976
JP 51-139044 12/1976
JP 52-32870 3/1977
JP 55-7149 1/1980
JP 58184480 10/1983
JP 59-40276 3/1984
JP 61-150982 7/1986
JP 62-230587 10/1987
JP 63-56170 3/1988
JP 4-50297 8/1988
JP 64-211180 1/1989
JP 1-187187 7/1989
JP 1-267286 10/1989
JP 1-30467 12/1989
JP 2-62394 3/1990
JP 2-225280 9/1990
JP 3-124688 5/1991
JP 4-50297 2/1992
JP 5-78066 3/1993
JP 7-137962 5/1995
JP 7-144857 6/1995
NL 154553 12/1902
WO WO93/14551 7/1993
WO WO 9528028 10/1995

* cited by examiner




Fig. 1




Fig. 3




Fig. 2




Fig. 4

TRACTION SHEAVE ELEVATOR, HOISTING UNIT AND MACHINE SPACE

This application is a continuation of application Ser. No. 08/896,531, filed on Jul. 18, 1997, now U.S. Pat. No. 6,148,962, which is a continuation of 08/433,077, filed May 3, 1995, now abandoned; which is a continuation-in-part of 08/264,343, filed Jun. 23, 1994, now U.S. Pat. No. 5,429,211; the entire contents of all of which are hereby incorporated by reference.

The present invention relates to a traction sheave elevator a hoisting unit and a machine space as described hereinbelow.

BACKGROUND OF THE INVENTION

One of the objectives in elevator development has been to achieve an efficient and economic space utilization. In conventional traction sheave driven elevators, the elevator machine room or other space for the drive machinery takes up a considerable part of the building space required for the elevator. The problem is not only the volume of the space required by the elevator, but also its placement in the building. There are various solutions for the placement of the machine room, but they generally involve significant restrictions as to the design of the building at least with regard to space utilization or appearance. For example, in the case of a so-called side-drive elevator with machine room below, a machine room or space is required below or beside the shaft, generally on the bottommost floor of the elevator system. Being a special space, the machine room generally increases the building costs.

SUMMARY OF THE INVENTION

To meet the need to achieve at an economic cost a reliable elevator allowing efficient space utilization and in which, irrespective of the hoisting height, the building space required for the elevator is substantially limited to the space needed by the elevator car and counterweight on their paths, including the safety distances, and the space needed to provide a passage for the hoisting ropes, and in which the problems or drawbacks described above can be avoided, a new type of traction sheave elevator is proposed as an invention. The traction sheave elevator of the invention is characterized by an elevator car moving along elevator guide rails, a counterweight moving along counterweight guide rails, a set of hoisting ropes on which the elevator car and counterweight are suspended in the elevator shaft, and a drive machine unit driving a traction sheave placed in the elevator shaft and acting on the hoisting ropes, the drive machine unit being flat in the direction of the drive shaft of the traction sheave, and a wall of the elevator shaft containing a machine space in which the essential parts of the drive machine unit are placed. The hoisting unit of the invention is characterized by the hoisting unit comprising a discoidal drive machine unit and an instrument panel attached to a frame of the hoisting unit. The machine space of the invention is characterized by the machine space being delimited in the thicknesswise direction of a wall by the plane of the wall surface facing towards an elevator shaft and the plane of the wall surface facing towards from the elevator shaft. Other embodiments of the invention are characterized by the features presented in the other claims.

Various advantages can be achieved by applying the invention, including the following:

The traction sheave elevator of the invention allows an obvious space saving to be achieved in the building because no separate machine room is required.

The elevator is cheap to install as the elevator machinery can be assembled and tested beforehand in factory.

Applying the invention to practice requires no major changes in the design or manufacture of the elevator.

The machinery and the instrument panel are within easy reach, so the manner of accessing the machinery for maintenance or in an emergency does not essentially differ from conventional elevators.

BRIEF DESCRIPTION OF THE DRAWINGS

In the following, the invention is described in detail by the aid of one of its embodiments by referring to the attached drawings, in which

FIG. 1 presents a diagrammatic view of a hoisting unit employed in the invention,

FIG. 2 presents an elevator with machinery below in which the invention is applied,

FIG. 3 presents the layout of the main components of an elevator applying the invention, projected on the cross-section of the elevator shaft, and

FIG. 4 presents an elevator with machinery above, implemented according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 presents a hoisting unit 9 for a traction sheave elevator as provided by the invention. The unit in this figure is the hoisting unit of a traction sheave elevator with machinery below, in which the hoisting ropes 3 go upwards from the traction sheave 7 of the hoisting machinery 6. In the case of an elevator with machinery above, the ropes would go downwards. The hoisting machinery 6 is fixed to the support 20 of the hoisting unit, which 20 is preferably of a frame-like design. Mounted on the frame 20 is also an instrument panel 8, which contains the elevator control equipment and the equipment needed for the control of and supply of power to the electromotor comprised in the hoisting machinery 6. The hoisting machinery 6 is of a discoidal shape and, in relation to its diameter, relatively flat in the direction of the traction sheave shaft. The traction sheave 7 protrudes from the discoidal hoisting machinery 6 into the shaft space. Placed on the circumference of the hoisting machinery 6 is a brake 14. An elevator machinery usable as a hoisting machinery 6 is described e.g. in Finnish patent application 941599. Such a machinery does not require a large machine space, so it can easily be placed in an opening in the wall or in a recess made in the wall on the side facing towards the shaft. A preferable thickness of the hoisting unit 9 is about or somewhat over ten centimeters. The traction sheave 7 is not included in this thickness. A 10 cm thick hoisting unit 9 can readily be accommodated in an ordinary elevator shaft wall because a typical wall thickness is at least about 15 cm, both in the case of a cast concrete wall and a brick wall.

FIG. 2 presents an elevator with machinery below in which the invention is applied, the hoisting unit 9 being placed beside the shaft in its lower part. The main parts of the elevator machinery 6 are mounted in a space limited in its maximum by the thickness of the wall of the elevator shaft 17, in an opening 15 in the wall which is open towards the shaft space and closed with a door 16 from the outside to prevent illicit access to the machinery or entry into the shaft through the opening 15. On the shaft side, the opening may be provided with a safety net or glass or the like to make sure that one cannot e.g. stretch a hand into the shaft space

past the equipment in the opening. In general, it is not sensible to close the machine space **15** completely from the shaft side because, regarding ventilation of the machine space **15**, an advantageous solution is one in which the machine space is ventilated through the shaft. In some cases, however, closing the machine space on the shaft side may be necessary e.g. to stop the propagation of noise. In such cases the machine space **15** is closed on the shaft side except for the inlets required for power transmission to the traction sheave **7** and other purposes. In any case, the machine space **15** has a depth not exceeding the thickness of the wall of the elevator shaft **17**. From the hoisting machinery **6** comprised in the hoisting unit, the traction sheave **7** moving the hoisting ropes **3** (depicted in broken lines) protrudes into the shaft **17**. The figure shows the portion of the hoisting ropes passing below the car **1** over diverting pulleys **4,5** and the portion coming down from the upper part of the shaft **17** to the traction sheave.

FIG. **3** presents the layout of the main components of an elevator with machinery below, projected on the cross-section of the elevator shaft **17**. The elevator car **1** moves along elevator guide rails **10** and the counterweight **2** along counterweight guide rails **11**. The hoisting machinery **6** and the instrument panel **8** are placed in an opening in the wall of the elevator shaft **17**. The traction sheave **7** protrudes from the hoisting machinery **6** and also from the opening **15** into the shaft **17**. The axis of rotation for shaft **17** is indicated as X. Diverting pulleys **12** placed in the top part of the shaft guide the passage of the hoisting ropes. One of the diverting pulleys **12** guides the hoisting ropes from the traction sheave **7** to the diverting pulley **13** on which the counterweight **2** is suspended and from which the hoisting ropes go further to a fixed rope anchorage at the top of the shaft. Another diverting pulley **12** guides the hoisting ropes from the traction sheave **7** to the diverting pulleys **4** and **5** attached to the car **1**, by means of which the elevator car **1** is suspended on the hoisting ropes and from which the ropes go further to a fixed rope anchorage at the top of the shaft. In the figure, the hoisting ropes are represented by their cross-sections on the traction sheave and diverting pulleys, but otherwise the ropes are not shown. At each landing, the wall of the elevator shaft **17** is provided with a door opening **18** for the landing door. The elevator car **1** is provided with a corresponding door opening **19**. If the elevator car is provided with a door, its door opening **19** is closed by the car door.

FIG. **4** presents a diagram representing an elevator with machinery above, implemented according to the invention. The hoisting unit **9** is placed beside the elevator shaft **117** in its upper part. The elevator machinery **6** is mounted in an opening **115** in the wall of the elevator shaft **117**. The opening is open towards the shaft and closed with a door **116** from the outside of the shaft. From the hoisting machinery **6** comprised in the hoisting unit, the traction sheave **7** moving the hoisting ropes **103** (depicted in broken lines) protrudes into the shaft **117**. The figure shows the portion of the hoisting ropes passing below the car **101** over diverting pulleys **104,105** and the portion going from the traction sheave towards the counterweight.

It is obvious to a person skilled in the art that different embodiments of the invention are not restricted to the examples described above, but that they may instead be varied within the scope of the claims presented below. For instance, the lay-out of the car and counterweight in the shaft is not a decisive question. It is also obvious to the skilled person that the drive shaft of the traction sheave can be provided with a support on the side facing the shaft as well, e.g. by using a support beam attached to the frame of

the hoisting machinery. The skilled person also knows that the traction sheave comprised in an elevator machinery is frequently not a fixed part of the machinery but a component which need not be mounted on its drive shaft until during installation of the elevator.

What is claimed is:

1. A traction sheave elevator system comprising:

an elevator shaft structure having at least one wall;

a plurality of guide rails;

an elevator car movable along the plurality of elevator guide rails;

a counterweight movable along a plurality of counterweight guide rails;

a set of hoisting ropes on which the elevator car and counterweight are suspended in the elevator shaft structure;

a motor having an axis of rotation oriented in the elevator shaft; and

a traction sheave driven by the motor on the axis of rotation;

the motor being flat in the direction of the drive shaft, the elevator shaft including at least one shaft wall adjacent the elevator car;

the at least one shaft wall contains a machine space being defined in the shaft wall, the motor being mounted and contained within the machine space such that the motor does not extend beyond an outer surface of the at least one shaft wall.

2. The system as defined in claim **1**, wherein the machine space is open at one side towards an interior of the elevator shaft structure and has a door at the opposite side.

3. The system as defined in claim **1** or **2**, wherein the motor is a discoidal motor and the system further comprises an instrument, said instrument panel containing equipment required for the control of and supply of power to the elevator car.

4. The system as defined in claim **3**, wherein the machine space for the motor is disposed in a lower part of the at least one shaft wall.

5. The system as defined in claim **3**, wherein the machine space for the motor is disposed in an upper part of the at least one shaft wall.

6. The system as defined in claim **3**, wherein the machine space is provided with an access restricting element.

7. A hoisting unit for a traction sheave elevator and an elevator shaft having shaft walls, the hoisting unit being mountable in the elevator shaft, the hoisting unit comprising a main portion including:

a frame,

a discoidal drive machine unit attached to the frame, and

an instrument panel attached to the frame of the hoisting unit, said frame being positioned in an opening or recess of the elevator shaft wall.

8. The hoisting unit as defined in claim **7**, wherein, in one direction, the main portion has a thickness not exceeding that of the wall, the wall being formed from a conventional cast concrete or brick.

9. A machine space in a wall defining an elevator shaft structure for a traction sheave elevator, the wall having a pair of opposed surfaces, wherein the machine space is a hole extending between the pair of opposed surfaces and is delimited in the thicknesswise direction of the wall by the plane of each of the pair of opposed surfaces, at least a portion of a drive machine unit for an elevator being positionable in the machine space, the drive machine unit

including a discoidal motor and a traction sheave with a majority of the discoidal motor being positionable within the machine space.

10. The system as defined in claim 7, wherein the shaft wall having the opening or recess has opposed surfaces with the opening or recess being contained between the opposed surfaces.

11. The system as defined in claim 10, wherein a majority of the frame is contained within the opening, in the shaft wall.

12. The system as defined in claim 10, wherein substantially all of the frame is contained within, the opening in the shaft wall.

13. The system as defined in claim 10, wherein the frame is entirely contained within the opening in the shaft wall.

14. The system as defined in claim 9, wherein the machine space contains hoisting equipment including the drive machine unit with discoidal motor which only extends from the space through one of the planes of the pair of opposed surfaces of the wall to the traction sheave.

15. The system as defined in claim 9, wherein the machine space is closed on one side thereof which side is coincident with one of the planes of the pair of opposed surfaces of the wall.

16. The system as defined in claim 9, wherein the machine space is completely closed on one side thereof which side is coincident with one of the planes of the pair of opposed surfaces of the wall.

17. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said elevator shaft including at least one substantially vertical wall defining a space between it and an adjacent elevator car, said drive assembly being mounted in said shaft and comprising:

a discoidal electric motor having a stator, a rotor, and an axis of rotation oriented in at least an extension of said space in said elevator shaft such that an extension of said axis will intersect the vertical wall; and

a traction sheave driven by said motor on said axis of rotation.

18. The invention of claim 17, wherein said drive assembly is so dimensioned as to present said traction sheave in said shaft in an extension of the space defined between said vertical wall and said elevator car adjacent to said wall.

19. The invention of claim 17, wherein said drive assembly is so dimensioned as to present said traction sheave in said shaft in an extension of the space defined between said vertical wall and said elevator car adjacent to said wall;

said shaft wall has a finite thickness;

said discoidal electric motor has a thickness along its axis of rotation no greater than said finite thickness; and
said discoidal electric motor is mounted within said shaft wall.

20. The invention of claim 19, wherein said discoidal electric motor is completely contained within said shaft wall.

21. The invention of claim 17, wherein said drive assembly is mounted entirely within said extension of said space.

22. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said drive assembly being mounted in said shaft and comprising:

a discoidal electric motor having a stator, a rotor, and an axis of rotation;

a traction sheave driven by said motor on said axis of rotation;

said elevator shaft including a shaft wall adjacent said elevator car;

said shaft wall having a finite thickness;

said discoidal motor being mounted and contained within the thickness of said shaft wall; and

said traction sheave being presented for rotation in said shaft.

23. The invention of claim 22, wherein said discoidal electric motor is completely contained within said shaft wall.

24. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said drive assembly being mounted in said shaft and comprising:

a discoidal motor having an axis of rotation oriented in said elevator shaft such that said axis will intersect an adjacent elevator car; and

a traction sheave driven by said motor on said axis of rotation;

said elevator shaft being a vertical shaft with a vertically extending boundary, the elevator shaft including a shaft wall adjacent said elevator car;

said shaft wall having a finite thickness and being adjacent the vertically extending boundary of the shaft; and
said discoidal motor being mounted and contained within the vertically extending boundary of the shaft.

25. The invention of claim 24, wherein said discoidal motor is mounted and contained within the thickness of said shaft wall.

26. The invention of claim 25, wherein said discoidal electric motor is completely contained within said shaft wall.

27. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said elevator shaft including at least one substantially vertical wall defining a space between it and an adjacent elevator car, said drive assembly being mounted in said shaft and comprising:

a discoidal electric motor having a stator, a rotor, and an axis of rotation oriented in at least an extension of said space in said elevator shaft such that an extension of said axis will intersect the plane of said vertical wall; and

a traction sheave driven by said motor on said axis of rotation;

said traction sheave drive assembly further comprising:
a counterweight being mounted in said shaft in a space defined between and edge of said shaft and said elevator car; and

a traction rope interconnected between said counterweight, said traction sheave and said elevator car.

28. The invention of claim 27, wherein said traction sheave has a diameter less than the diameter of at least one of said stator and said rotor of said discoidal motor.

29. The invention of claim 27, wherein said drive assembly is so dimensioned as to present said traction sheave in said shaft in an extension of the space defined between said shaft wall and said elevator car adjacent to said wall.

30. The invention of claim 27, wherein said drive assembly is so dimensioned as to present said traction sheave in said shaft in an extension of the space defined between said shaft wall and said elevator car adjacent to said wall;

said shaft wall has a finite thickness;

said discoidal electric motor has a thickness along its axis of rotation no greater than said finite thickness; and

said discoidal electric motor is mounted within said shaft wall.

31. The invention of claim **30**, wherein said discoidal electric motor is substantially completely contained within said shaft wall.

32. The invention of claim **27** or **28**, wherein said drive assembly is mounted entirely within said extension of said space.

33. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said drive assembly being mounted in said shaft and comprising:

- a discoidal electric motor having a stator, a rotor, and an axis of rotation;
- a traction sheave driven by said motor on said axis of rotation;
- said elevator shaft including a shaft wall adjacent said elevator car;
- said shaft wall having a finite thickness;
- said discoidal motor being mounted and contained within the thickness of said shaft wall; and
- said traction sheave being presented for rotation in said shaft;
- said traction sheave drive assembly further comprising:
 - a counterweight for and being mounted in said shaft in a space defined between an edge of said shaft and said elevator car; and
 - a traction rope interconnected between said counterweight, said traction sheave and said elevator car.

34. The invention of claim **33**, wherein said discoidal electric motor is completely contained within said shaft wall.

35. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said drive assembly being mounted in said shaft and comprising:

- a discoidal electric motor having a stator, a rotor, and an axis of rotation oriented in said elevator shaft such that an extension of said axis will intersect an adjacent elevator car;
- a traction sheave driven by said motor on said axis of rotation,
- said elevator shaft including a shaft wall adjacent said elevator car;
- said shaft wall having a finite thickness;
- said discoidal motor being mounted and contained within said shaft;
- said traction sheave drive assembly further comprising:
 - a counterweight for and being mounted in said shaft in a space defined between and edge of said shaft and said elevator car; and
 - a traction rope interconnected between said counterweight, said traction sheave and said elevator car.

36. The invention of claim **35**, wherein said discoidal motor is mounted and contained within the thickness of said shaft wall.

37. The invention of claim **36**, wherein said discoidal electric motor is completely contained within said shaft wall.

38. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said elevator shaft including at least one substantially vertical wall defining a space between it and an adjacent

elevator car, said drive assembly being mounted in said shaft and comprising:

- a discoidal electric motor having a stator, a rotor, and an axis of rotation oriented in at least an extension of said space in said elevator shaft such that an extension of said axis will intersect the plane of said vertical wall; and
- a traction sheave driven by said motor on said axis of rotation;
- said traction sheave drive assembly further comprising:
 - a counterweight for and being mounted in said shaft in a space defined between an edge of said shaft and said elevator car; and
 - a traction rope interconnected between said counterweight, said traction sheave and said elevator car;
- said elevator car including rope engaging support structures beneath same;
- said traction rope passing beneath said elevator car in engagement with said support structures and having a distal end, remote from said counterweight, attached to a fixed support structure in said shaft.

39. The invention of claim **38**, wherein said elevator car is substantially rectangular in cross-section; and

said traction rope passes diagonally beneath said elevator car.

40. The invention of claim **38**, wherein said drive assembly is so dimensioned relative to said elevator and said shaft as to present said traction sheave in said shaft in an extension of the space defined between said shaft wall and said elevator car adjacent to said wall.

41. The invention of claim **40**, wherein said elevator car and said shaft are substantially rectangular in cross-section.

42. The invention of claim **38**, wherein said drive assembly is so dimensioned as to present said traction sheave in said shaft in an extension of the space defined between said shaft wall and said elevator car adjacent to said wall;

- said shaft wall has a finite thickness;
- said discoidal electric motor has a thickness along its axis of rotation no greater than said finite thickness; and
- said discoidal electric motor is mounted within said shaft wall.

43. The invention of claim **42**, wherein said elevator car and said shaft are substantially rectangular in cross-section.

44. The invention of claim **42**, wherein said discoidal electric motor is completely contained within said shaft wall.

45. The invention of claim **44**, wherein said elevator car and said shaft are substantially rectangular in cross-section.

46. The invention of claim **45**, wherein said drive assembly is mounted entirely within said extension of said space.

47. The invention of claim **46**, wherein said elevator car and said shaft are substantially rectangular in cross-section.

48. A traction sheave drive assembly for an elevator car which minimizes the space occupied thereby in an elevator shaft, said drive assembly being mounted in said shaft and comprising:

- a discoidal electric motor having a stator, a rotor, and an axis of rotation;
- a traction sheave driven by said motor on said axis of rotation;
- said elevator shaft including a shaft wall adjacent said elevator car;
- said shaft wall having a finite thickness;
- said discoidal motor being mounted and contained within the thickness of said shaft wall;

said traction sheave drive assembly further comprising:
 a counterweight for and being mounted in said shaft in
 a space defined between an edge of said shaft and
 said elevator car; and
 a traction rope interconnected between said
 counterweight, said traction sheave and said elevator
 car;
 said elevator car including rope engaging support struc-
 tures beneath same;
 said traction rope passing beneath said elevator car in
 engagement with said support structures and having a
 distal end, remote from said counterweight, attached to
 a fixed support structure in said shaft.

49. The invention of claim **48**, wherein said elevator car
 and said shaft are substantially rectangular in cross-section.

50. The invention of claim **48**, wherein said discoidal
 electric motor is completely contained within said shaft
 wall.

51. The invention of claim **50**, wherein said elevator car
 and said shaft are substantially rectangular in cross-section.

52. A traction sheave drive assembly for an elevator car
 which minimizes the space occupied thereby in an elevator
 shaft, said drive assembly being mounted in said shaft and
 comprising:

a discoidal electric motor having a stator, a rotor, and an
 axis of rotation;

a traction sheave driven by said motor on said axis of
 rotation;

said elevator shaft including a shaft wall adjacent said
 elevator car;

said shaft wall having a finite thickness;

said discoidal motor being mounted and contained within
 said shaft;

said traction sheave drive assembly further comprising:

a counterweight for and being mounted in said shaft in
 a space defined between an edge of said shaft and
 said elevator car; and

a traction rope interconnected between said
 counterweight, said traction sheave and said elevator
 car;

said elevator car including rope engaging support struc-
 tures beneath same;

said traction rope passing beneath said elevator car in
 engagement with said support structures and having
 a distal end, remote from said counterweight,
 attached to a fixed support structure in said shaft.

53. The invention of claim **52**, wherein said discoidal
 motor is mounted and contained within the thickness of said
 shaft wall.

54. The invention of claim **53**, wherein said discoidal
 electric motor is completely contained within said shaft
 wall.

55. The invention of claim **52**, **53**, or **54**, wherein said
 elevator car and said shaft are substantially rectangular in
 cross-section.

56. The invention of claim **52**, wherein the discoidal
 motor is disposed in an upper part of the shaft wall.

57. A traction sheave drive assembly for an elevator car
 which minimizes the space occupied thereby in an elevator
 shaft, said elevator shaft including at least one substantially
 vertical wall defining a space between it and an adjacent
 elevator car, said drive assembly being mounted in said shaft
 and comprising:

a discoidal electric motor having a stator, a rotor, and an
 axis of rotation oriented in at least an extension of said
 space in said elevator shaft such that an extension of
 said axis will intersect the plane of said vertical wall;
 and

a traction sheave mounted on and directly driven by said
 rotor on said axis of rotation.

58. The invention of claim **57**, wherein said drive assem-
 bly is so dimensioned as to present said traction sheave in
 said shaft in an extension of the space defined between said
 shaft wall and said elevator car adjacent to said wall.

59. The invention of claim **57**, wherein said drive assem-
 bly is so dimensioned as to present said traction sheave in
 said shaft in an extension of the space defined between said
 shaft wall and said elevator car adjacent to said wall;

said shaft wall has a finite thickness;

said discoidal electric motor has a thickness along its axis
 of rotation no greater than said finite thickness; and

said discoidal electric motor is mounted within said shaft
 wall.

60. The invention of claim **59**, wherein said discoidal
 electric motor is completely contained within said shaft
 wall.

61. The invention of claim **57**, wherein said drive assem-
 bly is mounted entirely within said extension of said space.

62. A traction sheave drive assembly for an elevator car
 which, minimizes the space occupied thereby in an elevator
 shaft, said drive assembly being mounted in said shaft and
 comprising:

a discoidal electric motor having a stator, a rotor, and an
 axis of rotation oriented in said elevator shaft such that
 an extension of said axis will intersect an adjacent
 elevator car; and

a traction sheave mounted on and directly driven by said
 rotor on said axis of rotation;

said elevator shaft including a shaft wall adjacent said
 elevator car;

said shaft wall having a finite thickness; and

said discoidal motor being mounted and contained within
 said shaft.

63. The invention of claim **62**, wherein said discoidal
 motor is mounted and contained within the thickness of said
 shaft wall.

64. The invention of claim **63**, wherein said discoidal
 electric motor is completely contained within said shaft
 wall.

65. A method for configuring the space occupied by an
 elevator car and a drive assembly associated therewith, the
 drive assembly including a drive motor, a traction sheave, a
 counterweight, a hoisting rope, and a guide assembly, com-
 prising the steps of:

providing an elevator shaft with a vertically extending
 boundary;

placing the elevator car in said shaft;

providing at least one substantially vertical wall in the
 shaft, coextensive therewith and spaced from the eleva-
 tor car;

providing a first guide assembly in the shaft to hold and
 define a path of travel for the counterweight;

providing a second guide assembly in the shaft for the
 elevator car;

spacing said vertical wall from the elevator car to the
 extent required to accommodate the thickness dimen-
 sion of the counterweight, said guide assembly, and
 requisite safety distances, the vertical wall being adja-
 cent the vertically extending boundary of the shaft;

providing at said vertical wall a drive motor and traction
 sheave assembly with a common axis of rotation, with
 said common axis of rotation of said assembly oriented

to intersect the vertical wall while presenting the traction sheave for rotation in the space co-extensive with said shaft which is defined between the elevator car and said vertical wall, the drive motor being contained within the vertically extending boundary of the shaft; and

connecting the hoisting rope with the counterweight and the elevator car through the traction sheave.

66. The method of claim **65**, including the further step of mounting the drive motor on said vertical wall adjacent said guide assembly to present the traction sheave for rotation within the space between said vertical wall and the elevator car.

67. The method of claim **65**, including the further step of mounting the drive motor on said vertical wall adjacent said guide assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car; and

configuring the drive motor and vertical wall to contain the former within the latter.

68. The method of claim **67**, including the further step of configuring the drive motor and traction sheave assembly with a shaft having a length no greater than the spacing between the elevator car and the thickness of said vertical wall.

69. The method of claim **65**, **66**, or **67**, including the further step of configuring the drive motor and traction sheave assembly with a shaft having a length to accommodate presenting said traction sheave within the space between said vertical wall and the elevator car.

70. A method for configuring the space occupied by an elevator car and the drive assembly associated therewith, the drive assembly including a drive motor, a traction sheave, a counterweight, and a guide assembly, comprising the steps of:

constructing an elevator shaft;

placing the elevator car in said shaft;

providing at least one substantially vertical wall in the shaft, coextensive therewith and spaced from the elevator car;

providing a first guide assembly in the shaft to hold and define a path of travel for the counterweight;

providing a second guide assembly in the shaft for the elevator car;

spacing the vertical wall from the elevator car to the extent required to accommodate the thickness dimension of the counterweight and the first guide assembly;

providing at said vertical wall a drive motor and traction sheave assembly with a common axis of rotation and a substantially flat discoidal configuration, said traction sheave being directly driven by and of lesser diameter than said drive motor;

presenting the traction sheave for rotation in a space between the elevator car and the vertical wall; and

connecting the hoisting rope with the counterweight and the elevator car through the traction sheave.

71. The method of claim **70**, including the further step of mounting the drive motor on the vertical wall adjacent the first guide assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car.

72. The method of claim **70**, including the further step of mounting the drive motor on the vertical wall adjacent the first guide assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car; and

configuring the drive motor and traction sheave to present both of these in said elevator shaft in the space between the elevator car and the vertical wall.

73. The method of claim **70**, **71**, or **72**, wherein a shaft is provided along said common axis of rotation, the shaft having a length commensurate with the thickness dimensions of the counterweight and first guide assembly.

74. The method of claim **70**, **71**, or **72**, wherein said common axis of rotation is oriented to intersect the plane of said vertical wall while presenting the traction sheave for rotation in the space co-extensive with said shaft which is defined between the elevator car and said vertical wall.

75. The method of claim **74**, wherein a shaft is provided along said common axis of rotation, the shaft having a length commensurate with the thickness dimensions of the counterweight and first guide assembly.

76. A method for configuring the space occupied by an elevator car and the drive assembly associated therewith, the drive assembly including a drive motor, a traction sheave, a counterweight, a hoisting rope, and a guide assembly, comprising the steps of:

providing an elevator shaft;

placing the elevator car in said shaft;

providing at least one substantially vertical wall in the shaft, coextensive therewith and spaced from the elevator car;

providing a first guide assembly in the shaft to hold and define a path of travel for the counterweight;

providing a second guide assembly in the shaft for the elevator car;

spacing the at least one vertical wall from the elevator car only to the extent required to accommodate the thickness dimension of the counterweight, at least one of the guide assemblies, and requisite safety distances;

providing at the at least one vertical wall a drive motor and traction sheave assembly with a common axis of rotation, and configured so that said drive motor has a substantially flat discoidal stator and rotor configuration, with said common axis of rotation of said assembly oriented to intersect the plane of said vertical wall while presenting the traction sheave for rotation in a space co-extensive with said shaft which is defined between the elevator car and said vertical wall;

connecting the hoisting rope with the counterweight and the elevator car through the traction sheave; and

suspending the elevator car on the hoisting rope by passing the hoisting rope beneath the elevator car.

77. The method of claim **76**, wherein the elevator car is substantially rectangular in cross-section.

78. The method of claim **76**, including the further step of mounting the drive motor on the at least one vertical wall adjacent said guide assembly to present the traction sheave for rotation within the space between said vertical wall and the elevator car.

79. The method of claim **78**, wherein the elevator car is substantially rectangular in cross-section.

80. The method of claim **76**, including the further step of mounting the drive motor on said vertical wall adjacent said guide assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car; and

configuring the drive motor and vertical wall to contain the former within the latter.

81. The method of claim **80**, wherein the elevator car is substantially rectangular in cross-section.

82. The method of claim **80**, including the further step of configuring the drive motor and traction sheave assembly with a shaft having a length no greater than the spacing between the elevator car and the thickness of said vertical wall.

83. The method of claim **80**, wherein the elevator car is substantially rectangular in cross-section.

84. The method of claim **76**, **78**, or **80**, including the further step of configuring the drive motor and traction sheave assembly with a shaft having a length to accommodate presenting said traction sheave within the space between the at least one vertical wall and the elevator car.

85. The method of claim **84**, wherein the elevator car is substantially rectangular in cross-section.

86. A method for configuring the space occupied by an elevator car and the drive assembly associated therewith, the drive assembly including a drive motor, a traction sheave, a counterweight, and a guide assembly, comprising the steps of:

- providing an elevator shaft in a building within the profile of the latter;
- placing the elevator car in said shaft;
- providing at least one substantially vertical wall in the shaft, coextensive therewith and spaced from the elevator car;
- providing a first guide assembly in the shaft to hold and define a path of travel for the counterweight;
- providing a second guide assembly in the shaft for the elevator car;
- spacing the vertical wall from the elevator car to the extent required to accommodate the thickness dimension of the counterweight and the first guide assembly;
- providing at the at least one vertical wall a drive motor and traction sheave assembly with a common axis of rotation and a substantially flat discoidal configuration, said traction sheave being directly driven by and of lesser diameter than said drive motor;
- presenting the traction sheave for rotation in a space between the elevator car and the vertical wall; and
- connecting the hoisting rope with the counterweight and the elevator car through the traction sheave; and
- suspending the elevator car on the hoisting rope by passing the hoisting rope beneath the elevator car.

87. The method of claim **86**, wherein the elevator car is substantially rectangular in cross-section.

88. The method of claim **86**, including the further step of mounting the drive motor on the vertical wall adjacent the first guide assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car.

89. The method of claim **88**, wherein the elevator car is substantially rectangular in cross-section.

90. The method of claim including the further step of mounting the drive motor on the vertical wall adjacent the first guide assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car; and

- configuring the drive motor and traction sheave to present both of these in said elevator shaft in the space between the elevator car and the vertical wall.

91. The method of claim **90**, wherein the elevator car is substantially rectangular in cross-section.

92. The method of claim **86**, **88**, or **90**, wherein a shaft is provided along said common axis of rotation, the shaft having a length commensurate with the thickness dimensions of the counterweight and first rail assembly.

93. The method of claim **92**, wherein the elevator car is substantially rectangular in cross-section.

94. The method of claim **86**, **88**, or **90**, wherein said common axis of rotation is oriented to intersect said vertical wall while presenting the traction sheave for rotation in the space co-extensive with said shaft which is defined between the elevator car and said vertical wall.

95. The method of claim **94**, wherein the elevator car is substantially rectangular in cross-section.

96. The method of claim **86**, **88**, or **90**, wherein a shaft is provided along said common axis of rotation, the shaft having a length commensurate with the thickness dimensions of the counterweight and first guide assembly.

97. The method of claim **96**, wherein the elevator car is substantially rectangular in cross-section.

98. The method for configuring the space occupied by an elevator car and the drive assembly associated therewith, the drive assembly including a drive motor, a traction sheave, a counterweight, a hoisting rope, and a guide assembly, comprising the steps of:

- constructing an elevator shaft;
- placing the elevator car in said shaft;
- providing at least one substantially vertical wall in the shaft, coextensive therewith and spaced from the elevator car;
- providing a first guide assembly in the shaft to hold and define a path of travel for the counterweight;
- providing a second guide assembly in the shaft for the elevator car;
- spacing said vertical wall from the elevator car to the extent required to accommodate the thickness dimension of the counterweight, said guide assembly, and requisite safety distances;
- providing at said vertical wall a drive motor and traction sheave assembly with a common axis of rotation, and configured so that said drive motor has a substantially flat discoidal stator and rotor configuration, with said common axis of rotation of said assembly oriented to intersect the vertical wall while presenting the traction sheave for rotation in a space co-extensive with said shaft which is defined between the elevator car and said vertical wall; and
- connecting the hoisting rope with the counterweight and the elevator car through the traction sheave.

99. The method of claim **98**, including the further step of mounting the drive motor on said vertical wall adjacent said guide assembly to present the traction sheave for rotation within the space between said vertical wall and the elevator car.

100. The method of claim **98**, including the further step of mounting the drive motor on said vertical wall adjacent, said guide assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car; and

- configuring the drive motor and vertical wall to contain the former within the latter.

101. The method of claim **100**, including the further step of providing the drive motor and traction sheave assembly with a shaft along a common axis of rotation, the shaft having a length no greater than the spacing between the elevator car and the thickness of said vertical wall.

102. The method of claim **98**, **99**, or **100**, including the further step of providing the drive motor and traction sheave assembly with a shaft along a common axis of rotation, the shaft having a length to accommodate presenting said traction sheave within the space between said vertical wall and the elevator car.

15

103. A method for configuring the space occupied by an elevator car and the drive assembly associated therewith, the drive assembly including a drive motor, a traction sheave, a counterweight, a hoisting rope, and a guide assembly, comprising the steps of:

- providing an elevator shaft;
- placing the elevator car in said shaft;
- providing at least one substantially vertical wall in the shaft, coextensive therewith and spaced from the elevator car;
- providing a first guide assembly in the shaft to hold and define a path of travel for the counterweight;
- providing a second guide assembly in the shaft for the elevator car;
- spacing said vertical wall from the elevator car only to the extent required to accommodate the thickness dimension of the counterweight, said guide assembly, and requisite safety distances;
- providing at said vertical wall a drive motor and traction sheave assembly with a common axis of rotation, and configured so that said drive motor has a substantially flat discoidal stator and rotor configuration, with the axis of rotation of said assembly oriented to intersect the plane of said vertical wall while presenting the traction sheave for rotation in the space co-extensive with said shaft which is defined between the elevator car and said vertical wall;
- connecting the hoisting rope with the counterweight and the elevator car through the traction sheave; and
- suspending the elevator car on the hoisting rope by passing the hoisting rope beneath the elevator car.

104. The method of claim **103**, wherein the elevator car is substantially rectangular in cross-section.

105. The method of claim **103**, including the further step of mounting the drive motor on said vertical wall adjacent said guide rail assembly to present the traction sheave for rotation within the space between said vertical wall and the elevator car.

106. The method of claim **105**, wherein the elevator car is substantially rectangular in cross-section.

107. The method of claim **103**, including the further step of mounting the drive motor on said vertical wall adjacent said guide rail assembly to present the traction sheave for rotation within the space between the vertical wall and the elevator car; and

- configuring the drive motor and vertical wall to contain the former within the latter.

108. The method of claim **107**, wherein the elevator car is substantially rectangular in cross-section.

109. The method of claim **107**, including the further step of providing the drive motor and traction sheave assembly with a shaft along a common axis of rotation, the shaft having a length no greater than the spacing between the elevator car and the thickness of said vertical wall.

16

110. The method of claim **109**, wherein the elevator car is substantially rectangular in cross-section.

111. The method of claim **103**, **105**, or **107**, including the further step of providing the drive motor and traction sheave assembly with a shaft along a common axis of rotation, the shaft, having a length to accommodate presenting said traction sheave within the space between said vertical wall and the elevator car.

112. The method of claim **111**, wherein the elevator car is substantially rectangular in cross-section.

113. A method for configuring the space, occupied by an elevator car and the drive assembly associated therewith, the drive assembly including a drive motor, a traction sheave, a counterweight, a hoisting rope, and a guide assembly, comprising the steps of:

- constructing an elevator shaft;
- placing the elevator car in said shaft;
- providing at least one substantially vertical wall in the shaft, coextensive therewith and spaced from the elevator car;
- spacing the at least one vertical wall from the elevator car to the extent required to accommodate the thickness dimension of the counterweight, the guide assembly, and requisite safety distances;
- providing on said guide assembly a drive motor and traction sheave assembly with a common axis of rotation and configured so that said drive motor has a substantially flat discoidal configuration and that said traction sheave has a lesser diameter than said drive motor, with said common axis of rotation of said assembly oriented to intersect the plane of said vertical wall while presenting said traction sheave for rotation in the space coextensive with said shaft which is defined between the elevator car and said vertical wall;
- connecting the hoisting rope with the counterweight and the elevator car through the traction sheave; and
- suspending the elevator car on the hoisting rope by passing the hoisting rope beneath the elevator car.

114. The method of claim **113**, wherein the elevator car is substantially rectangular in cross-section.

115. The method of claim **113**, wherein the entirety of said drive motor and traction sheave assembly is included in the said space coextensive with said shaft.

116. The method of claim **115**, wherein the elevator car is substantially rectangular in cross-section.

117. The method of claim **131**, including the step of forming a receiving cavity within the thickness dimension of said vertical wall; and

- wherein at least a portion of said drive motor is extended into the receiving cavity formed in said vertical wall.

118. The method of claim **113**, wherein the elevator car is substantially rectangular in cross-section.

* * * * *