



US010456283B2

(12) **United States Patent**
Horgan et al.

(10) **Patent No.:** **US 10,456,283 B2**
(45) **Date of Patent:** **Oct. 29, 2019**

(54) **APPARATUS AND METHOD FOR
MAINTAINING PATENCY IN A VESSEL
ADJACENT TO NEARBY SURGERY**

(71) Applicant: **BOSTON SCIENTIFIC SCIMED,
INC.**, Maple Grove, MN (US)

(72) Inventors: **Fergal Horgan**, Co. Mayo (IE); **Adrian
McNamara**, Galway (IE); **Fionnuala
O’Gorman**, Dublin (IE)

(73) Assignee: **BOSTON SCIENTIFIC SCIMED,
INC.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 189 days.

(21) Appl. No.: **15/648,670**

(22) Filed: **Jul. 13, 2017**

(65) **Prior Publication Data**

US 2018/0014956 A1 Jan. 18, 2018

Related U.S. Application Data

(60) Provisional application No. 62/361,655, filed on Jul.
13, 2016.

(51) **Int. Cl.**
A61F 2/95 (2013.01)
A61F 2/844 (2013.01)
A61F 2/24 (2006.01)
A61M 25/04 (2006.01)

(52) **U.S. Cl.**
CPC *A61F 2/95* (2013.01); *A61F 2/2427*
(2013.01); *A61F 2/844* (2013.01); *A61F*
2002/9522 (2013.01); *A61F 2002/9528*
(2013.01); *A61F 2250/0003* (2013.01); *A61M*
25/04 (2013.01)

(58) **Field of Classification Search**
CPC *A61F 2/844*; *A61F 2/95*; *A61F 2/2427*;
A61F 2002/9522; *A61F 2250/0003*; *A61F*
2002/9528; *A61M 25/04*
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,545,390 A 10/1985 Leary
4,601,705 A 7/1986 McCoy
4,650,466 A 3/1987 Luther
4,777,951 A 10/1988 Cribier et al.
4,819,751 A 4/1989 Shimada et al.
4,986,830 A 1/1991 Owens et al.
5,041,093 A 8/1991 Chu
5,222,971 A 6/1993 Willard et al.
5,309,896 A * 5/1994 Moll *A61B 17/00234*
128/898
5,449,372 A 9/1995 Schmaltz et al.
5,554,181 A * 9/1996 Das *A61F 2/82*
606/194

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2747940 A1 2/2013

OTHER PUBLICATIONS


International Search Report and Written Opinion dated Sep. 26,
2017 for International Application No. PCT/US2017/041896.

Primary Examiner — Phong Son H Dang
(74) *Attorney, Agent, or Firm* — Seager, Tufte &
Wickhem LLP

(57) **ABSTRACT**

The disclosure pertains to an apparatus for maintaining
patency within vessels in the vicinity of surgical procedures
which might otherwise be compressed and partially or
totally occluded and methods of use therefor.

6 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,626,602 A	5/1997	Gianotti et al.	9,044,619 B2	6/2015	Hawkins et al.
5,906,590 A	5/1999	Hunjan et al.	9,050,441 B2	6/2015	Solar et al.
5,980,533 A *	11/1999	Holman A61F 2/95 606/191	9,161,834 B2	10/2015	Taylor et al.
6,013,019 A	1/2000	Fischell et al.	9,198,687 B2	12/2015	Fulkerson et al.
6,027,516 A	2/2000	Kolobow et al.	9,216,082 B2	12/2015	Von Segesser et al.
6,059,752 A	5/2000	Segal	9,220,521 B2	12/2015	Hawkins et al.
6,066,149 A	5/2000	Samson et al.	9,232,961 B2	1/2016	LeMaitre et al.
6,162,237 A	12/2000	Chan	9,242,081 B2	1/2016	Drasler et al.
6,187,054 B1	2/2001	Colone et al.	9,289,224 B2	3/2016	Adams et al.
6,231,598 B1 *	5/2001	Berry A61L 31/022 623/1.15	9,289,581 B2	3/2016	Magnuson et al.
6,368,344 B1 *	4/2002	Fitz A61F 2/95 606/108	9,339,230 B2	5/2016	Kassab
6,383,205 B1	5/2002	Samson et al.	9,351,756 B2	5/2016	Gershony et al.
6,398,758 B1	6/2002	Jacobsen et al.	9,364,254 B2	6/2016	Gershony et al.
6,458,151 B1	10/2002	Saltiel	9,375,555 B2	6/2016	Pedersen et al.
6,494,907 B1	12/2002	Bulver	9,387,098 B2	7/2016	Ferrera et al.
6,514,273 B1	2/2003	Voss et al.	9,414,852 B2	8/2016	Gifford, III et al.
6,540,768 B1	4/2003	Diaz et al.	9,421,025 B2	8/2016	Hawkins et al.
6,562,064 B1	5/2003	deBeer	9,445,829 B2	9/2016	Brady et al.
6,572,648 B1	6/2003	Klumb et al.	9,480,823 B2	11/2016	Roche et al.
6,616,689 B1 *	9/2003	Ainsworth A61F 2/915 623/1.15	9,486,188 B2	11/2016	Secrest et al.
6,645,237 B2	11/2003	Klumb et al.	9,504,807 B2	11/2016	Drasler et al.
6,660,032 B2	12/2003	Klumb et al.	9,545,323 B2	1/2017	Cully
6,673,042 B1	1/2004	Samson et al.	10,195,014 B2 *	2/2019	Lamson A61B 17/0401
6,921,414 B2	7/2005	Klumb et al.	2001/0020173 A1	9/2001	Klumb et al.
6,991,641 B2	1/2006	Diaz et al.	2001/0020182 A1	9/2001	Klumb et al.
7,004,954 B1	2/2006	Voss et al.	2001/0044621 A1	11/2001	Klumb et al.
7,128,752 B2	10/2006	Bales	2001/0051822 A1 *	12/2001	Stack A61F 2/91 623/1.11
7,618,432 B2	11/2009	Pedersen et al.	2002/0077693 A1	6/2002	Barclay et al.
7,744,620 B2	6/2010	Pedersen et al.	2003/0028245 A1	2/2003	Barclay et al.
7,766,871 B2	8/2010	Hirszowicz et al.	2003/0225444 A1	12/2003	Klumb et al.
7,875,050 B2	1/2011	Samson et al.	2004/0122466 A1	6/2004	Bales
7,931,664 B2	4/2011	Gray	2004/0153142 A1	8/2004	Klumb et al.
7,951,111 B2	5/2011	Drasler et al.	2004/0220604 A1	11/2004	Fogarty et al.
7,951,186 B2	5/2011	Eidenschink et al.	2005/0060025 A1 *	3/2005	Mackiewicz A61F 2/91 623/1.34
7,996,993 B2	8/2011	Gray	2005/0165412 A1	7/2005	Secrest et al.
8,057,396 B2	11/2011	Forster et al.	2005/0273147 A1	12/2005	Israel
8,066,757 B2	11/2011	Ferrera et al.	2006/0020324 A1 *	1/2006	Schmid A61F 2/856 623/1.16
8,070,791 B2	12/2011	Ferrera et al.	2006/0136033 A1	6/2006	Hermann et al.
8,088,140 B2	1/2012	Ferrera et al.	2006/0136034 A1	6/2006	Modesitt et al.
8,100,935 B2	1/2012	Rosenbluth et al.	2006/0136035 A1	6/2006	Hermann et al.
8,192,479 B2	6/2012	Paul, Jr.	2006/0206125 A1	9/2006	Fogarty et al.
8,197,493 B2	6/2012	Ferrera et al.	2006/0235506 A1 *	10/2006	Ta A61F 2/91 623/1.16
8,361,016 B2	1/2013	Siegel et al.	2006/0282152 A1 *	12/2006	Beyerlein A61F 2/95 623/1.11
8,366,737 B2	2/2013	Hancock et al.	2007/0016243 A1	1/2007	Ramaiah et al.
8,406,867 B2	3/2013	Kassab	2007/0173923 A1 *	7/2007	Savage A61F 2/91 623/1.15
8,460,368 B2	6/2013	Taylor et al.	2007/0219616 A1	9/2007	Modesitt et al.
8,486,014 B2	7/2013	Kelly et al.	2007/0239259 A1 *	10/2007	Boylan A61F 2/91 623/1.15
8,486,025 B2	7/2013	Solar et al.	2007/0293930 A1 *	12/2007	Wang A61F 2/91 623/1.11
8,486,102 B2	7/2013	Pedersen et al.	2008/0058856 A1	3/2008	Ramaiah et al.
8,486,104 B2	7/2013	Samson et al.	2008/0114439 A1	5/2008	Ramaiah et al.
8,491,614 B2	7/2013	LeMaitre et al.	2008/0125848 A1 *	5/2008	Kusleika A61L 29/02 623/1.11
8,574,247 B2	11/2013	Adams et al.	2010/0070015 A1 *	3/2010	Schneider A61F 2/95 623/1.11
8,574,262 B2	11/2013	Ferrera et al.	2010/0160951 A1	6/2010	Madison
8,585,594 B2	11/2013	Forster et al.	2010/0318097 A1	12/2010	Ferrera et al.
8,585,713 B2	11/2013	Ferrera et al.	2011/0082490 A1	4/2011	Connelly et al.
8,623,074 B2	1/2014	Ryan	2012/0046678 A1	2/2012	LeMaitre et al.
8,632,559 B2	1/2014	Gershony et al.	2012/0259400 A1 *	10/2012	Von Oepen A61F 2/86 623/1.11
8,652,099 B2	2/2014	Fierens et al.	2012/0271409 A1 *	10/2012	Bruszewski A61F 2/07 623/1.34
8,679,142 B2	3/2014	Slee et al.	2013/0267974 A1	10/2013	LeMaitre et al.
8,709,075 B2	4/2014	Adams et al.	2014/0214148 A1 *	7/2014	Shokoohi A61F 2/95 623/1.12
8,784,467 B2	7/2014	Connelly et al.	2016/0100855 A1	4/2016	LeMaitre et al.
8,784,480 B2	7/2014	Taylor et al.	2018/0071120 A1 *	3/2018	Sullivan A61F 2/90
8,808,237 B2	8/2014	Thielen et al.			
8,828,040 B2	9/2014	Goff			
8,900,264 B2	12/2014	Drasler et al.			
8,926,680 B2	1/2015	Ferrera et al.			
8,945,143 B2	2/2015	Ferrera et al.			
8,945,172 B2	2/2015	Ferrera et al.			
9,005,139 B2	4/2015	Klaiman et al.			
9,034,025 B2	5/2015	Sanati et al.			
9,044,618 B2	6/2015	Hawkins et al.			

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4A




Figure 4B




Figure 4C




Figure 4D




Figure 4E




Figure 5




Figure 6

1

**APPARATUS AND METHOD FOR
MAINTAINING PATENCY IN A VESSEL
ADJACENT TO NEARBY SURGERY**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application claims the benefit of priority to U.S. Provisional Application Ser. No. 62/361,655, filed Jul. 13, 2016, the entirety of which is incorporated herein by reference.

BACKGROUND

In the course of surgical interventions, particularly within the heart, the necessary insertion and manipulation of instruments and prostheses may apply pressure to adjacent structures which, when major blood vessels are located within those structures, may result in temporary partial or complete blockage of the vessels and an attendant risk of tissue damage.

For example during the transcatheter positioning of a replacement aortic valve, displacement of the native valve and/or the expansion of components of the replacement valve may incidentally apply pressure to adjacent cardiac wall tissue and thus to the vessels associated with that tissue. In the instance of aortic valve replacement, pressure may be transmitted to the left anterior descending (LAD) branch of the left coronary artery and in particular to the first septal branch of the LAD which supplies the anterior and superior critical portion of the interventricular conduction system. The blood supply to the left anterior fascicle is narrow and the fascicle is susceptible to ischemic damage and possible conduction disturbances. Damage, if it occurs, may be transient or permanent and may not be immediately apparent.

While stents, including temporary stents and steerable deployment/retrieval systems therefor are known in the art, those stents are deployed in an occluded or partially occluded coronary artery or other vessel and rely for their utility, in part, upon expansion to a diameter greater than the diameter of the vessel and/or an occluding deposit prior to introduction of the stent, the over-expansion being necessary to increase the patency of the vessel in which the stent is to be deployed.

Accordingly, a need exists for methods and appropriate apparatus for preventing, or at least minimizing, restriction of blood flow in the vicinity of surgical interventions.

SUMMARY

In certain aspects, this disclosure pertains to an apparatus for maintaining patency of a non-occluded coronary artery during nearby surgery comprising a retrievable patency maintaining element having a first compact configuration and a second expanded configuration, wherein in the second expanded configuration the retrievable patency maintaining element is sized and adapted to maintain patency of a non-occluded coronary artery while contacting opposed walls of the non-occluded coronary artery without significantly altering a diameter of the non-occluded coronary artery and further wherein the retrievable patency maintaining element is configured and adapted to sufficiently resist external collapsing forces which may be applied to the non-occluded coronary artery during nearby surgery such that patency is maintained; a steerable delivery catheter having a distal lumen sized and adapted to receive the

2

retrievable patency maintaining element in the first compact configuration and to release the retrievable patency maintaining element within the non-occluded coronary artery; and a retrieval mechanism for the retrievable patency maintaining element.

In addition or alternatively invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery comprising advancing a steerable delivery catheter having a retrievable patency maintaining element contained therein in a first compact configuration into an non-occluded coronary artery within a patient within which coronary artery patency is to be preserved; deploying the retrievable patency maintaining element in the non-occluded coronary artery, withdrawing the steerable delivery catheter a predetermined distance from the non-occluded coronary artery within which patency is to be preserved; performing surgery nearby the non-occluded coronary artery within which patency is to be preserved; retrieving the retrievable patency maintaining element from the non-occluded coronary artery using a retrieval mechanism for the retrievable patency maintaining element; and removing the retrieval mechanism for the retrievable patency maintaining element from the patient.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1, illustrates schematically the relationships between the aortic valve and a vessel to be protected against undesirable compression. Throughout the figures, heart tissue has been largely omitted or indicated in phantom for clarity.

FIG. 2 illustrates the placement of a guidewire.

FIG. 3 illustrates an aspect of use of the invention.

FIGS. 4A-4E illustrate exemplary, non-limiting forms of retrievable patency maintaining elements.

FIG. 5 illustrates schematically the function of an implanted temporarily implanted stent of the invention.

FIG. 6 illustrates an aspect of use of the invention.

DETAILED DESCRIPTION

The following description should be read with reference to the drawings wherein like reference numerals indicate like elements throughout the several views. The drawings, which are not necessarily to scale, are not intended to limit the scope of the claimed invention. The detailed description and drawings illustrate exemplary aspects of the claimed invention.

Although some suitable dimensions, ranges and/or values pertaining to various components, features and/or specifications are disclosed, one of skill in the art, informed by the present disclosure, would understand that desired dimensions, ranges and/or values may deviate from those expressly disclosed unless the context clearly indicates an intended limitation.

All numbers are herein assumed to be modified by the term "about." The recitation of numerical ranges by endpoints includes all numbers subsumed within that range (e.g., 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

As used in this specification and the appended claims, the singular forms "a", "an", and "the" include the plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term "or" is generally employed in its sense including "and/or" unless the content clearly dictates otherwise.

It is noted that references in the specification to "an aspect", "some aspects", "other aspects", etc., indicate that the aspect described may include a particular feature, struc-

ture, or characteristic, but every aspect may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same aspect. Further, when a particular feature, structure, or characteristic is described in connection with an aspect, it would be within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other aspects whether or not explicitly described unless clearly stated to the contrary.

For example, the apparatus described herein comprises a steerable delivery catheter, a retrievable patency maintaining element, and a retrieval mechanism for the retrievable patency maintaining element, each of which may be provided in any of several alternative forms. It would be unnecessarily repetitious to attempt to recite each possible combination of the elements suited to provide the respective functions of the claimed elements. Instead, it will be understood that the claimed apparatus comprises a steerable delivery catheter selected from a group of steerable delivery catheters; a retrievable patency maintaining element selected from a group of retrievable patency maintaining elements; and a retrieval mechanism for the retrievable patency maintaining element selected from a group of retrieval mechanisms for the retrievable patency maintaining elements, wherein the steerable delivery catheter is adapted to deliver the selected retrievable patency maintaining element and the retrieval mechanism is adapted to retrieve the selected retrievable patency maintaining element. It will also be understood that the retrieval mechanism may, or may not, be the same as the steerable delivery catheter.

The apparatus of the claims will be described with reference to its use during the implantation of a transcatheter aortic valve replacement and with reference to the utility of the apparatus in maintaining patency of a coronary artery, in particular a non-occluded first septal branch, located in the vicinity of the aorta which might otherwise be adversely compressed during the procedure. FIG. 1 illustrates, somewhat schematically, the implantation of a replacement aortic heart valve using a transcatheter approach. In the figure, the majority of the coronary tissue has been omitted to more clearly show the relative positions of the pertinent structures which include the aorta **10**, the atrioventricular node (AV node) **12**, the right bundle branch (RBB) **14**, the left bundle branch (LBB) **16**, the left coronary artery **20**, the left anterior descending (LAD) artery **22**, and the first septal branch **24** thereof. In addition, the figure illustrates an initial placement of a Transcatheter Aortic Valve Replacement (TAVR) device **30** and the delivery catheter **32** for the TAVR device. Although the intervening tissue has been omitted, it will be seen that the TAVR device may be juxtaposed with the arterial pathway defined by the first septal branch **24** such that incidental contact between the TAVR device **30** and the heart wall may tend to compress the first septal branch **24**. Such compression may temporarily restrict or block blood flow through the narrow first septal branch **24** with possible ischemic damage to the septum, the left anterior fascicle and to the anterior and superior critical portion of the interventricular conduction system with possible conduction disturbances. The damage may be transient or permanent. One of ordinary skill in the art is capable of assessing proposed surgical procedures with regard to likelihood that tissue compression around the surgical site will spread from the surgical site and with regard to the risk of damage from temporary compression of tissue around the surgical site and thus will be able to evaluate the term "nearby" as used herein.

In a non-limiting example of an apparatus of the invention and its use, a steerable delivery catheter **50** containing a retrievable patency maintaining element **60** in a first compact configuration may be steered to a non-occluded artery to be protected by being advanced over a guidewire **40** which has previously been advanced through an aorta **10** into a left coronary artery **20** and into a non-occluded first septal branch **24** of a left anterior descending artery **22** (FIGS. **2** and **3**). Once the steerable delivery catheter **50** has been positioned within the non-occluded first septal branch **24**, a retrievable patency maintaining element **60** of, for example, a type illustrated in FIG. **4A-E** may be deployed from a first compact configuration within the distal end of the steerable delivery catheter **50** into the non-occluded first septal branch **24**, and there may assume a second expanded configuration when deployed within the non-occluded first septal branch **24**. If desired, the steerable delivery catheter **50** may be withdrawn a predetermined distance (as shown in FIG. **3**) to a less crowded portion of the aorta **10** or even removed from the patient. In this aspect of the invention, the retrievable patency maintaining element **60** has attached thereto a wire tether **70** which remains accessible to the operator. In some alternate aspects of the invention the steerable delivery catheter **50** may be of sufficiently small cross-section that it may remain within the coronary arteries during a surgical procedure. In other aspects, the retrievable patency maintaining element **60** may be completely detached from the steerable delivery catheter **50**.

At this point, a surgical procedure, such as the implantation of a transcatheter aortic valve replacement, may be carried out in the conventional manner. The close proximity of aortic annulus to the ventricular conduction system and the susceptibility of the first septal branch **24** to inadvertent compression due to mechanical interactions before during and after prosthesis implantation, may lead to restricted blood flow and possible ischemic damage to the left anterior fascicle and/or left posterior fascicle with resultant conduction disturbances which may be transient or permanent. The retrievable patency maintaining element **60** resists collapsing forces directed toward the protected artery thereby preventing some or all of the potential ischemic damage to the conduction pathways.

Following the surgical procedure, a retrieval mechanism **80**, which may be the steerable delivery catheter **50** or a may be a separate device, is advanced to the retrievable patency maintaining element **60**, either directly or over a tether element **70**, if present, whereupon the retrievable patency maintaining element **60**, may be engaged and removed. Engagement of the retrievable patency maintaining element **60** by the retrieval mechanism **80** may, in some aspects, include withdrawing the retrievable patency maintaining element **60** at least partially within the distal end of the retrieval mechanism **80**.

In a further non-limiting example of an apparatus of the invention and its use, a steerable delivery catheter **50** containing a retrievable patency maintaining element **60** in a first compact configuration may be steered to a non-occluded artery, e.g., first septal branch **24** to be protected, by employing a steerable delivery catheter **50** of the type including a flexible tip and one or more push or pull wires. Once the steerable delivery catheter **50** has reached the non-occluded first septal branch **24**, a retrievable patency maintaining element **60** of the type illustrated in, for example, FIG. **4A** may be deployed within the non-occluded first septal branch **24** by withdrawing the steerable delivery catheter **50**, whereupon the retrievable patency maintaining element **60** expands or is expanded to a diameter not more

5

than 10% greater than the nominal diameter of the non-occluded first septal branch **24** prior to the insertion of the retrievable patency maintaining element **60**. The steerable delivery catheter **50** may then be further withdrawn a predetermined distance (See FIG. **3**) thereby largely clearing the field near the aortic valve so that the implantation of a transcatheter aortic valve replacement device **30**, may be carried out in the conventional manner.

As may be seen in FIG. **5**, the presence of a retrievable patency maintaining element **60** within first septal branch **24**, or other susceptible vessel, reduces or prevents obstruction of the vessel by compression of tissue adjacent to a site of incidental compression of coronary tissue near the non-occluded first septal branch **24** will be resisted, thereby maintaining patency of the non-occluded first septal branch **24**.

A steerable delivery catheter **50** of the invention may be actively steered or may be passively steered by being advanced along a previously positioned guidewire **40**. An actively steered catheter may, for example, be of the type including a flexible tip and one or more push or pull wires (exemplified by U.S. Pat. No. 5,906,590); of the type including a plurality of thermally activated deflection elements (exemplified by U.S. Pat. No. 4,601,705); of the type employing rotation of a rigid torsional element, such as a bent guidewire, to direct the curved distal end selectively (exemplified by U.S. Pat. No. 4,545,390); and of the type employing electroactive polymers (exemplified by U.S. Pat. No. 7,951,186), each incorporated by reference, among others known in the art.

A suitable retrievable patency maintaining element **60** generally has the form of a temporarily implantable stent of the art which has been adapted for the current purpose by limiting the degree of expansion such that the stent may contact the walls of the unobstructed coronary artery in which it is deployed without significantly altering the diameter of the artery. One of ordinary skill in the art will appreciate that an artery is not significantly altered if the diameter increase is limited to no more than 0%, 1%, 2%, 4%, or 10%. The retrievable patency maintaining element **60** is adapted and configured for the current purpose by the choice of materials and or the inclusion of structure which resists deformation of the retrievable patency maintaining element **60** when external vessel collapsing forces are applied to the region of the vessel containing the retrievable patency maintaining element **60**. Structural modifications may include bridging elements which employ tension and/or compression to preserve the generally cylindrical shape of the retrievable patency maintaining element **60**.

Non-limiting examples of suitable retrievable patency maintaining elements **60** include a helical balloon **62A** (see FIG. **4A**), exemplified in U.S. Pat. No. 7,766,871; an inflatable balloon cage **62B** (see FIG. **4B**), the balloons optionally including a check-valve (not shown) and a detachable inflation lumen **62C**; a helical ribbon coil **64** (FIG. **4C**), exemplified in, for example, U.S. Pat. No. 6,027,516; a coiled sheet **66** (FIG. **4D**), exemplified in, for example, U.S. Pat. No. 6,027,516; an expandable slotted tube **68** (FIG. **4E**), exemplified in, for example, U.S. Pat. No. 6,013,019. Other devices such as expandable wire or polymeric braids may also be used. Suitable retrievable patency maintaining elements **60** may be self-expanding or may be actuated to attain their expanded configuration in a conventional manner.

In some aspects, a retrievable patency maintaining element **60** is released within the coronary artery to be protected and held in position by one or more wall engaging features (not shown). In other aspects, a retrieval mechanism

6

80 may engage a proximal portion of the retrievable patency maintaining element **60** to allow it to be pulled within the retrieval mechanism **80** or may suitably elongate the retrievable patency maintaining element **60** thereby reducing its diameter to allow its removal. In certain aspects, the retrievable patency maintaining element **60** has attached thereto a tether **70** which facilitates retrieval of the retrievable patency maintaining element **60** by guiding a retrieval mechanism **80** to the retrievable patency maintaining element **60** and providing a tensile force adapted to pull the retrievable patency maintaining element **60** within the distal end of the retrieval mechanism **80** or allowing the retrieval mechanism **80** to be advanced over the retrievable patency maintaining element **60**. Any of a variety of engagement mechanisms known in the art may be used.

A tether **70**, if present, may also serve to maintain the position of the retrievable patency maintaining element **60** within the coronary artery during the surgical procedure. Tether(s) **70**, if present may be, for example, a suture, a braid, or a wire.

In yet other aspects, a retrieval mechanism **80** adapted to function with a balloon retrievable patency maintaining element **60** may include a check-valve release or other balloon deflating feature. As noted previously, in certain aspects, the steerable delivery catheter **50** may be configured and adapted to serve as a retrieval mechanism **80**.

GLOSSARY OF ELEMENTS OF THE DRAWINGS

- 10** Aorta
- 12** Atrioventricular node (AV node)
- 16** Left bundle branch (LBB)
- 20** Left coronary artery
- 22** Left anterior descending (LAD) artery
- 24** First septal branch artery
- 30** Transcatheter Aortic Valve Replacement device (TAVR)
- 32** TAVR device delivery catheter
- 40** Guidewire
- 50** Steerable delivery catheter
- 60** Retrievable patency maintaining element
- 62A-68** Variations of retrievable patency maintaining element **60**
- 70** Tether
- 80** Retrieval mechanism

In certain aspects, this disclosure pertains to an apparatus for maintaining patency of a non-occluded coronary artery during nearby surgery comprising a retrievable patency maintaining element having a first compact configuration and a second expanded configuration, wherein in the second expanded configuration the retrievable patency maintaining element is sized and adapted to maintain patency of a non-occluded coronary artery while contacting opposed walls of the non-occluded coronary artery without significantly altering a diameter of the non-occluded coronary artery and further wherein the retrievable patency maintaining element is configured and adapted to sufficiently resist external collapsing forces which may be applied to the non-occluded coronary artery during nearby surgery such that patency is maintained; a steerable delivery catheter having a distal lumen sized and adapted to receive the retrievable patency maintaining element in the first compact configuration and to release the retrievable patency maintaining element within the non-occluded coronary artery; and a retrieval mechanism for the retrievable patency maintaining element.

In addition or alternatively the invention relates to an apparatus, wherein the steerable delivery catheter employs an initially positioned guidewire which serves to steer the steerable delivery catheter to a deployment site.

In addition or alternatively the invention relates to an apparatus, wherein the steerable delivery catheter employs a catheter which has a deflectable tip.

In addition or alternatively the invention relates to an apparatus, wherein the steerable delivery catheter and the retrieval mechanism are the same catheter.

In addition or alternatively the invention relates to an apparatus, wherein the steerable delivery catheter and the retrieval mechanism are different catheters.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element maintains a connection to the steerable delivery catheter during the nearby surgery.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element maintains a connection to the steerable delivery catheter through at least one of a tether, an activation link, and an inflation tube.

In addition or alternatively the invention relates to an apparatus, wherein the tether or the activation link is a suture, a braid, or a wire.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element maintains a connection to the retrieval mechanism during the nearby surgery.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element maintains a connection to the retrieval mechanism through at least one of a tether, an activation link, and an inflation tube.

In addition or alternatively the invention relates to an apparatus, wherein the tether or the activation link is a suture, a braid, or a wire.

In addition or alternatively the invention relates to an apparatus, wherein retrievable patency maintaining element is an inflatable element which includes a check valve.

In addition or alternatively the invention relates to an apparatus, wherein retrievable patency maintaining element is an expandable helical wire stent.

In addition or alternatively the invention relates to an apparatus, wherein retrievable patency maintaining element is an expandable laser cut tubular stent.

In addition or alternatively the invention relates to an apparatus, wherein retrievable patency maintaining element is an initially coiled sheet of an elastomeric material.

In addition or alternatively the invention relates to an apparatus for maintaining patency of a non-occluded coronary artery during nearby surgery comprising a retrievable patency maintaining element having a first compact configuration and a second expanded configuration, wherein in the second expanded configuration the retrievable patency maintaining element is sized and adapted to maintain patency of a non-occluded coronary artery while contacting opposed walls of the non-occluded coronary artery without significantly altering a diameter of the non-occluded coronary artery and further wherein the retrievable patency maintaining element is configured and adapted to sufficiently resist external collapsing forces which may be applied to the non-occluded coronary artery during nearby surgery such that patency is maintained; a steerable delivery catheter having a distal lumen sized and adapted to receive the retrievable patency maintaining element in the first compact configuration and to release the retrievable patency

maintaining element within the non-occluded coronary artery; and a retrieval mechanism for the retrievable patency maintaining element.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element maintains a connection to the retrieval mechanism during the nearby surgery.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element maintains a connection to the retrieval mechanism through at least one of a tether, an activation link, and an inflation tube.

In addition or alternatively the invention relates to an apparatus, wherein the tether or the activation link is a suture, a braid, or a wire.

In addition or alternatively the invention relates to an apparatus, wherein the inflation tube includes a valve adapted to control flow of fluid during inflation, an implantation interval, and/or deflation of the retrievable patency maintaining element.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element is expanded from the first compact configuration to the second expanded configuration by at least one of relative motion between the tether and the steerable delivery catheter; relative motion between the activation link and the steerable delivery catheter; and introduction of a fluid through the inflation tube and a valve.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element is self-expanding from the first compact configuration to the second expanded configuration.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element is formed from a shape memory material.

In addition or alternatively the invention relates to an apparatus, wherein the shape memory material is Nitinol.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element is a balloon.

In addition or alternatively the invention relates to an apparatus, wherein the retrievable patency maintaining element is a collapsible cage-like structure.

In addition or alternatively the invention relates to an apparatus, wherein the steerable delivery catheter includes the retrieval mechanism for the retrievable patency maintaining element.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery comprising advancing a steerable delivery catheter having a retrievable patency maintaining element contained therein in a first compact configuration into a non-occluded coronary artery within a patient within which coronary artery patency is to be preserved; deploying the retrievable patency maintaining element in the non-occluded coronary artery, withdrawing the steerable delivery catheter a predetermined distance from the non-occluded coronary artery within which patency is to be preserved; performing surgery nearby the non-occluded coronary artery within which patency is to be preserved; retrieving the retrievable patency maintaining element from the non-occluded coronary artery using a retrieval mechanism for the retrievable patency maintaining element; and removing the retrieval mechanism for the retrievable patency maintaining element from the patient.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary

artery during nearby surgery, wherein the withdrawing step further includes maintaining a connection between the retrievable patency maintaining element and the steerable delivery catheter or a retrieval mechanism.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery, wherein maintaining a connection between the retrievable patency maintaining element and the steerable delivery catheter or a retrieval mechanism is through at least one of a tether, an activation link, and an inflation tube.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery, wherein the tether or the activation link is a suture, a braid, or a wire.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery, wherein the inflation tube includes a valve adapted to control flow of a fluid during inflation, an implantation interval, and/or deflation of the retrievable patency maintaining element.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery, wherein the withdrawing step does not include maintaining contact between the retrievable patency maintaining element and the steerable delivery catheter or a retrieval mechanism.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery, wherein the retrieving step includes advancing the retrieval mechanism along the connection between the retrievable patency maintaining element and the steerable delivery catheter or a retrieval mechanism.

In addition or alternatively the invention relates to a method of preserving patency in a non-occluded coronary artery during nearby surgery, wherein the retrieving step is performed without relying upon a connection between the retrievable patency maintaining element and the retrieval mechanism.

Although the illustrative examples described above relate to cardiac surgery and in particular to surgery in the vicinity of an aortic valve, the use of the methods and apparatus disclosed in other tissue is also contemplated.

Various modifications and alterations of this invention will become apparent to those skilled in the art without departing from the scope and principles of this invention, and it should be understood that this invention is not to be unduly limited to the illustrative embodiments set forth hereinabove. All publications and patents are herein incorporated by reference to the same extent as if each individual publication or patent was specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A method of preserving patency in a non-occluded coronary artery during nearby surgery comprising:
 - advancing a steerable delivery catheter having a retrievable patency maintaining element contained therein in a first compact configuration into a non-occluded coronary artery within a patient within which coronary artery patency is to be preserved;
 - deploying the retrievable patency maintaining element in the non-occluded coronary artery;
 - withdrawing the steerable delivery catheter a predetermined distance from the non-occluded coronary artery within which patency is to be preserved;
 - performing surgery nearby the non-occluded coronary artery within which patency is to be preserved;
 - retrieving the retrievable patency maintaining element from the non-occluded coronary artery using a retrieval mechanism for the retrievable patency maintaining element;
 - removing the retrieval mechanism for the retrievable patency maintaining element from the patient wherein the withdrawing step further includes maintaining a connection between the retrievable patency maintaining element and the steerable delivery catheter or a retrieval mechanism; wherein maintaining a connection between the retrievable patency maintaining element and the steerable delivery catheter or a retrieval mechanism is through at least one of a tether, an activation link, and an inflation tube; and wherein the inflation tube includes a valve adapted to control flow of a fluid during inflation, an implantation interval, and/or deflation of the retrievable patency maintaining element.
2. The method of claim 1, wherein the withdrawing step further includes maintaining a connection between the retrievable patency maintaining element and the steerable delivery catheter or the retrieval mechanism.
3. The method of claim 2, wherein maintaining a connection between the retrievable patency maintaining element and the steerable delivery catheter or the retrieval mechanism is through at least one of a tether, an activation link, and an inflation tube.
4. The method of claim 1, wherein the withdrawing step does not include maintaining contact between the retrievable patency maintaining element and the steerable delivery catheter or the retrieval mechanism.
5. The method of claim 1, wherein the retrieving step includes advancing the retrieval mechanism along the connection between the retrievable patency maintaining element and the steerable delivery catheter or a retrieval mechanism.
6. The method of claim 1, wherein the retrieving step is performed without relying upon a connection between the retrievable patency maintaining element and the retrieval mechanism.

* * * * *